

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED
OMB No. 1004-0137
Expires: March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE- Other instructions on reverse side.

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other2. Name of Operator
BOPCO, L. P.3a. Address
P. O. Box 2760, Midland, TX 797023b. Phone No. (include area code)
432-683-22774. Location of Well (Footage, Sec., T., R., M., or Survey Description)

NENW, UL C, 620' FNL, 2000' FWL, Lat: N 32.179764, Long: W 103.8706
SWNE, UL G, 1950' FNL, 1950' FEL, Sec 28, T24S-R30E

5. Lease Serial No.

BHL: NMNM 0002862

6. If Indian, Allottee or Tribe Name

See pg 1 of 8pt DP for lease info.

7. If Unit or CA/Agreement, Name and/or No.

Poker Lake Unit NMNM 71016X

8. Well Name and No.

Poker Lake Unit 367H

9. API Well No.

30-015-40927

10. Field and Pool, or Exploratory Area

Nash Draw (Del., BS, Avalon Sand)

11. County or Parish, State


Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Please see attachment for revisions.

14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

Christopher Volek

Title Drilling Engineer

Signature

Date

12/26/2012

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

APPROVED

Approved by

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title

Office

Date

DEC 26 2012

Is/ Chris Walls

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly, and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2).

1/14/2013

Accepted for record
NMOCD

BOPCO, L.P. requests to plug and abandon PLU #367H on 12/24/2012 due to surface hole collapse while attempting to drill out from the conductor. This will be accomplished by running 1" tubing to a depth of 95' and filling the 20" conductor and rat hole from a depth of 116' to surface with 375 sacks of class 'C' cement and then capping the conductor with a steel plate. The properties of the class 'C' cement are as follows; density = 14.8 ppg, yield = 1.33 cuft/sack, total volume = 495 cuft. McVay #5 will then skid 50' in the v-door direction and attempt to re-spud on the same drilling location.