

Submit 1 Copy To Appropriate District Office,  
District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised August 1, 2011

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-015-40753
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Mirage 30 PM State Com
8. Well Number 1H
9. OGRID Number 14744
10. Pool name or Wildcat Winchester; Bone Spring 65010

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
Mewbourne Oil Company

3. Address of Operator  
PO Box 5270 Hobbs, NM 88241

4. Well Location

Unit Letter P : 300 feet from the South line and 150 feet from the East line  
Section 30 Township 19S Range 29E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3311 GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☒

OTHER: ☐


13. Describe proposed or completed operations. (Clearly state all pertinent details; and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

01/29/13..MI & spud 17 1/2" hole. TD'd hole @ 330'. Ran 330' of 13 3/8" 48 H40 ST&C csg. Cemented with 180 sks Thixad Class H with additives. Mixed @ 14.6 /g w/ 1.49 yd. Tail with 400 sks Class C w/2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 11:45 AM 01/30/13. Did not circ cement. Slow rate lift pressure @ 90# @ 3 BPM. WOC 6 hrs. Ran temperature survey indicating TOC @ 125'. PU 1" pipe & tag @ 116'. Cmt in 5 stages with 189 sks Class H. Mixed @ 14.6#/g w/1.49 yd. At 9:00 PM 01/31/13, tested BOPE & csg to 1250# for 30 minutes, held OK. Drilled out with 12 1/4" bit.

Copy of the temperature survey attached.

Spud Date: 01/29/2013

Rig Release Date:



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 02/04/13

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: Al Wade TITLE Dist. & Supervisor DATE 2/5/13

Conditions of Approval (if any):

*JMD*

Mewbourne Mirage 30 pm St. com. #1h  
T.O.C. 125' 1-30-13

