				RECEI	VED							
Form 3160-5 (August 2007)		UNITED STATES TMENT OF THE IN OF LAND MANAG	ITERIOR	APR 10 OCD Artesia		OMB NO	APPROVED 0. 1004-0135 July 31, 2010					
c			5. Lease Serial No. NMLC029395B									
Do i	not use this for	m for proposals to se form 3160-3 (API	6. If Indian, Allottee of	Tribe Name								
SUBI	MIT IN TRIPLIC		7. If Unit or CA/Agree	ment, Name and/or No).							
 Type of Well Øil Well Gas 	Well 🔲 Other	8. Well Name and No. TURNER B 101										
2. Name of Operator LINN OPERATING	INC.		9. API Well No. 30-015-26695									
3a. Address 600 TRAVIS STRE HOUSTON, TX 77	002		Ph: 281-84	o. (include area code) 40-4272		10. Field and Pool, or Exploratory LEONARD;QUEEN, SOUTH						
4. Location of Well (For	otage, Sec., T., R., N	1., or Survey Description)	1			11. County or Parish, and State						
Sec 20 T17S R31E 32.824565 N Lat, 10			EDDY COUNTY, NM									
12. CHI	ECK APPROPF	LATE BOX(ES) TO	INDICATE	ENATURE OF N	NOTICE, RE	PORT, OR OTHER	R DATA					
TYPE OF SUBMIS	SION	ACTION										
X Notice of Intent		Acidize	Dee	pen cture Treat	—	on (Start/Resume)	U Water Shut-Off					
Subsequent Report	Subsequent Report				Reclamat		Well Integrity Other					
Final Abandonmen		Casing Repair Change Plans	☐ New Construction ☐ Recomp ☑ Plug and Abandon ☐ Tempor			prarily Abandon						
		Convert to Injection	Plug Back U Water D			-						
following completion of testing has been complet determined that the site i PROPOSED PLUG 1. MIRU PLUGGIN 2. SET CIBP @ 270 3. SPOT 20 SX CE 4. SPOT 20 SX CE 5. SPOT 20 SX CE 5. SPOT 20 SX CE 14. I hereby certify that the	the involved opera ed. Final Abandon s ready for final ins GING AND ABA G EQUIPMENT 00'. CIRC HOL MENT @ 1250- MENT @ 1250- MENT @ 417-2 <u>MENT</u> @ 417-2	NDONMENT PROC NDWH. NU BOP. W/MUD LADEN F 1050'. WOC & TAG $\overline{05'}$. $\overline{06}$ $\overline{06}$ 17'. WOC & TAG. 17'. WOC & TAG. 17'. WOC & TAG. 17'. For LINN OF mmitted to AFMSS for	ults in a multip d only after all EEDURES: POH W/ PF LUID. SPOT	ROD EQUIP. 20 SX CMT ON 20 SX CMT ON 4 by the BLM Well IC., sent to the Ca by KURT SIMMON	TOP OF CIE SEE CO Unformation S Information S Information S Son 03/27/2	winterval, a Form 3160 have been completed, a RECLAMA A BP. Accortec NM E ATTACHED NDITIONS OF ACCORTECTIONS NDITIONS OF ACCORTECTIONS NDITIONS OF ACCORTECTIONS NDITIONS OF ACCORTECTIONS NDITIONS OF ACCORTECTIONS NDITIONS OF ACCORTECTIONS NDITIONS OF ACCORTECTIONS NDITIONS OF ACCORTECTIONS NDITIONS OF	TION PROCEDUR TACHED for record FOR APPROVA	e 4/4/13				
Name(Printed/Typed)	TERRY B CALL	AHAN		Title REGUL	ATORY SPE			<u> </u>				
Signature	(Electronic Submis			Date 03/26/20			<u></u>					
		THIS SPACE FO				E						
Approved By	mer G	? Como	<u> </u>	Title 5	EPS		4-8- Date	73				
Conditions of approval, if any certify that the applicant holds which would entitle the applic	s legal or equitable ant to conduct oper	itle to those rights in the ations thereon.	subject lease	Office LFC			······					
Title 8 U.S.C. Section 1001 a States any false, fictitious or	and Title 43 U.S.C. fraudulent stateme	Section 1212, make it a c nts or representations as t	rime for any pe o any matter w	rson knowingly and thin its jurisdiction.	willfully to mak	e to any department or a	gency of the United	_				

** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED **

Additional data for EC transaction #202531 that would not fit on the form

32. Additional remarks, continued

ъ т

6. SPOT 10 SX CEMENT SURFACE PLUG. 60'- 5 cu-F.

7. CUT OFF WELLHEAD AND WELD ON DRY HOLE MARKER.

Verify and to Suitace all annulus.

Well Nume: APT No. Sourd Date: WOD Update: WOD Start: Carment Blend: Carment Blend: Int Cart Int Cart Carment Blend: Carment Blend: Carment Blend: Cartell of Perforati TOC U. Grayburg: Mater: Carsyburg: Carsyburg:	Prement 2995 Unit 2017 2016 Unit 2017 2017 <th>Hole Stee: 71/6' Expective (beb/th): 5-1/2' atas 1-55, (RW-RHC3 5T&C Connext Blend: 5-1/2' atas 1-55, (RW-RHC3 5T&C Arburn: Cmi w/ 800 at Nall C1 °C cmi. Circ 125 as to ph Arburn: 7-1/6' Arburn: 7-1/6' Arburn: 7-1/6' Poile Star 2-1/2' Poile Star 2-1/2' Poile Star 2-1/2' Poile Star 2-1/2' Poile Star 102 Poile Star 102 Poile Star 102 Poile Star 103.2 Poile Star 0.4% Malad 32.2 Poile Star 0.4% Malad 32.2</th>	Hole Stee: 71/6' Expective (beb/th): 5-1/2' atas 1-55, (RW-RHC3 5T&C Connext Blend: 5-1/2' atas 1-55, (RW-RHC3 5T&C Arburn: Cmi w/ 800 at Nall C1 °C cmi. Circ 125 as to ph Arburn: 7-1/6' Arburn: 7-1/6' Arburn: 7-1/6' Poile Star 2-1/2' Poile Star 2-1/2' Poile Star 2-1/2' Poile Star 2-1/2' Poile Star 102 Poile Star 102 Poile Star 102 Poile Star 103.2 Poile Star 0.4% Malad 32.2 Poile Star 0.4% Malad 32.2
Melibore Diagram		
Weil Name. Turner B. 201'. Footate: D.20-175-31E 990 FNL 1350 FNL. Footate: D.20-175-31E 990 FNL 1350 FNL. Footate: D.20-175-31E 990 FNL 1350 FNL. Section: 20 Genery: 64/Con. Genery: 132 81 565 (NULOT Such - TD, DUL/MSR. 1247 to TD, AMS 1243 - TD, Creatiook 1241 - TD, Creatiook 1241 - TD, Creatiook 1243 - TD, Creationk 1243 - TD, Creationk 1244 - TD, Creationk 1243 - TD, Creationk 1243 - TD, Creationk 1243 - TD, Creationk 1244 - TD,	7/3/1991 Perfd 15 faller w/ 1 55/32. hold per ft. Perfd 2011,31',15', 37', 44', 45', 48' 7/10/1991 found 95 TD (# 151/91, 45', 55', 15 data). Found 16 TD (# 151/91, 55', 55', 15 data). 7/10/1991 found 95 TD (# 151/91, 55', 55', 15 data). Found 16 TD (# 151/91, 55', 55', 15 data). Actuation with the static. Actuation with the static. Actuation with the static. 2/11/2012 Swah tert Sturbine new - perf 3500' - 3556' (1 hole). Found 16 TD (# 151/91, 55') 2/11/2012 Swah tert Sturbine new - perf 3500' - 3556' (1 hole). Found 15 Sturbine new. OR obtain. 2/11/2012 Swah tert Sturbine new - perf 3500' - 3556' (1 hole). Found 15 Sturbine new. OR obtain. 2/11/2012 Swah tert Sturbine new - perf 3500' - 3501' (1 hole). Found 15 Sturbine new. OR obtain. 2/11/2012 Swah tert Sturbine new - perf 3501' - 3506' (1 hole). Found 15 Sturbine new. OR obtain. 2/11/2012 Swah tert Sturbine new - perf 3501' - 3506' (1 hole). Found 15 Sturbine new. OR obtain. 2/11/2012 Swah tert found 15 Sturbine new. JSS Actual new Sturbine. JSS Actual new 12 Sturbine new - perf 301' - 306' (fould 15 much new. JSS Actual new Sturbine 15 Sturbine. 2/11/2012 Swah tert found new 2001' - 306' (fould 5 much new. JSS Actual new 25 Actual New 25 Not. JSS Actual New 2000' 12 Not. 2/11/2012	Nota Vacuum zone - perf 1010' - 105' (0 new hole, & 6 de hole), Toil of 6 volts runs. Final Swab runs. 105K oil, S 10ku, S van Biulid 100, 100% oil terminden huds 10% oile. 02/16/32 Acidited Vacuum zone 1017'- 105' (14 halan) w/ 1500 oil 15% hufe avit. Fize Vacuum perf 1010'- 105' 02/15/32 Acidited Vacuum zone 1017'- 105' (14 halan) w/ 1500 uil 11/00 uil. Ruho to perf. 02/15/37 Fatted Vacuum zone 1017'- 105' (14 halan) w/ 1500 uil 11/00 uil. Ruho to perf. 02/15/36 Fatted Vacuum 2014''S and Strath visa down itom 1/2006. 2/2000 02/11/100 Under terk - 10 18 had pint. 02/11/200 Tested 44 hole www. 02/11/200 Under terk - 10 18 had pint. 02/11/200 Under terk - 10 18 had pint.

1 1 5 5 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	201 1 1 4 4 5 5 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	.9 © 551 /	00 ACC' / C 025 Ro L Cur 05 100: b. Helester 121/4" in Cur 5 8 2.44155 p0 6	6)end: Cmt w/ 600 cmt w/ 14.6 Surface	L <u>el Parficialions</u> tudure. 2723. 43 4. Vibure. 2761. 15 2793. 2800	LG 12 23 .2918.24 Prem 2481.61.25 6.90 Va 29991,3030 6140 holet, 305 (16 hol 1 2 311,31"3 ,39 44 46 0"95 104 Lovi 1 321 / 14"6 6	Jack '. 0'. 2, '.55 56 7,63 66 69,92' '. '' ''.' Li '' Si '' Si '' '.' '' '.' '' '.' '' '' '' '' '' '' '' '' '' '' '' '' '' '' '' '' '' '' '' '' '' '' '' '' '' '' '' '' '' '' '''	в. В. П.		d · · 0 tri (m) top a CBP			Hole size 77/8 Lind Cut: 5.1/2 Jan. J.55.ER RNG3 574CC Competity Publich Comment Dublich Com Ruber Land Crown Currit 3. 4 (10 mil		Hole Sile 7.7.8 Hood Cage 5.1.2 II ; 55 ER ANG3 57 & C Copacty (bX/M) 3500 gai uuperfluch 102 Prefituch 2020	d Cement Blo	r kurmensister a. 250 sti fål prem plustom v/10 M. soband/sus 5. salt å 0. % Halad 322. Cmt wi 15 32 gal	
	<u>Proposed</u> Weilbore Diagram	5001 10 LT 10 LT 10 LT 10 LT 10 LT	۲. ۳.		59 59 6		540 0 CM 61350 050 (M			CIBP citulated w/ mud lad		- 	- 303 · 56 3043 · 52	2007E 0	92 43		, , , , , , , , , , , , , , , , , , ,	s d satur
Turner B 101*			: 312/345578 - 0. 67 902005 Gabur Maken Boont: 5pet 0 ton om 7 1/7 3656 Mc 11	kw. ? Lesether Acher Manuella: (6/15 C L/LDT Surf TO, DLL/M 5 7 C, beer k.1243 TD	и. a 67 Run JS a 13 H.1 7 Стич 400 цк H. GTC tmt. Clic 108 testo Dri. 12.1.4. I a 12.46 Run 12.35 a 15.5 c 6 Стич 800 ц. 8.0.1°C tmt. Clic 12.5 це 1.5.5 c 6 Dri. 77.8. h. a 857. Кал 36.44.5.1.2.144 ст. 3. °. Ст	w 11.00 tastyl Cl°C cmh. Clir 75 tasto li Perfol 6 hol 15 32'holde rith Perf 5 3 3 ' 8' 5 95' 98' 36.00' 1 ' 8' 10'10' 10'10'10'10'10'10'10'10'10'10'10'10'10'1	9 Found PBID 2819'S 5 read access Nr. nt 3 35 to 6 holes Audiare wood 3155 Khee add. 3795'3 holes 1 tiof 6 tweb runt. Record 1 wr Swebiert Shurchier zone 3741 3745'2 holes 1 tiof 6 tweb runt. Record 1 wr 13 Swebiert Shrizone 1741 3745'2 holes 1 tiof 6 tweb runt. Of oilcut. Swebiert Shrizone on 3741 3745'3 holes 1 tot of 5 sweb runt. Of oilcut. Swebierd w no fluid enti , Wull Rescad on 7 13 2	93 Swath htr art 3586* 3590* 3 holes. Tot! 5 wash runt % cal Accidences htr arf 3586* 3590* 3 hies. Prum 300° at % 100 accid swath strint rif 3586* 3590* 3 holes. Totil 6 wash user 10% of Gardine Varcuum erf 3048* 3031 8 holes ar 750 al 15% c.d. Swath Varcuum erf 3048* 3031 8 holes. Totil 6 fewath % 4.20% clicul Waited 30 min. Final tweat run 20-30% clicul.	23 Bird weit dwar flowed 100% of for 1 min foem Vacuum erf 3 11 - 3048' Sweeb Vacuum nom if 3031, 3048' tott Bholes. Tot sweeb unst. 15 oil ut Frev Vacuum 13031' 3048' tott Bholes w 15 000 al trosstilnkeef etc. n 23 8008 20 d 5 naf 8 Bood 202 202 Mar. Flanh to if Ta st dw 23 MCI Inform I as resta0708' A rest35548 Min rest352 # 19 1388.	92 R Pon Z1 Sith Sith Sith Veb PB1D 3700°. Ran after Frs to t at a findium w while has sand had been ta ed. Lo khowed maorit of trimt had stated in Vacuum r13031'. 3045° w totilistervant at aled from 13951 - 3654°. 92 Rill w pr th rocks and m., RTP.	93 wab Va um zone 1/303 43' 8h les Torl 9 wab run Final wab run 27% oil u. Acidit Vacuum ari 3031' 3045' totl 8 holestw/1500 ga 15 Nefe ac d. Swib Va uum zone atter a idin peri 3031 - 3045' totl 8 holesti. Totl 7 web ruen. 375 % okcur.	23 Sweb Sta hterione 3566' Toti3 tweb nun. o ut. Trace off cut 29 Ritt Pe Vacuum tone 302 30410 3043 - 3052 w 4.5 Tot D.4 ia a w 17 29 Jaintital . Tracer Survey Showed all fueld going no top perf& going p. Does nos spopear has main 24 unun 2 wastreated.					Acting the state of the second state of the construction and the second state of the state of the se	r Han Polson . Mutakmotok a Kiz TA . Let BP RIH.w. C.B. 2571 5. aboveto erfs. 2721. Rikk.w. Zerschni land on CiBP. Ran Mittw. um. truck witnessed Blakt Heidfols.
	بو ۳	to k. rve : ount :	2 7.8 	k w	ۍ ۲	5	56 013	766	265	2001 1 2001/81	199 E	1991/1E 1991/21	16/3 2	2661/12	35/95 2 12/00	2 8	00/ 00/(1 1 1 3 1 2	12/11 12 14

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. <u>Notification</u>: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. <u>Mud Requirement</u>: Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.

5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. <u>Show date well was plugged</u>.

8. <u>Trash</u>: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

J. Amos 3/6/11

Requirements for ground level dry hole markers <u>Well Identification Markers</u> Conditions of Approval (COA)

The BLM Carlsbad Field Office (CFO) Conditions of Approval (COA) Requires that ground level dry hole markers be placed on well within the Lesser Prairie Chicken habitat area. The dry hole markers will be to the following specifications. The operator will construct the markers as follows:

- 1. An 8 inch X 8 inch steel plate 1/8 to 3/16 of an inch thick is to be placed on the old dry hole marker stand pipe 2 inches from ground level, in the Lesser Prairie Chicken habitat area.
- 2. Steel plate may be welded or bolted approximately 2 inches from ground level on the stand pipes. If plates are bolted to the stand pipe, the person installing the plate will be required to weld a pipe collar on the plate and place a minimum of two set screws/bolt on each collar. Aluminum data plates may be bolted with minimum ¼ inch bolt and locking nuts or self tapping fine threaded screws. A minimum of one in each corner is to be installed on each plate.
- 3. An 8 inch x 8 inch aluminum plate, which is 12 gauge or .080 sign material (1/8 inch aluminum plate may be used in place of the .080 plate) with the required information for that well stamped or engraved in a minimum 3/8 inch tall letter or number.
- 4. The following information will be stamped or engraved on the 8 inch X 8 inch aluminum plate in the following order.
 - a. First row: Operators name
 - b. Second row: Well name and number
 - c. Third row: Legal location to include ¼ ¼, Section, Township, and range. If the legal location cannot be placed on one row it can be split into two rows with the ¼ ¼ (example: 1980 FNL 1980 FWL) being on the top row.
 - d. Fourth row: Lease Number and API number.
 - i. Example marker plate: (attached)

NMOCD Order No. R-12965 also required the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a ground level dry hole marker was installed as required in the COA's from the BLM.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion subinit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Inspection & Enforcement

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909, 575-361-2648 (Cell)

Mike Burton Environmental Protection Specialist 575-234-2226

Jeffery Robertson Natural Resource Specialist 575-234-2230

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Doug Hoag Civil Engineering Technician 575-234-5979

Linda Denniston Environmental Protection Specialist 575-234-5974

Realty, Compliance

Randy Pair Environmental Protection Specialist 575-234-6240

Permitting

Cody Layton Natural Resource Specialist 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Todd Suter Surface Protection Specialist 575-234-5987

Tanner Nygren Natural Resource Specialist 575-234-5975

Amanda Lynch Natural Resource Specialist 575-234-5922

LegIon Brumley Environmental Protection Specialist 575-234-5957