Office	State of New Mexico	,	Form C-103
District I – (575) 393-6161	Energy, Minerals and Natural Reson	irces	Revised August 1, 2011
1625 N. French Dr., Hobbs, NM 88240		WELI	API NO.
<u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISI	ON	30-015-41090
District III – (505) 334-6178	1220 South St. Francis Dr.	5. Inc	licate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 87505		STATE FEE
District IV - (505) 476-3460	Salita Fe, Nivi 6/303	6. Sta	te Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505	·	,	•
	ICES AND REPORTS ON WELLS	7. Le	ase Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPO	SALS TO DRILL OR TO DEEPEN OR PLUG BACK		
	CATION FOR PERMIT" (FORM C-101) FOR SUCH		Josey Wales 16 State Com
PROPOSALS.)	1 Converti Dodan		ell Number
1. Type of Well: Oil Well	Gas well Guner		3H
2. Name of Operator	·	9. 00	RID Number
Devon Energy Production Com	pany, L.P.		6137
3. Address of Operator		10. P	ool name or Wildcat
333 W. Sheridan Avenue, Okl	ahoma City, Oklahoma 73102 (405) 552-	7970 Wild	leat G-02 S2427030; Bone Spring
4. Well Location		1	
Unit Letter O: 150 f	eet from the South line and 1980 fe	et from theE	ast line
Section 16 Towns	·		IPM Eddy, County New Mexico
Section 10 Towns	11. Elevation (Show whether DR, RKB, RA		iPM Eddy, County New Mexico
	3323	, GR, etc.)	
	3323		
12. Check	Appropriate Box to Indicate Nature of	Notice, Repor	t or Other Data
NOTICE OF IN	ITENITION TO	ALIDAEA!	ITAT DESCRIPTION
	ITENTION TO:		JENT REPORT OF:
PERFORM REMEDIAL WORK	· · · · · · · · · · · · · · · · · · ·	IAL WORK	ALTERING CASING
TEMPORARILY ABANDON	The state of the s	ENCE DRILLING	OPNS. PANDA .
PULL OR ALTER CASING	MULTIPLE COMPL CASING	S/CEMENT JOB	
	·	Ŧ	
DOWNHOLE COMMINGLE			
OTHER: Change to Original APD		:	
OTHER: Change to Original APD			
OTHER: Change to Original APD 13. Describe proposed or comp	pleted operations. (Clearly state all pertinent	details, and give p	
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed w	pleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M	details, and give p	
OTHER: Change to Original APD 13. Describe proposed or comp	pleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M	details, and give p	
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed w	pleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M	details, and give p	
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed w	pleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M	details, and give p	
OTHER: Change to Original APD 13. Describe proposed or compost of starting any proposed we proposed completion or recomposed completion.	pleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M completion.	details, and give pultiple Completion	ns: Attach wellbore diagram of
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion. Devon Energy Production Company	pleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M	details, and give pultiple Completion hole to 9,130° and	ns: Attach wellbore diagram of di
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion. Devon Energy Production Company	pleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M completion. LP respectfully requests to drill a 8-3/4"pilot	details, and give pultiple Completion hole to 9,130° and	ns: Attach wellbore diagram of di
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion or recomposed completion. Devon Energy Production Company, 900' plugs with 450 sks Class H @	oleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M completion. LP respectfully requests to drill a 8-3/4"pilot 16.4 #/gal =+0.25% CFR-3 +0.1% HR-800, a	details, and give pultiple Completion hole to 9,130° and	ns: Attach wellbore diagram of di
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion or recomposed completion. Company, 900' plugs with 450 sks Class H @ 0.5% CFR-3 + 0.1% HR-800	oleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M completion. LP respectfully requests to drill a 8-3/4"pilot 16.4 #/gal =+0.25% CFR-3 +0.1% HR-800, a	details, and give pultiple Completion hole to 9,130° and	ns: Attach wellbore diagram of di
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion or recomposed completion. Company, 900' plugs with 450 sks Class H @ 0.5% CFR-3 + 0.1% HR-800	oleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M completion. LP respectfully requests to drill a 8-3/4"pilot 16.4 #/gal =+0.25% CFR-3 +0.1% HR-800, a	details, and give pultiple Completion hole to 9,130° and	ns: Attach wellbore diagram of di
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion or recomposed completion. Company, 900' plugs with 450 sks Class H @ 0.5% CFR-3 + 0.1% HR-800	oleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M completion. LP respectfully requests to drill a 8-3/4"pilot 16.4 #/gal =+0.25% CFR-3 +0.1% HR-800, a	details, and give pultiple Completion hole to 9,130° and	ns: Attach wellbore diagram of di
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion or recomposed completion. Company, 900' plugs with 450 sks Class H @ 0.5% CFR-3 + 0.1% HR-800	oleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M completion. LP respectfully requests to drill a 8-3/4"pilot 16.4 #/gal =+0.25% CFR-3 +0.1% HR-800, a	details, and give pultiple Completion hole to 9,130° and	ns: Attach wellbore diagram of di
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion or recomposed completion. Company, 900' plugs with 450 sks Class H @ 0.5% CFR-3 + 0.1% HR-800	oleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M completion. LP respectfully requests to drill a 8-3/4"pilot 16.4 #/gal =+0.25% CFR-3 +0.1% HR-800, a	details, and give pultiple Completion hole to 9,130° and	ns: Attach wellbore diagram of di
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion or recomposed completion. Company, 900' plugs with 450 sks Class H @ 0.5% CFR-3 + 0.1% HR-800	oleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M completion. LP respectfully requests to drill a 8-3/4"pilot 16.4 #/gal =+0.25% CFR-3 +0.1% HR-800, a	details, and give pultiple Completion hole to 9,130° and	ns: Attach wellbore diagram of di
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion or recomposed completion. Company 900' plugs with 450 sks Class H @ 0.5% CFR-3 + 0.1% HR-800 MAXIMUM LATERAL TVD 7,37	pleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For Micrompletion. LP respectfully requests to drill a 8-3/4"pilot 16.4 #/gal =+0.25% CFR-3 +0.1% HR-800, and the state of the state	details, and give pultiple Completion hole to 9,130' and 1 x 600' top p	ns: Attach wellbore diagram of di
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion or recomposed completion. Company 900' plugs with 450 sks Class H @ 0.5% CFR-3 + 0.1% HR-800 MAXIMUM LATERAL TVD 7,37	oleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M completion. LP respectfully requests to drill a 8-3/4"pilot 16.4 #/gal =+0.25% CFR-3 +0.1% HR-800, a	details, and give pultiple Completion hole to 9,130' and 1 x 600' top p	ns: Attach wellbore diagram of di
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion or recomposed completion. Company 900' plugs with 450 sks Class H @ 0.5% CFR-3 + 0.1% HR-800 MAXIMUM LATERAL TVD 7,37	pleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For Micrompletion. LP respectfully requests to drill a 8-3/4"pilot 16.4 #/gal =+0.25% CFR-3 +0.1% HR-800, and the state of the state	details, and give pultiple Completion hole to 9,130' and 1 x 600' top p	ns: Attach wellbore diagram of di
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion or recomposed completion Company, 900' plugs with 450 sks Class H @ 0.5% CFR-3 + 0.1% HR-800 MAXIMUM LATERAL TVD 7,37	bleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For Mecompletion. LP respectfully requests to drill a 8-3/4"pilot 16.4 #/gal =+0.25% CFR-3 +0.1% HR-800, a respectfully requests to drill a second of the secon	details, and give pultiple Completion hole to 9,130' and 1 x 600' top pultiple knowledge and b	ns: Attach wellbore diagram of d plugged back to KOP by setting 2 x lug with 350 sks Class H @ 17.5#/gal +
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion or recomposed completion. Company 900' plugs with 450 sks Class H @ 0.5% CFR-3 + 0.1% HR-800 MAXIMUM LATERAL TVD 7,37	pleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For Micrompletion. LP respectfully requests to drill a 8-3/4"pilot 16.4 #/gal =+0.25% CFR-3 +0.1% HR-800, and the state of the state	details, and give pultiple Completion hole to 9,130' and 1 x 600' top pultiple knowledge and b	ns: Attach wellbore diagram of d plugged back to KOP by setting 2 x lug with 350 sks Class H @ 17.5#/gal +
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion or recomposed completion. Company 900' plugs with 450 sks Class H @ 0.5% CFR-3 + 0.1% HR-800 MAXIMUM LATERAL TVD 7,37	bleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M completion. LP respectfully requests to drill a 8-3/4"pilot 16.4 #/gal =+0.25% CFR-3 +0.1% HR-800, a 78". TITLE Regulator	details, and give pultiple Completion hole to 9,130' and 1 x 600' top pultiple knowledge and b	ns: Attach wellbore diagram of d plugged back to KOP by setting 2 x lug with 350 sks Class H @ 17.5#/gal +
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion or recomposed completion. Company 900' plugs with 450 sks Class H @ 0.5% CFR-3 + 0.1% HR-800 MAXIMUM LATERAL TVD 7,37. I hereby certify that the information SIGNATURE Crim Worker Erin Worker.	bleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M completion. LP respectfully requests to drill a 8-3/4"pilot 16.4 #/gal =+0.25% CFR-3 +0.1% HR-800, a 78". TITLE Regulator	details, and give pultiple Completion hole to 9,130' and 1 x 600' top pultiple knowledge and b	ns: Attach wellbore diagram of d plugged back to KOP by setting 2 x lug with 350 sks Class H @ 17.5#/gal +
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion or recomposed completion. Company 900' plugs with 450 sks Class H @ 0.5% CFR-3 + 0.1% HR-800 MAXIMUM LATERAL TVD 7,37	bleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M completion. LP respectfully requests to drill a 8-3/4"pilot 16.4 #/gal =+0.25% CFR-3 +0.1% HR-800, a 78". TITLE Regulator	details, and give pultiple Completion hole to 9,130' and 1 x 600' top pultiple knowledge and b	ns: Attach wellbore diagram of d plugged back to KOP by setting 2 x lug with 350 sks Class H @ 17.5#/gal +
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion or recomposed completion or recomposed completion Company 900' plugs with 450 sks Class H @ 0.5% CFR-3 + 0.1% HR-800 MAXIMUM LATERAL TVD 7,37 I hereby certify that the information SIGNATURE	bleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For Micrompletion. LP respectfully requests to drill a 8-3/4"pilot 16.4 #/gal =+0.25% CFR-3 +0.1% HR-800, and the state of the best of my above is true and complete to the best of my TITLE Regulator man	details, and give pultiple Completion hole to 9,130' and 1 x 600' top pultiple knowledge and b	elief. Sociate DATE 05/09/13 dvn.com PHONE: (405) 552-7970
OTHER: Change to Original APD 13. Describe proposed or composed of starting any proposed we proposed completion or recomposed completion or recomposed completion. Company 900' plugs with 450 sks Class H @ 0.5% CFR-3 + 0.1% HR-800 MAXIMUM LATERAL TVD 7,37. I hereby certify that the information SIGNATURE Crim Worker Erin Worker.	bleted operations. (Clearly state all pertinent ork). SEE RULE 19.15.7.14 NMAC. For M completion. LP respectfully requests to drill a 8-3/4"pilot 16.4 #/gal =+0.25% CFR-3 +0.1% HR-800, a 78". TITLE Regulator	details, and give pultiple Completion hole to 9,130' and 1 x 600' top pultiple knowledge and b	ns: Attach wellbore diagram of d plugged back to KOP by setting 2 x lug with 350 sks Class H @ 17.5#/gal +