

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-40522
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Lone Tree Draw 13 State Com
8. Well Number 4H
9. OGRID Number 6137
10. Pool name or Wildcat Carlsbad; Delaware

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Devon Energy Production Company, L.P.

3. Address of Operator
333 W. Sheridan, Oklahoma City, OK 73102

4. Well Location

Unit Letter B : 150 feet from the North line and 2390 feet from the east line
Section 13 Township 21S Range 27E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3177' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: Spud Report ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/13/12 - 12/15/12: MIRU. Spud well @ 08:30 hrs. TD 17-1/2" hole @ 345'. RIH w/8 jts 13-3/8" 48# H-40 BTC csg & set @ 345'. Lead w/650 sx CI "C" cmt, yld: 1.34 cf/sx. Disp w/47.4 bbls FW. Circ 32 bbls of cmt to surf. Test BOP, annular & CK manifold to 250 psi L, 1500 psi H, 10 mins, good test. Test casing to 1210 psi 70% of Burst.

12/18/12 - 12/20/12: TD 12-1/4" hole @ 2584'. RIH w/59 jts 9-5/8" 40# J-55 STC csg & set @ 2584'. Cmt 1st stage, lead w/200 sx CI C, yld 1.73 sf/sx. Tail w/300 sx CI C, yld: 1.33 cf/sx; displ w/194 bbls FW. Circ 10 sx of cement to pits. RD cmt equip. Test BOP, annular, & CK manifold 250 psi L & 2500 H psi; held 10 min. Test casing to 1500 psi, hold for 30 min. OK. Set DV tool @ 1462'. Open up DV tool. Cmt state 2, lead w/670 sx CI C, yield 1.73 cf/sx, cmt tail w/150 sx CI C. Displace w/114 bbls FW, returned 288 sx cmt to surface. RD cmt equip. Test BOP, annular & CK manifold to 250 psi L, 2500 psi H, 10 mins, good test. Test casing to 1500 psi 70% of Burst.

12/23/12 - 12/27/2012: TD 8-3/4" pilot hole @ 7950'. CHC. Log pilot hole. Set isolation cmt plug with 50 sx cmt. Displace w/93 bbls wtr. Plug depth: 5318 - 5418'. Set top of whipstock @ 4400', KOP 4389'. Cement whipstock w/220sx of CI H cmt.; yld: 1.18. Disp w/3.5 bbls of FW. No cmt circulated to surface. TIH & tag cmt @ 140' above whipstock.

12/31/12 - 1/02/2013: TD' 8-3/4" production hole @ 9568'. RIH w/93 jts 5-1/2" 17# HCP110 LTC & 122 jts 5-1/2" HCP-110 BTC csg, set @ 9568'; CHC. Lead w/285 sx CI H, Yld 2.454 cf/sx, Tail w/1,300 sx CI "C" cmt, Yld 1.28 cf/sx; disp w/ 221 bbls of FW; Returned 1.5 bbls of wtr to surface. RD Cementer. Release Rig @ 1800 hrs on 1/02/2013.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE: Patti Riechers TITLE: Regulatory Specialist DATE: 05/06/2013

Type or print name: Patti Riechers E-mail address: patti.riechers@dvn.com PHONE: 405-228-4248

For State Use Only

APPROVED BY: SRDade TITLE: Dist # Supervisor DATE: 5/15/2013

Conditions of Approval (if any):