

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
OMB NO. 1004-0135
Expires: July 31, 2010**SUNDRY NOTICES AND REPORTS ON WELLS**
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.*5. Lease Serial No.
NMNM54290

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

8. Well Name and No.

NORTH BRUSHY DRAW FED 35 2H

2. Name of Operator

RKI EXPLORATION & PROD LLC

Contact: ROBYN L LAMPLEY

E-Mail: rlampley@rkixp.com

9. API Well No.

30-015-40006-00-X1

3a. Address

210 PARK AVE SUITE 900
OKLAHOMA CITY, OK 73102

3b. Phone No. (include area code)

Ph: 405-996-5775
Fx: 405-996-5772

10. Field and Pool, or Exploratory

CORRAL CANYON

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 35 T25S R29E NENE 0330FNL 0660FEL

11. County or Parish, and State

EDDY COUNTY, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice☐ Acidize☐ Alter Casing☐ Casing Repair☐ Change Plans☐ Convert to Injection☐ Deepen☐ Fracture Treat☐ New Construction☐ Plug and Abandon☐ Plug Back☐ Production (Start/Resume)☐ Reclamation☐ Recomplete☐ Temporarily Abandon☐ Water Disposal☐ Water Shut-Off☐ Well Integrity☒ Other
Drilling Operations

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomple horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recomple in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

On 2/22/2013, drilled 12-1/4 inch hole to 3178 feet. Ran 77 joints of 9 5/8", J-55, 40#, LTC casing. FS @ 3176 feet. FC @ 3133 feet.

Cementing:


Lead: 1025 sks of POZ mix (35/65)

Poz/"C"+5%(BWOW)PF44+6%PF20+1%PF1+.125ppsPF29+.25ppsPF46+3ppsPF42) (12.9 ppg, 1.92 yield)

Tail: 200 sks of Class C ("C"+0.2%PF13) (14.8 ppg, 1.33yield)

Circulated 176 sks/ 60 bbls.

120 Code 6/26/13
Accepted for record
NMOC



14. I hereby certify that the foregoing is true and correct.

Electronic Submission #210489 verified by the BLM Well Information System
For RKI EXPLORATION & PROD LLC, sent to the Carlsbad
Committed to AFMS for processing by KURT SIMMONS on 06/18/2013 (13KMS5098SE)

Name (Printed/Typed) ROBYN L LAMPLEY

Title REGULATORY ANALYST

Signature (Electronic Submission)

Date 06/12/2013

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By

ACCEPTEDJAMES A AMOS
Title SUPERVISOR EPS

Date 06/22/2013

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office Carlsbad

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **

Handwritten signature

Additional data for EC transaction #210489 that would not fit on the form

32. Additional remarks, continued

On 2/23/2013 tested casing to 1500 psi, held for 30 minutes.