

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-39958
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator RKI Exploration and Production, LLC		6. State Oil & Gas Lease No.
3. Address of Operator 210 Park Ave, Ste 900 OKC, OK 73102		7. Lease Name or Unit Agreement Name RDX 16
4. Well Location Unit Letter <u>C</u> : <u>330</u> feet from the <u>North</u> line and <u>1650</u> feet from the <u>West</u> line Section <u>16</u> Township <u>26S</u> Range <u>30E</u> NMPM Eddy County		8. Well Number 14H
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3090' GR		9. OGRID Number 246289
		10. Pool name or Wildcat Brushy Draw Delaware East

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

On 4/10/2013, drilled 12 -1/4 inch hole to 3496'. Ran 81 joints of 9 5/8" CSG = 79 JTS, 40#, J-55, LT&C, 8RD, SHOE @ 3,489' & F.C. @ 3,442'.

Cementing:

Lead: 750 sks of Pozmix (35/65poz/c+5%(bwow)pf44+6%pf20+1%+.125#/sksp29+.25#/sks+pf46+3#/sksp42) (12.9 ppg, 1.92 yield)
Tail: 200 sks of Class C (c+0.2%pf13 200# sugar) (14.8 ppg, 1.33 yield)
Displacement: H2O (261 volume)
Spacer: 20 bbl w/red dye (20 volume)


Circulated 41/bbls/119 sks to surface.

Spud Date:

4/4/2013

Rig Release Date:

4/28/2013



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

R. Lampley

TITLE: Regulatory Analyst

DATE: 6/26/2013

Type or print name: Robyn Lampley E-mail address: rlampley@rkixp.com PHONE: 405-996-5775

For State Use Only

APPROVED BY:

R. Wade

TITLE

Dist. J. Spewison

DATE

7/2/13

Conditions of Approval (if any):

90