

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-38511
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name STALEY STATE
8. Well Number #15
9. OGRID Number 281994
10. Pool name or Wildcat Red Lake, Glorieta-Yeso NE (96836)
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3606' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
LRE OPERATING, LLC

3. Address of Operator
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401

4. Well Location

Unit Letter J : 1746 feet from the SOUTH line and 1896 feet from the EAST line
Section 30 Township 17-S Range 28-E NMPM Eddy County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Payadd Workover ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

6/20/13: MIRUSU. TOH w/rods, pump, & tbg. Set 5-1/2" CBP @ 3600'. PT 5-1/2" csg & CBP to 4000 psi-OK. Perfed additional Yeso @ 3300', 05', 10', 15', 20', 25', 30', 35', 40', 45', 50', 55', 60', 65', 70', 75', 80', 85', 90', 95', 3400', 10', 22', 26', 30', 37', 48', 54', 60', 88', 94', 98', 3509' w/1-0.38" spf. Total 33 holes. On 6/27/13, treated new perfs w/3000 gal 15% HCL acid & 50 perf balls. Fraced w/69,768# Barry White & 25,252# resin coated 16/30 sand in 25# X-linked gel. CO after frac, drilled CBP @ 3600', & CO to PBTD4736'. TOH. On 6/30/13, landed 2-7/8" 6.5# J-55 tbg @ 4675'. Ran pump & rods. Released workover rig on 7/1/13.

Spud Date: 4/26/11

Drilling Rig Release Date: 5/9/11

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 7/3/13

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573

For State Use Only

APPROVED BY: R. Dade TITLE Dist H. Spewrson DATE 7/8/2013

Conditions of Approval (if any):

an