Submit I Copy To Appropriate District Office	State of New Mexico		Form C-103
<u>District I</u> – (575) 393-6161 1635 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natúral Resources		Revised August 1, 2011 WELL API NO.
<u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISION		30-015-39258
District III - (505) 334-6178	1220 South St. Francis Dr.		5. Indicate Type of Lease STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> – (505) 476-3460	Santa Fe, NM 87505		6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505	nta Fe, NM		L-322
SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			State B 33 DA
PROPOSALS.)			8. Well Number IH
Type of Well: Oil Well			9. OGRID Number
Mewbourne Oil Company			14744
3. Address of Operator		10. Pool name or Wildcat	
PO Box 5270 Hobbs, NM 8824.1		N. Seven Rivers; Glorieta Yeso 97565	
4. Well Location Unit Letter D 380 feet from the North Line and 150 feet from the West Line			
Unit Letter_D : 380feet from theNorth line and150 feet from theWest line Section 33			
11. Elevation (Show whether DR, RKB, RT, GR, etc.)			
3499' GL			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF IN	ITENTION TO:	SUBS	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	_
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRII	_
PULL OR ALTER CASING DOWNHOLE COMMINGLE	MULTIPLE COMPL	CASING/CEMENT	JOB 🛮
_			
OTHER:	lated energtions (Clearly state all a	OTHER:	Laive portinent dates including estimated date
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of			
proposed completion or recompletion.			
06/19/13MI & spud 12 14" hole. T	"D'd hole @ 710'. Ran 710' of 9 %"	36# J55 LT&C csg.	Cemented with 180 sks Thixad Class H
w/additives. Mixed @ 14.6 /g w/ 1.49 yd. Tail w/300 sks Class C w/2% CaCl2. Mixed @ 14.8#/gals w/1.34 yd. Plug down @ 8:15 PM			
06/20/13. Did not circ cement. Lift pressure @ 400# @ 3 BPM. WOC 6 hrs. Ran temperature survey indicating TOC @ 218'. TIH w/1" pipe & tagged @ 205'. Cmt in 3 stages w/102 sks Class C w/4% CaCl2. Mixed @ 14.8#/g w/1.34 yd. WOC. Circ 10 sks of cmt to			
the pit. At 10:30 P.M. 06/21/13, tested csg & BOPE to 1250# for 30 minutes, held OK. Drilled out with 8 3/4" bit.			
,	Ü	,	·
			RECEIVED
Spud Date: 06/19/2013	Rig Releas	se Date:	1111 2 2 2 2 2 2
			JUL 2 3 2013
			JUL 2 3 2013 NMOCD ARTES'A
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE Lathan TITLE Hobbs Regulatory DATE 07/10/13			
SIGNATORIE DATE OFFICIAL			
Type or print name _Jackie Lathan_	E-mail address:	jlathan@mewbourne	e.com_ PHONE: 575-393-5905
For State Use Only	ral a	QC 1	40
APPROVED BY:	MITLE ///SE	- A Sepan	(SI) DATE 7/24//3
Conditions of Approval (if any):		•	1//

an