Form 3160-5

(August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an
abandoned well. Use form 3160-3 (APD) for such proposals.

Lease Serial No.

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.					14101141010007		
					6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE - Other instructions on reverse side.					7. If Unit or CA/Agreement, Name and/or No.		
Type of Well					8. Well Name and No. OSAGE 34 FEDERAL 5H		
2. Name of Operator Contact: VICKIE MARTINEZ SM ENERGY E-Mail: VMARTINEZ@SM-ENERGY.COM					9. API Well No. 30-015-41250-00-X1		
3a. Address 3300 N A ST BLDG 7 STE 200 MIDLAND, TX 79705	(include area code 8-1709 -1701)	10. Field and Pool, or Exploratory PARKWAY				
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					11. County or Parish; a	nd State	
Sec 34 T19S R29E SESE 560			EDDY COUNTY, NM				
12. CHECK APPR	ROPRIATE BOX(ES) TO	O INDICATE	NATURE OF	NOTICE, RI	EPORT, OR OTHER	. DATA	
TYPE OF SUBMISSION	TYPE OF ACTION						
☐ Notice of Intent	☐ Acidize	☐ Deepen		☐ Production (Start/Resume)		☐ Water Shut-Off	
_	☐ Alter Casing	☐ Fracture Treat		☐ Reclam	ation	☐ Well Integrity	
Subsequent Report	□ Casing Repair	□ New	Construction	□ Recomp	olete	Other	
☐ Final Abandonment Notice	☐ Change Plans	Plug	and Abandon	□ Tempor	arily Abandon	Drilling Operations	
	☐ Convert to Injection	n Plug Back		■ Water I	Disposal		
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 5/28/13 SPUD WELL @ 07:30 AM; TD'ED 26" HOLE 5/29/13 RAN 20" 94# J-55 CSG; SET @ 375 FT 5/30/13 CMT W/1070 SX CLASS C (LEAD); CMT TO SURFACE 6/1/13 TD'ED 17 1/2" HOLE; RAN 13 3/8? 48#/54.5# J-55 CSG; SET @ 1512 FT 6/2/13 CMT W/610 SX CLASS H (LEAD) & 550 SX CLASS H (TAIL) & CMT TO SURFACE; TESTED BOPE 3000# & ANNULAR TO 1500#. TESTED CASING TO 1250# FOR 30 MINUTES. HELD OK. DRILLED OUT WITH 12-1/4? BIT. CHART ATTACHED. 6/6/13 RAN 9 5/8? 36# J-55 CSG; SET @ 3275 FT; CMT W/325 SX CLASS C (LEAD) & CMT TO SURFACE 6/7/13 TESTED BOPE 3000# & ANNULAR TO 1500#. TESTED CASING TO 1250# FOR 30 MINUTES. HELD OK. DRILLED OUT WITH 8-3/4? BIT. CHART ATTACHED. 6/11/13 TD'ED 8 3/4" HOLE							
14. I hereby certify that the foregoing is true and correct. Electronic Submission #211968 verified by the BLM Well Information System For SM ENERGY, sent to the Carlsbad Committed to AFMSS for processing by KURT SIMMONS on 07/12/2013 (13KMS6691SE)							
Name (Printed/Typed) VICKIE M		07/12/2013 (1 EER TECH	·	·			
·			2110111	EER TEON			
Signature (Electronic S	Date 06/27/2	2013					
	THIS SPACE FO	OR FEDERA	L OR STATE	OFFICE U	SE		
Approved By ACCEPTED			JAMES A _{Title} SUPERVI			Date 07/21/2013	
Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to conduct the applicant the applicant to conduct the applicant the ap	Office Carlsba	ıd					
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent					ake to any department or a	agency of the United	

7 8

Additional data for EC transaction #211968 that would not fit on the form

32. Additional remarks, continued

6/12/13 RAN 7? 26# HCP-110 CSG; SET @ 7526 FT; CMT W/590 SX CLASS TXI (LEAD) & 385 SX CLASS C (TAIL) & CMT TO SURFACE
6/13/13 TESTED BOPE 3000# & ANNULAR TO 1500#. TESTED CASING TO 1500# FOR 30 MINUTES. HELD OK. DRILLED OUT WITH 6-1/8? BIT. CHART ATTACHED.
6/19/13 TD'ED 6 1/8" HOLE
6/20/13 RAN 4 1/2? 11.6# P-110 CSG; SET @ 11855 FT
6/22/12 RIG RELEASE @ 06:00