

Submit 1 Copy To Appropriate District Office

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

REVISED

Form C-103

Revised August 1, 2011

WELL API NO.
30-015-39958

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
RDX 16

8. Well Number
14H

9. OGRID Number
246289

10. Pool name or Wildcat
WILDCAT G-03 S263016K;BONE SPRING

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
RKI Exploration and Production, LLC

3. Address of Operator
210 Park Ave, Ste 900 OKC, OK 73102

4. Well Location

Unit Letter C : 330 feet from the North line and 1650 feet from the West line

Section 16 Township 26S Range 30E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3090' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

On 4/10/2013, drilled 12 -1/4 inch hole to 3496'. Ran 81 joints of 9 5/8" CSG = 79 JTS, 40#, J-55, LT&C, 8RD, SHOE @ 3,489' & F.C. @ 3,442'.

Cementing:

Lead: 750 sks of Pozmix (35/65poz/c+5%(bwow)pf44+6%pf20+1%+.125#/sksp29+.25#/sks+pf46+3#/sksp42) (12.9 ppg, 1.92 yield)
Tail: 200 sks of Class C (c+0.2%pf13 200# sugar) (14.8 ppg, 1.33 yield)
Displacement: H2O (261 volume)
Spacer: 20 bbl w/red dye (20 volume)

Circulated 41/bbls/119 sks to surface.

Spud Date: 4/4/2013

Rig Release Date: 4/28/2013

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE: R. Lampley TITLE: Regulatory Analyst DATE: 8/28/2013

Type or print name: Robyn Lampley E-mail address: rlampley@rkixp.com PHONE: 405-996-5775

For State Use Only

APPROVED BY: T.C. Shepard TITLE: "Geologist" DATE: 8/28/2013

Conditions of Approval (if any):