

Form 3160-5				OCD Artesi					
(August 2007)	UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT					FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010 5. Lease Serial No. NMLC029389E 6. If Indian, Allottee or Tribe Name			
, ,									
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an									
abandoned well. Use form 3160-3 (APD) for such proposals.									
SUBMIT IN TRIPLICATE - Other instructions on reverse side.						7. If Unit or CA/Agreement, Name and/or			
 1. Type of Well Dil Well S Gas Well Other 						8. Well Name and No. NESTE KENWOOD 6 FEDERAL 00			
2. Name of Operator Contact: DAVID A EYLER CIMAREX ENERGY CO. OF COLORADOail: DEYLER@MILAGRO-RES.COM						9. API Well No. 30-015-31850			
3a. Address 600 N. MARIE MIDLAND, TX	ENFELD, SUITE X 79701	600	3b. Phone No. (include area code) Ph: 432-687-3033			10. Field and Pool, or Exploratory SHUGART; MORROW, NORTH			
4. Location of Well	(Footage, Sec., T	, R., M., or Survey Descript	ion)			11. County	or Parish, a	ind State	
Sec 6 T18S R31E NENW 990FNL 1650FWL							EDDY COUNTY, NM		
		ROPRIATE BOX(ES)					OTHE		
TYPE OF SU					F ACTION				
					······································				
🛛 Notice of Int	tent	Acidize Alter Casing		Fracture Treat	Reclam		loume)	□ Water Shut □ Well Integri	
Subsequent I	Report	Casing Repair		New Construction	Recomp			☐ Other	
🗖 Final Aband	onment Notice	Change Plans		Plug and Abandon		arily Abando	on		
		Convert to Injection		Plug Back	U Water [-			
If the proposal is Attach the Bond following completesting has been of determined that t 1) SET 5-1/2"	to deepen directiona under which the wor etion of the involved completed. Final Ab he site is ready for fi CIBP @ 11,400	ration (clearly state all perti- lly or recomplete horizontal k will be performed or prov operations. If the operation andonment Notices shall be nal inspection.)	lly, give subsurf ide the Bond No results in a mu filed only after	ace locations and measure o, on file with BLM/BIA ltiple completion or recuration and requirements, include	ured and true ve A. Required su	ertical depths of bsequent report new interval, a n have been c SEE AT	of all pertine rts shall be t a Form 3160 completed, a TACH	ent markers and zor filed within 30 days 0-4 shall be filed on nd the operator has ED FOR	
If the proposal is Attach the Bond following comple testing has been determined that t 1) SET 5-1/2" 2) CIRC. WEL 3) PUMP 40 S 4) PUMP 25 S 6) PUMP 25 S 6) PUMP 25 S 6) PUMP 25 S 7) PUMP 25 S 8) PUMP 25 S 9) PERF. X C 10)DIG OUT 2 WELD ON ST	to deepen directiona under which the wor etion of the involved completed. Final Ab he site is ready for fi CIBP @ 11,400 L W/ PXA FLUII SXS.CMT. @ 10, SXS.CMT. @ 3,0 SXS.CMT. @ 3,0 SXS.CMT. @ 3,0 SXS.CMT. @ 2,8 SXS.CMT. @ 2,8 SXS.CMT. @ 1,1 IRC. TO SURF., X CUT OFF WEL TEL PLATE TO	Ily or recomplete horizontal k will be performed or prov operations. If the operation andonment Notices shall be nal inspection.) '; PUMP 55 SXS.CMT. D. 800'-10,530'(T/ATOKA 95'-8,605'(T/WC); WO 00'-5,800'(SPACER PI 95'-3,155'(8-5/8" CSG. 80'-2,750'(T/S.A.). provide 95'-3,155'(8-5/8" CSG. 80'-2,750'(T/S.A.). provide S0'-2,750'(T/S.A.). provide S0'-2,750'(T/S.A.). provide FILLING ALL ANNULI LHEAD 3' B.G.L.; VEF CSGS. X INSTALL DF CSGS. X INSTALL DF CSGS. X INSTALL DF Electronic Submission For CIMAREX EN	Ily, give subsurf ide the Bond No. results in a mui filed only after @ 11,400'-1 A, T/STWN.). C X TAG CW LUG). SHOE); WO TAG P(SHOE); WO TAG P	ace locations and measu on file with BLM/BL/ httple completion or recall requirements, included 10,990'(T/MRRW.). IT. PLUG. C X TAG CMT. PLI CSG.SHOE); WOO IT. @ 250'-3'. O SURF. ON ALL A SURF. ON ALL A RKER. C X TAG CMT. PLI CSG.SHOE); WOO IT. @ 250'-3'. CSG.SHOE); WOO	UG. X Required su ompletion in a i ding reclamation C X TAG. ANNULI; Il Information to the Carls	REI	of all pertine rts shall be t a Form 3160 TACH TIONS	ent markers and zor filed within 30 days A shall be filed on a d the operator has ED FOR OF APPR d for necessor ACCE VE	
If the proposal is Attach the Bond following completesting has been determined that t 1) SET 5-1/2" 2) CIRC. WEL 3) PUMP 40 S 4) PUMP 25 S 5) PUMP 25 S 6) PUMP 25 S 6) PUMP 25 S 7) PUMP 25 S 7) PUMP 25 S 8) PUMP 75 S 9) PERF. X C 10)DIG OUT X WELD ON ST	to deepen directiona under which the wor etion of the involved completed. Final Ab he site is ready for fi CIBP @ 11,400 L W/ PXA FLUII SXS.CMT. @ 10, SXS.CMT. @ 3,0 SXS.CMT. @ 3,0 SXS.CMT. @ 3,0 SXS.CMT. @ 2,8 SXS.CMT. @ 2,8 SXS.CMT. @ 1,1 IRC. TO SURF., X CUT OFF WEL TEL PLATE TO	Ily or recomplete horizontal k will be performed or prov operations. If the operation andonment Notices shall be nal inspection.) '; PUMP 55 SXS.CMT. D. 800'-10,530'(T/ATOKA 95'-8,605'(T/WC); WO 00'-5,800'(T/ATOKA 95'-3,155'(8-5/8" CSG. 80'-2,750'(T/S.A.). 60'-535'(T/YATES, B/S FILLING ALL ANNULI LHEAD 3' B.G.L.; VEF CSGS. X INSTALL DF LHEAD 3' B.G.L.; VEF CSGS. X INSTALL DF LILING ALL ANNULI LHEAD 3' B.G.L.; VEF CSGS. X INSTALL DF LILING ALL ANNULI LHEAD 3' B.G.L.; VEF CSGS. X INSTALL DF CSGS. X INSTALL DF CSGS. X INSTALL DF CSGS. X INSTALL DF CSGS. X INSTALL DF	Ily, give subsurf ide the Bond No. results in a mui filed only after @ 11,400'-1 A, T/STWN.). C X TAG CW LUG). SHOE); WO TAG P(SHOE); WO TAG P	ace locations and measu on file with BLM/BL/ httple completion or recall requirements, included 10,990'(T/MRRW.). IT. PLUG. C X TAG CMT. PLI CSG.SHOE); WOO IT. @ 250'-3'. O SURF. ON ALL A SURF. ON ALL A RKER. C X TAG CMT. PLI CSG.SHOE); WOO IT. @ 250'-3'. CSG.SHOE); WOO	UG. C X TAG. ANNULI; Information Informa	REI	of all pertine rts shall be i a Form 3160 TACH TIONS	Int markers and zor filed within 30 days A shall be filed on and the operator has ED FOR OF APPR I for negative ACCE VE ACCE VE JG 27 2013	
If the proposal is Attach the Bond following completesting has been determined that t 1) SET 5-1/2" 2) CIRC. WEL 3) PUMP 40 S 4) PUMP 25 S 5) PUMP 25 S 6) PUMP 25 S 6) PUMP 25 S 7) PUMP 25 S 7) PUMP 25 S 8) PUMP 75 S 9) PERF. X C 10)DIG OUT X WELD ON ST	to deepen directiona under which the wor etion of the involved completed. Final Ab he site is ready for fi CIBP @ 11,400 L W/ PXA FLUII SXS.CMT. @ 10, SXS.CMT. @ 3,2 SXS.CMT. @ 3,2 SXS.CMT. @ 3,2 SXS.CMT. @ 1,1 IRC. TO SURF., X CUT OFF WEL TEEL PLATE TO	Ily or recomplete horizontal k will be performed or prov operations. If the operation andonment Notices shall be nal inspection.) '; PUMP 55 SXS.CMT. D. 800'-10,530'(T/ATOKA 95'-8,605'(T/WC); WO 00'-5,800'(SPACER PI 95'-3,155'(8-5/8" CSG. 80'-2,750'(T/S.A.). PO 00'-535'(T/YATES, B/G FILLING ALL ANNULI LHEAD 3' B.G.L.; VEF CSGS. X INSTALL DF CSGS. X INSTALL DF CSGS. X INSTALL DF For CIMAREX EN Committed to AFMSS for SYLER	Ily, give subsurf ide the Bond No. results in a mui filed only after @ 11,400'-1 A, T/STWN.). C X TAG CW LUG). SHOE); WO TAG P(SHOE); WO TAG P	ace locations and measu b. on file with BLM/BL/ liple completion or rec all requirements, includ 10,990'(T/MRRW.). IT. PLUG. C X TAG CMT. PLI CSG.SHOE); WOU IT. @ 250'-3'. O SURF. ON ALL A SURF. ON ALL A RKER. C S COLORADO, sent by JOHNNY DICKE	UG. S - 14 29 , C X TAG. ANNULI; II Information II Information ISON on 08/	REI	of all pertine rts shall be i a Form 3160 TACH TIONS	ent markers and zor filed within 30 days A shall be filed on nd the operator has ED FOR OF APPR of for negative ACCE VE ACCED JG 27 2013	
If the proposal is Attach the Bond following comple testing has been determined that t 1) SET 5-1/2" 2) CIRC. WEL 3) PUMP 40 S 4) PUMP 25 S 5) PUMP 25 S 6) PUMP 25 S 6) PUMP 25 S 6) PUMP 25 S 7) PUMP 25 S 9) PERF. X C 10)DIG OUT 2 WELD ON ST Growd L 14. Thereby certify Name (Printed/Ty)	to deepen directiona under which the wor etion of the involved completed. Final Ab he site is ready for fi CIBP @ 11,400 L W/ PXA FLUII SXS.CMT. @ 10, SXS.CMT. @ 3,2 SXS.CMT. @ 3,2 SXS.CMT. @ 3,2 SXS.CMT. @ 2,8 SXS.CMT. @ 2,8 SXS.CMT. @ 1,1 IRC. TO SURF., X CUT OFF WEL TEL PLATE TO	Illy or recomplete horizontal k will be performed or prov operations. If the operation andonment Notices shall be nal inspection.) '; PUMP 55 SXS.CMT. D. 800'-10,530'(T/ATOKA 95'-8,605'(T/WC); WO 00'-5,800'(SPACER PI 95'-3,155'(8-5/8" CSG 80'-2,750'(T/SA.). 95'-3,155'(8-5/8" CSG 80'-2,750'(T/SA.). 00'-535'(T/YATES, B/S FILLING ALL ANNULI LHEAD 3' B.G.L.; VEF CSGS. X INSTALL DF CSGS. X INSTALL DF Lectronic Submission For CIMAREX EN Committed to AFMSS for EYLER ubmission)	Ily, give subsurf ide the Bond No results in a mu filed only after @ 11,400'-1 A, T/STWN.). C X TAG CM LUG). SHOE); WO A P(SHOE); WO A P(SALT, 13-3/8 , 85 SXS.CM AIFY CMT. T AY HOLE MA LERGY CO. OI or processing	ace locations and measu on file with BLM/BL/ httple completion or recall requirements, included 10,990'(T/MRRW.). IT. PLUG. C X TAG CMT. PLI (CSG.SHOE); WOO T. @ 250'-3'. O SURF. ON ALL A SURF. ON ALL A RKER. C X TAG CMT. PLI (T. @ 250'-3'. O SURF. ON ALL A SURF. ON ALL A	UG. UG. UG. UG. UG. UG. C. 14 29 C X TAG. ANNULI; Il Information to the Carlsl RSON on 08/	REP	of all pertine rts shall be i a Form 3160 TACH TIONS	ent markers and zor filed within 30 days A shall be filed on nd the operator has ED FOR OF APPR of for negative ACCE VE ACCED JG 27 2013	
If the proposal is Attach the Bond following comple testing has been of determined that t 1) SET 5-1/2" 2) CIRC. WEL 3) PUMP 40 S 4) PUMP 25 S 5) PUMP 25 S 6) PUMP 25 S 6) PUMP 25 S 6) PUMP 25 S 7) PUMP 25 S 8) PUMP 75 S 9) PERF. X C 10)DIG OUT X WELD ON ST <i>Gourd</i> (14. 1 hereby certify Name (<i>Printed/Ty</i>) Signature	to deepen directiona under which the wor etion of the involved completed. Final Ab he site is ready for fi CIBP @ 11,400 L W/ PXA FLUII SXS.CMT. @ 10, SXS.CMT. @ 10, SXS.CMT. @ 3,2 SXS.CMT. @ 3,2 SXS.CMT. @ 3,2 SXS.CMT. @ 3,2 SXS.CMT. @ 2,8 SXS.CMT. @ 1,1 IRC. TO SURF., X CUT OFF WEL TEEL PLATE TO CONCOMPOSITION OF that the foregoing is (Electronic S	Illy or recomplete horizontal k will be performed or prov operations. If the operation andonment Notices shall be nal inspection.) '; PUMP 55 SXS.CMT. D. 800'-10,530'(T/ATOKA 95'-8,605'(T/WC); WO 00'-5,800'(SPACER PI 95'-3,155'(8-5/8" CSG 80'-2,750'(T/SA.). 95'-3,155'(8-5/8" CSG 80'-2,750'(T/SA.). 00'-535'(T/YATES, B/S FILLING ALL ANNULI LHEAD 3' B.G.L.; VEF CSGS. X INSTALL DF CSGS. X INSTALL DF Lectronic Submission For CIMAREX EN Committed to AFMSS for EYLER ubmission)	Ily, give subsurf ide the Bond No results in a mu filed only after @ 11,400'-1 A, T/STWN.). C X TAG CM LUG). SHOE); WO A P(SHOE); WO A P(SALT, 13-3/8 , 85 SXS.CM AIFY CMT. T AY HOLE MA LERGY CO. OI or processing	ace locations and measu on file with BLM/BL/ httple completion or recall requirements, included 10,990'(T/MRRW.). IT. PLUG. C X TAG CMT. PLI (CSG.SHOE); WOO T. @ 250'-3'. O SURF. ON ALL / SURF. ON ALL / NRKER. C X TAG CMT. PLI CSG.SHOE); WOO T. @ 250'-3'. O SURF. ON ALL / NRKER. C X TAG CMT. PLI CSG.SHOE); WOO T. @ 250'-3'. O SURF. ON ALL / NRKER. C X TAG CMT. PLI CSG.SHOE); WOO T. @ 250'-3'. O SURF. ON ALL / CSG.SHOE); WOO T. @ 250'-3'. C SURF. ON ALL / C SURF.	UG. UG. C X TAG. ANNULI; II Information to the Carls RSON on 08/ 013 OFFICE US	REP	of all pertine rts shall be i a Form 3160 TACH TIONS	ent markers and zor iled within 30 days 1-4 shall be filed on nd the operator has ED FOR OF APPR ic for record ACHED ON PROCEDUR ACHED IG 27 2013 CD ARTES Procession CE Statession CD ARTES	
If the proposal is Attach the Bond following comple testing has been determined that t 1) SET 5-1/2" 2) CIRC. WEL 3) PUMP 40 S 4) PUMP 25 S 6) PUMP 25 S 6) PUMP 25 S 6) PUMP 25 S 7) PUMP 25 S 8) PUMP 75 S 9) PERF. X C 10)DIG OUT 2 WELD ON ST <i>Gcome</i> () 14. Thereby certify Name (<i>Printed/T</i>) Signature	to deepen directiona under which the wor etion of the involved completed. Final Ab he site is ready for fi CIBP @ 11,400 L W/ PXA FLUII SXS.CMT. @ 10, SXS.CMT. @ 4,7 SXS.CMT. @ 3,2 SXS.CMT. @ 2,8 SXS.CMT. @ 2,8 SXS.CMT. @ 2,8 SXS.CMT. @ 1,1 IRC. TO SURF., X CUT OFF WEL TEEL PLATE TO (Electronic S) (Electronic S)	Ily or recomplete horizontal k will be performed or prov operations. If the operation andonment Notices shall be nal inspection.) '; PUMP 55 SXS.CMT. D. 800'-10,530'(T/ATOKA 95'-8,605'(T/WC); WO 00'-5,800'(SPACER PI 95'-3,155'(8-5/8" CSG. 80'-2,750'(T/S.A.). P 00'-535'(T/YATES, B/S FILLING ALL ANNULI LHEAD 3' B.G.L.; VEF CSGS. X INSTALL DF CSGS. X INSTALL DF Lectronic Submission For CIMAREX EN Committed to AFMSS for EYLER ubmission) THIS SPACE I	Ily, give subsurf ide the Bond NG results in a mu filed only after @ 11,400'-1 A, T/STWN.). C X TAG CM LUG). SHOE); WO A P(ace locations and measu o. on file with BLM/BL/ httple completion or rec all requirements, includ 10,990'(T/MRRW.). IT. PLUG. C X TAG CMT. PLI CSG.SHOE); WO T. @ 250'-3'. O SURF. ON ALL / CSG.SHOE); WO IT. @ 250'-3'. O SURF. ON ALL / RKER. Date 08/13/2 RAL OR STATE	UG. UG. UG. UG. UG. UG. C. 14 29 C X TAG. ANNULI; Il Information to the Carlsl RSON on 08/	REP	of all pertine rts shall be i a Form 3160 TACH TIONS	A shall be filed on not the operator has ED FOR OF APPR I for record ADCD 8/00 ON PROCEDUR ACHED IG 27 2013 CD ARTES	
If the proposal is Attach the Bond following comple testing has been determined that t 1) SET 5-1/2" 2) CIRC. WEL 3) PUMP 40 S 4) PUMP 25 S 5) PUMP 25 S 6) PUMP 25 S 6) PUMP 25 S 6) PUMP 25 S 7) PUMP 25 S 8) PUMP 75 S 9) PERF. X C 10)DIG OUT 2 WELD ON ST <i>Geome</i> 14. Thereby certify Name (<i>Printed/T</i>) Signature	to deepen directiona under which the wor etion of the involved completed. Final Ab he site is ready for fi CIBP @ 11,400 L W/ PXA FLUII SXS.CMT. @ 10, SXS.CMT. @ 10, SXS.CMT. @ 2,8 SXS.CMT. @ 3,2 SXS.CMT. @ 3,2 SXS.CMT. @ 3,2 SXS.CMT. @ 3,2 SXS.CMT. @ 1,1 IRC. TO SURF., X CUT OFF WEL TEEL PLATE TO CONCOMPOSITION (Electronic S (Electronic S) (Electronic S) (I f any, are attached int holds legal or equine applicant to condu	Illy or recomplete horizontal k will be performed or prov operations. If the operation andonment Notices shall be nal inspection.) '; PUMP 55 SXS.CMT. D. 800'-10,530'(T/ATOKA 95'-8,605'(T/WC); WO 00'-5,800'(SPACER PI 95'-3,155'(8-5/8" CSG. 80'-2,750'(T/SA.). 00'-535'(T/YATES, B/S FILLING ALL ANNULI LHEAD 3' B.G.L.; VEF CSGS. X INSTALL DF LOAD A COMMISSION FOR CIMAREX EN COMMITTED SUBMISSION FOR CIMAREX EN Committed to AFMSS for EYLER Ubmission) THIS SPACE I A Approval of this notice do itable title to those rights in ct operations thereon.	Ily, give subsurf ide the Bond NG results in a mu filed only after @ 11,400'-1 A, T/STWN.). C X TAG CW LUG). SHOE); WO A T, 13-3/8 , 85 SXS.CM RIFY CMT. T RY HOLE MA WERGY CO. OI or processing FOR FEDE	ace locations and measu on file with BLM/BL/ httple completion or rec- all requirements, inclue 10,990'(T/MRRW.). IT. PLUG. C X TAG CMT. PLI CSG.SHOE); WO T. @ 250'-3'. O SURF. ON ALL / CSG.SHOE); WO T. @ 250'-3'. O SURF. ON ALL / NRKER. C Z LL CC Title AGENT Date 08/13/2 RAL OR STATE Office C	UG. UG. Carlot and true volume ompletion in a i ing reclamation UG. Carlot A. Carlot A. UG. Carlot A. Carlot A.	SEE	of all pertine rts shall be t a Form 3160 TACH TIONS CLAMATI AT CLAMATI AT	ent markers and zor iled within 30 days 1-4 shall be filed on nd the operator has ED FOR OF APPR I for record ON PROCEDUR ACHED IG 27 2013 CD ARTES Date	
If the proposal is Attach the Bond following comple testing has been determined that t 1) SET 5-1/2" 2) CIRC. WEL 3) PUMP 40 S 4) PUMP 25 S 5) PUMP 25 S 6) PUMP 25 S 6) PUMP 25 S 6) PUMP 25 S 7) PUMP 25 S 8) PUMP 75 S 9) PERF. X C 10)DIG OUT 2 WELD ON ST <i>Geometry</i> 14. Thereby certify 14. Thereby certify Name (<i>Printed/T</i>) Signature	to deepen directiona under which the wor etion of the involved completed. Final Ab he site is ready for fi CIBP @ 11,400 L W/ PXA FLUII SXS.CMT. @ 10, SXS.CMT. @ 10, SXS.CMT. @ 3,2 SXS.CMT. @ 3,2 SXS.CMT. @ 3,2 SXS.CMT. @ 2,8 SXS.CMT. @ 1,0 IRC. TO SURF., X CUT OFF WEL TEEL PLATE TO CONCEPTION (Electronic S (Electronic S (Electronic S) (I f any, are attached unt holds legal or equine applicant to condu	Illy or recomplete horizontal k will be performed or prov operations. If the operation andonment Notices shall be nal inspection.) '; PUMP 55 SXS.CMT. D. 800'-10,530'(T/ATOKA 95'-8,605'(T/WC); WO 00'-5,800'(SPACER PI 95'-3,155'(8-5/8" CSG. 80'-2,750'(T/S.A.). 00'-535'(T/YATES, B/S FILLING ALL ANNULI LHEAD 3' B.G.L.; VEF CSGS. X INSTALL DF LHEAD 3' B.G.L.; VEF CSGS. X INSTALL DF LHEAD 3' B.G.L.; VEF CSGS. X INSTALL DF CSGS. X INSTALL DF LHEAD 3' B.G.L.; VEF CSGS. X INSTALL DF LAB 1' C C C C C C C C C C C C C C C C C C	Ily, give subsurf ide the Bond NG results in a mu filed only after @ 11,400'-1 A, T/STWN.). C X TAG CW LUG). SHOE); WO A P(ace locations and measu on file with BLM/BL/ httple completion or rec- all requirements, inclue 10,990'(T/MRRW.). IT. PLUG. C X TAG CMT. PLI CSG.SHOE); WO T. @ 250'-3'. O SURF. ON ALL A CSG.SHOE); WO T. @ 250'-3'. O SURF. ON ALL A RKER. C X TAG CMT. PLI CSG.SHOE); WO T. @ 250'-3'. O SURF. ON ALL A RKER. Date 08/13/2 RAL OR STATE Office Office Office	UG. UG. Carlot and true volume ompletion in a i ling reclamation UG. Carlot 29 Carlot 20 Carlot 20 Ca	SEE	of all pertine rts shall be t a Form 3160 TACH TIONS CLAMATI AT CLAMATI AT	ent markers and zor iled within 30 days 1-4 shall be filed on nd the operator has ED FOR OF APPR I for necore ACHED IG 2 7 2013 CD ARTES Date	

÷.



Printed //30/2013



BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. <u>Notification</u>: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.

5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. <u>Show date well was plugged.</u>

8. <u>Trash</u>: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

J. Amos 3/6/11

Requirements for ground level dry hole markers <u>Well Identification Markers</u> Conditions of Approval (COA)

The BLM Carlsbad Field Office (CFO) Conditions of Approval (COA) Requires that ground level dry hole markers be placed on well within the Lesser Prairie Chicken habitat area. The dry hole markers will be to the following specifications. The operator will construct the markers as follows:

- 1. An 8 inch X 8 inch steel plate 1/8 to 3/16 of an inch thick is to be placed on the old dry hole marker stand pipe 2 inches from ground level, in the Lesser Prairie Chicken habitat area.
- 2. Steel plate may be welded or bolted approximately 2 inches from ground level on the stand pipes. If plates are bolted to the stand pipe, the person installing the plate will be required to weld a pipe collar on the plate and place a minimum of two set screws/bolt on each collar. Aluminum data plates may be bolted with minimum ¹/₄ inch bolt and locking nuts or self tapping fine threaded screws. A minimum of one in each corner is to be installed on each plate.
- 3. An 8 inch x 8 inch aluminum plate, which is 12 gauge or .080 sign material (1/8 inch aluminum plate may be used in place of the .080 plate) with the required information for that well stamped or engraved in a minimum 3/8 inch tall letter or number.
- 4. The following information will be stamped or engraved on the 8 inch X 8 inch aluminum plate in the following order.
 - a. First row: Operators name
 - b. Second row: Well name and number
 - c. Third row: Legal location to include ¹/₄ ¹/₄, Section, Township, and range. If the legal location cannot be placed on one row it can be split into two rows with the ¹/₄ ¹/₄ (example: 1980 FNL 1980 FWL) being on the top row.
 - d. Fourth row: Lease Number and API number.
 - i. Example marker plate: (attached)

NMOCD Order No. R-12965 also required the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a ground level dry hole marker was installed as required in the COA's from the BLM.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Inspection & Enforcement

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909, 575-361-2648 (Cell)

Mike Burton Environmental Protection Specialist 575-234-2226

Jeffery Robertson Natural Resource Specialist 575-234-2230

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Doug Hoag Civil Engineering Technician 575-234-5979

Linda Denniston Environmental Protection Specialist 575-234-5974

Solomon Hughes Natural Resource Specialist 575-234-5951

Permitting

Cody Layton Natural Resource Specialist 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Todd Suter Surface Protection Specialist 575-234-5987

Tanner Nygren Natural Resource Specialist 575-234-5975

Amanda Lynch Natural Resource Specialist 575-234-5922

Legion Brumley Environmental Protection Specialist 575-234-5957

<u>Realty, Compliance</u> Randy Pair Environmental Protection Specialist 575-234-6240