

LEGEND
NATURAL GAS

Legend Natural Gas


Eddy County, New Mexico

Bucshot State Com

Buckshot State Com 3H

API No.:30-015-41094


Side Track #1



Design: Side Track #1

Standard Survey Report

11 September, 2013




Scientific Drilling

www.scientificdrilling.com



Scientific Drilling Survey Report



Company:	Legend Natural Gas	Local Co-ordinate Reference:	Well: Buckshot, State Com 3H
Project:	Eddy County, New Mexico	TVD Reference:	KB @ 3077.0usft (Rig)
Site:	Buckshot, State Com	MD Reference:	KB @ 3077.0usft (Rig)
Well:	Buckshot, State Com 3H	North Reference:	Grid
Wellbore:	Side Track #1	Survey Calculation Method:	Minimum Curvature
Design:	Side Track #1	Database:	CompassC

Project:	Eddy County, New Mexico		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site		Bucshot State Com			
Site Position:		Northing:	424,485.20 usft	Latitude:	32° 10' 0.568 N
From:	Map	Easting:	604,246.30 usft	Longitude:	104° 7' 48.090 W
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "	Grid Convergence:	0.11 °

Well:	Buckshot State Com 3H					
Well Position	+N/-S	0.0 usft	Northing:	424,485.20 usft	Latitude:	32° 10' 0.568 N
	+E/-W	0.0 usft	Easting:	604,246.30 usft	Longitude:	104° 7' 48.090 W
Position Uncertainty		0.0 usft	Wellhead Elevation:	usft	Ground Level:	3,052.0 usft

Wellbore	Side Track #1				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2010	8/31/2013	7.57	59.98	48,302

Design:	Side Track #1				
Audit Notes:					
Version:	1.0	Phase:	ACTUAL	Tie On Depth:	7,311.0
Vertical Section:	Depth From (TVD) (usft)	+N-S (usft)	+E-W (usft)	Direction (°)	
	0.0	0.0	0.0	344.95	

Survey Program		Date	9/11/2013		
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description	
100.0	338.0	Ves Gyro (Original Wellpath)	SRG-GYRO-MS	surface readout gyro multishot	
445.0	7,311.0	SDI MWD (Original Wellpath)	MWD	MWD - Standard	
7,347.0	12,613.0	SDI MWD (Side Track #1)	MWD	MWD - Standard	

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N-S (usft)	+E-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.63	191.48	100.0	-0.5	-0.1	-0.5	0.63	0.63	0.00
200.0	0.75	201.40	200.0	-1.7	-0.5	-1.5	0.17	0.12	9.92
300.0	1.34	205.81	300.0	-3.3	-1.2	-2.9	0.60	0.59	4.41
338.0	1.18	209.23	338.0	-4.1	-1.6	-3.5	0.47	-0.42	9.00
445.0	3.01	192.67	444.9	-7.8	-2.7	-6.8	1.78	1.71	-15.48
507.0	3.56	195.94	506.8	-11.2	-3.6	-9.9	0.94	0.89	5.27
602.0	3.96	204.51	601.6	-17.1	-5.8	-15.0	0.72	0.42	9.02
696.0	3.96	217.17	695.4	-22.6	-9.1	-19.5	0.93	0.00	13.47



Scientific Drilling Survey Report



Company:	Legend Natural Gas	Local Co-ordinate Reference:	Well: Buckshot State Com 3H
Project:	Eddy County New Mexico	TVD Reference:	KB @ 3077.0usft (Rig)
Site:	Buckshot State Com	MD Reference:	KB @ 3077.0usft (Rig)
Well:	Buckshot State Com 3H	North Reference:	Grid
Wellbore:	Side Track #1	Survey Calculation Method:	Minimum Curvature
Design:	Side Track #1	Database:	CompassC

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
790.0	4.82	231.76	789.1	-27.6	-14.2	-23.0	1.49	0.91	15.52
885.0	6.07	242.57	883.7	-32.4	-21.8	-25.6	1.70	1.32	11.38
980.0	7.12	241.25	978.0	-37.6	-31.4	-28.1	1.12	1.11	-1.39
1,074.0	8.25	245.58	1,071.2	-43.1	-42.6	-30.6	1.35	1.20	4.61
1,168.0	8.71	245.20	1,164.2	-48.9	-55.2	-32.9	0.49	0.49	-0.40
1,263.0	9.50	247.49	1,258.0	-54.9	-69.0	-35.1	0.91	0.83	2.41
1,357.0	9.41	247.66	1,350.7	-60.8	-83.3	-37.1	0.10	-0.10	0.18
1,451.0	9.90	249.02	1,443.3	-66.6	-97.9	-38.9	0.57	0.52	1.45
1,545.0	10.29	253.61	1,535.9	-71.9	-113.5	-40.0	0.95	0.41	4.88
1,640.0	8.79	256.01	1,629.6	-76.1	-128.7	-40.0	1.63	-1.58	2.53
1,734.0	7.30	258.48	1,722.7	-79.0	-141.5	-39.5	1.63	-1.59	2.63
1,828.0	7.81	262.07	1,815.8	-81.1	-153.7	-38.4	0.74	0.54	3.82
1,923.0	8.62	267.44	1,909.9	-82.3	-167.2	-36.0	1.17	0.85	5.65
2,017.0	8.97	273.50	2,002.8	-82.1	-181.6	-32.2	1.05	0.37	6.45
2,111.0	8.53	272.27	2,095.7	-81.4	-195.9	-27.8	0.51	-0.47	-1.31
2,205.0	9.23	272.98	2,188.5	-80.7	-210.4	-23.4	0.75	0.74	0.76
2,300.0	10.37	278.40	2,282.2	-79.1	-226.4	-17.6	1.54	1.20	5.71
2,395.0	12.40	277.55	2,375.3	-76.5	-245.0	-10.3	2.14	2.14	-0.89
2,470.0	14.28	277.69	2,448.3	-74.2	-262.1	-3.6	2.51	2.51	0.19
2,591.0	15.75	279.24	2,565.1	-69.6	-293.1	8.9	1.26	1.21	1.28
2,685.0	17.05	280.83	2,655.3	-64.9	-319.3	20.2	1.46	1.38	1.69
2,780.0	18.10	280.42	2,745.9	-59.7	-347.5	32.6	1.11	1.11	-0.43
2,874.0	18.61	279.66	2,835.1	-54.5	-376.6	45.1	0.60	0.54	-0.81
2,968.0	18.27	277.27	2,924.2	-50.1	-406.0	57.0	0.88	-0.36	-2.54
3,062.0	18.35	273.71	3,013.5	-47.3	-435.4	67.4	1.19	0.09	-3.79
3,156.0	17.55	272.06	3,102.9	-45.8	-464.3	76.3	1.01	-0.85	-1.76
3,251.0	14.52	269.74	3,194.2	-45.4	-490.6	83.5	3.26	-3.19	-2.44
3,345.0	13.38	273.72	3,285.4	-44.7	-513.2	90.0	1.58	-1.21	4.23
3,440.0	14.35	274.93	3,377.7	-43.0	-535.9	97.6	1.07	1.02	1.27
3,534.0	15.43	275.27	3,468.5	-40.8	-559.9	105.9	1.15	1.15	0.36
3,630.0	14.24	269.57	3,561.3	-39.8	-584.5	113.3	1.96	-1.24	-5.94
3,724.0	14.57	266.15	3,652.4	-40.6	-607.8	118.5	0.97	0.35	-3.64
3,819.0	13.94	269.80	3,744.4	-41.5	-631.2	123.8	1.16	-0.66	3.84
3,913.0	13.01	268.37	3,835.8	-41.8	-653.1	129.2	1.05	-0.99	-1.52
4,007.0	12.64	267.01	3,927.5	-42.7	-673.9	133.8	0.51	-0.39	-1.45
4,102.0	12.79	269.73	4,020.2	-43.2	-694.8	138.6	0.65	0.16	2.86
4,196.0	13.33	273.44	4,111.7	-42.6	-716.1	144.7	1.06	0.57	3.95
4,290.0	13.78	272.41	4,203.1	-41.5	-738.1	151.5	0.54	0.48	-1.10
4,385.0	13.71	274.77	4,295.4	-40.1	-760.6	158.7	0.59	-0.07	2.48
4,479.0	13.42	274.45	4,386.8	-38.3	-782.6	166.1	0.32	-0.31	-0.34
4,574.0	13.53	274.48	4,479.2	-36.6	-804.6	173.5	0.12	0.12	0.03
4,668.0	14.20	274.43	4,570.4	-34.9	-827.1	181.0	0.71	0.71	-0.05
4,763.0	13.52	272.44	4,662.7	-33.5	-849.8	188.3	0.87	-0.72	-2.09



Scientific Drilling Survey Report



Company:	Legend Natural Gas	Local Co-ordinate Reference:	Well: Buckshot State Com 3H
Project:	Eddy County, New Mexico	TVD Reference:	KB @ 3077.0usft (Rig)
Site:	Buckshot State Com	MD Reference:	KB @ 3077.0usft (Rig)
Well:	Buckshot State Com 3H	North Reference:	Grid
Wellbore:	Side Track #1	Survey Calculation Method:	Minimum Curvature
Design:	Side Track #1	Database:	CompassC

Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
4,858.0	13.09	271.99	4,755.1	-32.6	-871.7	194.7	0.47	-0.45	-0.47	
4,952.0	13.26	271.63	4,846.6	-32.0	-893.1	201.0	0.20	0.18	-0.38	
5,046.0	13.42	270.29	4,938.1	-31.6	-914.7	206.9	0.37	0.17	-1.43	
5,235.0	14.26	273.26	5,121.6	-30.2	-959.9	220.0	0.58	0.44	1.57	
5,328.0	14.28	272.31	5,211.7	-29.1	-982.8	227.1	0.25	0.02	-1.02	
5,422.0	13.66	272.84	5,303.0	-28.0	-1,005.5	233.9	0.67	-0.66	0.56	
5,517.0	13.88	272.63	5,395.2	-27.0	-1,028.1	240.8	0.24	0.23	-0.22	
5,611.0	13.23	273.86	5,486.6	-25.7	-1,050.1	247.7	0.76	-0.69	1.31	
5,705.0	12.93	273.67	5,578.2	-24.3	-1,071.3	254.6	0.32	-0.32	-0.20	
5,800.0	13.51	273.09	5,670.7	-23.0	-1,093.0	261.5	0.63	0.61	-0.61	
5,894.0	13.69	273.24	5,762.0	-21.8	-1,115.1	268.4	0.20	0.19	0.16	
5,989.0	13.50	273.80	5,854.4	-20.5	-1,137.3	275.5	0.24	-0.20	0.59	
6,083.0	12.41	274.72	5,946.0	-18.9	-1,158.4	282.4	1.18	-1.16	0.98	
6,178.0	11.45	274.90	6,038.9	-17.3	-1,177.9	289.1	1.01	-1.01	0.19	
6,272.0	10.39	273.57	6,131.2	-15.9	-1,195.7	295.0	1.16	-1.13	-1.41	
6,367.0	8.48	268.53	6,224.9	-15.6	-1,211.2	299.4	2.19	-2.01	-5.31	
6,461.0	6.77	267.72	6,318.1	-16.0	-1,223.7	302.2	1.82	-1.82	-0.86	
6,556.0	7.10	263.41	6,412.4	-16.9	-1,235.1	304.3	0.65	0.35	-4.54	
6,650.0	7.45	273.38	6,505.6	-17.2	-1,247.0	307.1	1.39	0.37	10.61	
6,745.0	6.87	274.52	6,599.9	-16.4	-1,258.8	311.0	0.63	-0.61	1.20	
6,840.0	6.98	272.42	6,694.2	-15.7	-1,270.2	314.6	0.29	0.12	-2.21	
6,934.0	6.07	272.00	6,787.6	-15.3	-1,280.9	317.8	0.97	-0.97	-0.45	
7,028.0	4.05	265.12	6,881.2	-15.4	-1,289.2	319.8	2.24	-2.15	-7.32	
7,122.0	2.66	259.98	6,975.1	-16.0	-1,294.6	320.6	1.51	-1.48	-5.47	
7,217.0	2.04	254.51	7,070.0	-16.9	-1,298.4	320.8	0.69	-0.65	-5.76	
7,311.0	1.14	242.69	7,163.9	-17.7	-1,300.9	320.6	1.01	-0.96	-12.57	
7,347.0	0.74	267.58	7,199.9	-17.9	-1,301.4	320.5	1.56	-1.11	69.14	
7,410.0	1.14	283.96	7,262.9	-17.8	-1,302.4	320.9	0.76	0.63	26.00	
7,442.0	2.64	347.51	7,294.9	-17.0	-1,302.9	321.8	7.39	4.69	198.59	
7,473.0	6.33	6.76	7,325.8	-14.6	-1,302.9	324.1	12.69	11.90	62.10	
7,504.0	10.46	12.21	7,356.5	-10.1	-1,302.1	328.2	13.55	13.32	17.58	
7,536.0	15.48	14.40	7,387.7	-3.2	-1,300.4	334.5	15.76	15.69	6.84	
7,568.0	20.93	12.38	7,418.0	6.6	-1,298.1	343.3	17.14	17.03	-6.31	
7,599.0	26.03	7.99	7,446.5	18.7	-1,296.0	354.5	17.38	16.45	-14.16	
7,630.0	30.07	4.56	7,473.8	33.2	-1,294.4	368.1	14.03	13.03	-11.06	
7,662.0	33.68	3.15	7,501.0	50.1	-1,293.3	384.1	11.52	11.28	-4.41	
7,693.0	36.76	0.69	7,526.3	67.9	-1,292.7	401.2	10.94	9.94	-7.94	
7,724.0	39.75	358.41	7,550.7	87.1	-1,292.9	419.7	10.66	9.65	-7.35	
7,756.0	43.79	358.41	7,574.5	108.4	-1,293.4	440.5	12.63	12.63	0.00	
7,787.0	47.31	358.58	7,596.2	130.5	-1,294.0	462.0	11.36	11.35	0.55	
7,818.0	51.79	358.32	7,616.3	154.1	-1,294.7	484.9	14.47	14.45	-0.84	
7,850.0	54.69	358.06	7,635.5	179.7	-1,295.5	509.9	9.09	9.06	-0.81	
7,881.0	54.69	358.14	7,653.4	205.0	-1,296.3	534.5	0.21	0.00	0.26	



Scientific Drilling Survey Report



Company:	Legend Natural Gas	Local Co-ordinate Reference:	Well Buckshot, State Com: 3H
Project:	Eddy County, New Mexico	TVD Reference:	KB @ 3077.0usft (Rig)
Site:	Buckshot State Com	MD Reference:	KB @ 3077.0usft (Rig)
Well:	Buckshot State Com 3H	North Reference:	Grid
Wellbore:	Side Track #1	Survey Calculation Method:	Minimum Curvature
Design:	Side Track #1	Database:	CompassC

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
7,913.0	53.99	358.23	7,672.1	231.0	-1,297.1	559.8	2.20	-2.19	0.28
7,944.0	53.46	358.32	7,690.4	256.0	-1,297.9	584.1	1.73	-1.71	0.29
7,976.0	52.94	358.32	7,709.6	281.6	-1,298.6	609.1	1.63	-1.63	0.00
8,007.0	51.97	358.49	7,728.5	306.2	-1,299.3	633.0	3.16	-3.13	0.55
8,039.0	52.23	358.49	7,748.1	331.4	-1,300.0	657.5	0.81	0.81	0.00
8,070.0	56.10	359.02	7,766.3	356.5	-1,300.5	681.9	12.56	12.48	1.71
8,101.0	60.50	359.46	7,782.5	382.9	-1,300.9	707.5	14.24	14.19	1.42
8,133.0	63.66	0.08	7,797.5	411.2	-1,301.0	734.8	10.02	9.88	1.94
8,164.0	63.93	0.16	7,811.2	439.0	-1,300.9	761.6	0.90	0.87	0.26
8,196.0	64.46	0.52	7,825.1	467.8	-1,300.8	789.4	1.94	1.66	1.13
8,227.0	64.63	0.69	7,838.5	495.8	-1,300.5	816.4	0.74	0.55	0.55
8,259.0	66.57	0.60	7,851.7	524.9	-1,300.1	844.4	6.07	6.06	-0.28
8,290.0	70.61	0.52	7,863.0	553.8	-1,299.9	872.2	13.03	13.03	-0.26
8,322.0	74.48	1.04	7,872.6	584.3	-1,299.4	901.6	12.19	12.09	1.63
8,353.0	78.88	1.66	7,879.7	614.4	-1,298.7	930.5	14.33	14.19	2.00
8,385.0	83.19	1.22	7,884.7	646.0	-1,297.9	960.8	13.54	13.47	-1.38
8,448.0	88.99	359.29	7,889.0	708.9	-1,297.7	1,021.4	9.70	9.21	-3.06
8,542.0	89.60	359.37	7,890.2	802.8	-1,298.8	1,112.5	0.65	0.65	0.09
8,636.0	89.87	359.55	7,890.6	896.8	-1,299.6	1,203.5	0.35	0.29	0.19
8,731.0	90.40	359.81	7,890.4	991.8	-1,300.2	1,295.3	0.62	0.56	0.27
8,826.0	90.13	359.55	7,889.9	1,086.8	-1,300.7	1,387.2	0.39	-0.28	-0.27
8,886.0	90.13	359.55	7,889.8	1,146.8	-1,301.2	1,445.3	0.00	0.00	0.00
8,920.0	90.48	359.64	7,889.6	1,180.8	-1,301.4	1,478.2	1.06	1.03	0.26
9,015.0	90.48	359.55	7,888.8	1,275.8	-1,302.1	1,570.1	0.09	0.00	-0.09
9,109.0	89.60	359.02	7,888.8	1,369.8	-1,303.3	1,661.2	1.09	-0.94	-0.56
9,204.0	89.43	359.99	7,889.6	1,464.8	-1,304.1	1,753.1	1.04	-0.18	1.02
9,298.0	90.40	0.43	7,889.7	1,558.8	-1,303.7	1,843.8	1.13	1.03	0.47
9,393.0	88.99	0.60	7,890.2	1,653.8	-1,302.9	1,935.3	1.49	-1.48	0.18
9,487.0	89.60	1.04	7,891.4	1,747.8	-1,301.5	2,025.7	0.80	0.65	0.47
9,582.0	90.13	1.48	7,891.6	1,842.7	-1,299.5	2,116.9	0.73	0.56	0.46
9,677.0	89.78	0.52	7,891.7	1,937.7	-1,297.8	2,208.2	1.08	-0.37	-1.01
9,771.0	91.36	1.13	7,890.7	2,031.7	-1,296.4	2,298.6	1.80	1.68	0.65
9,866.0	90.60	0.60	7,889.1	2,126.7	-1,295.0	2,390.0	0.98	-0.80	-0.56
9,960.0	90.84	0.52	7,887.9	2,220.7	-1,294.1	2,480.5	0.27	0.26	-0.09
10,054.0	89.52	359.90	7,887.6	2,314.7	-1,293.7	2,571.2	1.55	-1.40	-0.66
10,148.0	90.40	0.69	7,887.7	2,408.7	-1,293.3	2,661.8	1.26	0.94	0.84
10,243.0	89.43	359.99	7,887.8	2,503.7	-1,292.7	2,753.4	1.26	-1.02	-0.74
10,337.0	89.78	0.16	7,888.5	2,597.7	-1,292.6	2,844.2	0.41	0.37	0.18
10,432.0	90.22	0.43	7,888.5	2,692.7	-1,292.1	2,935.8	0.54	0.46	0.28
10,526.0	90.66	0.78	7,887.8	2,786.7	-1,291.1	3,026.3	0.60	0.47	0.37
10,621.0	90.66	0.43	7,886.7	2,881.6	-1,290.1	3,117.8	0.37	0.00	-0.37
10,716.0	90.31	359.64	7,885.9	2,976.6	-1,290.0	3,209.5	0.91	-0.37	-0.83
10,811.0	89.52	358.85	7,886.0	3,071.6	-1,291.3	3,301.5	1.18	-0.83	-0.83
10,905.0	90.40	359.20	7,886.1	3,165.6	-1,292.9	3,392.7	1.01	0.94	0.37

Company:	Legend Natural Gas	Local Co-ordinate Reference:	Well: Buckshot State Com 3H
Project:	Eddy County, New Mexico	TVD Reference:	KB @ 3077.0usft (Rig)
Site:	Buckshot State Com	MD Reference:	KB @ 3077.0usft (Rig)
Well:	Buckshot State Com 3H	North Reference:	Grid
Wellbore:	Side Track #1	Survey Calculation Method:	Minimum Curvature
Design:	Side Track #1	Database:	CompassC

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
10,999.0	90.40	359.37	7,885.4	3,259.6	-1,294.1	3,483.8	0.18	0.00	0.18
11,092.0	90.66	359.64	7,884.6	3,352.6	-1,294.9	3,573.8	0.40	0.28	0.29
11,186.0	90.75	0.08	7,883.4	3,446.6	-1,295.1	3,664.6	0.48	0.10	0.47
11,281.0	90.22	0.08	7,882.6	3,541.6	-1,295.0	3,756.3	0.56	-0.56	0.00
11,375.0	89.96	0.16	7,882.5	3,635.6	-1,294.8	3,847.1	0.29	-0.28	0.09
11,470.0	89.52	0.34	7,882.9	3,730.6	-1,294.3	3,938.7	0.50	-0.46	0.19
11,564.0	89.34	0.78	7,883.8	3,824.6	-1,293.4	4,029.2	0.51	-0.19	0.47
11,658.0	90.13	1.04	7,884.3	3,918.6	-1,291.9	4,119.6	0.88	0.84	0.28
11,752.0	90.31	1.57	7,883.9	4,012.5	-1,289.8	4,209.8	0.60	0.19	0.56
11,846.0	89.87	359.90	7,883.7	4,106.5	-1,288.6	4,300.3	1.84	-0.47	-1.78
11,940.0	90.57	359.90	7,883.4	4,200.5	-1,288.8	4,391.1	0.74	0.74	0.00
12,000.0	90.57	359.90	7,882.8	4,260.5	-1,288.9	4,449.0	0.00	0.00	0.00
12,035.0	90.84	0.43	7,882.4	4,295.5	-1,288.8	4,482.8	1.70	0.77	1.51
12,129.0	90.48	0.08	7,881.3	4,389.5	-1,288.3	4,573.5	0.53	-0.38	-0.37
12,223.0	90.75	0.52	7,880.3	4,483.5	-1,287.8	4,664.1	0.55	0.29	0.47
12,318.0	89.87	0.52	7,879.8	4,578.5	-1,287.0	4,755.6	0.93	-0.93	0.00
12,412.0	90.13	0.34	7,879.8	4,672.5	-1,286.3	4,846.2	0.34	0.28	-0.19
12,506.0	90.57	1.04	7,879.2	4,766.5	-1,285.1	4,936.7	0.88	0.47	0.74
12,553.0	90.75	0.96	7,878.6	4,813.5	-1,284.3	4,981.9	0.42	0.38	-0.17
12,613.0	90.75	0.96	7,877.8	4,873.5	-1,283.3	5,039.5	0.00	0.00	0.00
3H BHL									

Design Annotations				
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
12,553.0	7,878.6	4,813.5	-1,284.3	SDI MWD
12,613.0	7,877.8	4,873.5	-1,283.3	Bit Projection

Checked By: _____ Approved By: _____ Date: _____