Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR RUREALLOE LAND MANAGEMENT

RECEIVED)	Ì
007 -		L

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

B	UREAU OF LAND MANAG	EMENT	I OCT O	0		July 31, 2010	
SUNDRY NOTICES AND REPORTS ON WELLS			3 2013	5. Lease Serial No. NMLC029395A			
Do not use this form for proposals to drill or to re-enter an CD ARTESIA If Indian, abandoned well. Use form 3160-3 (APD) for such proposals CD ARTESIA If Indian,				6. If Indian, Allottee c	r Tribe Name		
SUBMIT IN TRI	PLICATE - Other instruct	ions on rev	erse side.		7. If Unit or CA/Agree	ement, Name and/or No.	
1. Type of Well	V 1 F-1080				8. Well Name and No. TURNER A 033		
② Oil Well ☐ Gas Well ☐ Oth 2. Name of Operator		ERRY B CA	ALLAHAN		9. API Well No.		
LINN ENERGY	E-Mail: tcallahan@li	nnenergy.cor	n n		30-015-05231		
3a. Address 600 TRAVIS STREET, SUITE HOUSTON, TX 77002	5100	3b. Phone No Ph: 281-84	. (include area code) 0-4272		10. Field and Pool, or Exploratory GRAYBURG JACKSON;SR-Q-G-S		
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description)				11. County or Parish, and State		
Sec 18 T17S R31E Mer NMP 32.831802 N Lat, 103.910191		-			EDDY COUNTY	′, NM	
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATE	NATURE OF 1	NOTICE, RI	EPORT, OR OTHE	R DATA	
TYPE OF SUBMISSION			TYPE OF	ACTION			
Notice of Intent	☐ Acidize	☐ Dee	pen	☐ Product	ion (Start/Resume)	☐ Water Shut-Off	
_	☐ Alter Casing	☐ Frac	ture Treat	□ Reclam:	ation	■ Well Integrity	
☐ Subsequent Report	Casing Repair	□ Nev	Construction	☐ Recomp	lete	☐ Other	
☐ Final Abandonment Notice	☐ Change Plans		g and Abandon		arily Abandon		
	Convert to Injection	Plug	,	☐ Water D			
13. Describe Proposed or Completed Ope If the proposal is to deepen direction. Attach the Bond under which the wor following completion of the involved testing has been completed. Final At determined that the site is ready for final.	ally or recomplete horizontally, gind will be performed or provide the operations. If the operation results and onment Notices shall be filed	ive subsurface ne Bond No. on Its in a multipl	locations and measu of file with BLM/BIA e completion or reco	red and true ve Required sulp mpletion in a re ing reclamation	rtical depths of all pertin osequent reports shall be new interval, a Form 316 n, have been completed, a	ent markers and zones. filed within 30 days 0-4 shall be filed once and the operator has	
PROPOSED P&A PROCEDU	RES:				SEE ATTACHE		
1. MIRU P&A RIG. RIG.W/ TE	3G. TAG CMT @ 1715'+/-	. CIRC MU	D LADEN FLUID) (CONDITIONS	OF APPROVAL	
2. SPOT 30 SXS CMT @ 130	0- WOC AND TAG.	forat.	Z @ 13E	0, 50	z cmt y	0 1200'	
3. PERF 7" CSG @,569'. CIF							
4. CUTOFF WELLHEAD. IN:	STALL MARKER. RDMO.	AH c	ut-off	verity	ent to.	surf all	
ATTACHED CURRENT & PR			annulus	. R.	nedial	ent may	
be required, RECLAMATION PROCEDURE				,			
14. I hereby certify that the foregoing is	true and correct.		<u> </u>				
	Electronic Submission #22 For LINN Committed to AFMSS for pr	I ENERGY,	sent to the Carlsb	ad	•		
Name(Printed/Typed) TERRY B	CALLAHAN		Title REG CO	OMPLIANCE	SPECIALIST III		
Signature (Electronic S	ubmission)		Date 09/25/20	013	Accepted t		
	THIS SPACE FOR	RFEDERA	L OR STATE	OFFICE U	SE	, , , , , , , , , , , , , , , , , , , ,	
Approved By James	Q. amos		Title _S,	EPS		Date 10-20-1	
Conditions of approval, if any, are attached ertify that the applicant holds legal or equ which would entitle the applicant to condu	itable title to those rights in the s	ot warrant or ubject lease	Office C1	<i>CO</i>			
7							

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

	Occiding of Septembers 9/14/1988 LSRF 2,005' (nat with 190 g), nitter phrevin	Atid or fyritus tyretnent Ditelik 9/EU/1856 i 1,963*1,000's skat with 190 att misor@kretin	Paris Peris (Paristration) Red (Paristration) Red (Paristration) Red (Paristration)	1 stad Here Size: Fred City: Fred City: Capacity (bisk/th): Capac	Dist. 2007	,DC2-186
El 2000 (100 (100 (100 (100 (100 (100 (100		NG-55278 - 121 ~ 127 ~ 127 127 127 127 127 127 127 127 127 127	BOOMS ON THE STATE OF THE STATE	tage of the control o	1,362'.69"	Oppe Hole from 1935: 2307
Cursut.			and the second light of th		Pies	TD: 2.007'
Word Pases Turner A 833 Word Pases Turner A 833 Word Pases Turner A 833 Word Pases Word Pases	Dies 1974 (1981) 1924 (1971) Tode & Cook to \$177; Set \$-\$40°, csp @ 177 & cmid w/ 100 secret. Dillard Thick to 1993 & 1974 (1982) 1995 (1982) 1995 (1983) Tode @ 1982 (1982) Tode @ 1982					

We3 Name:	Turner A #33			
	Locations			
Location	ISSOFNL JUST FEL.			
Section:	T: 173 R: 31£ Sec: 18			
Bleck:				
SUPPRY				
Capely:	{66;			
lat/tore:				
i lest:	lenn Grayburg taifirma			
	Elevetions;			
Gi:-	3762'.			
Dr.				
KB-G2 Cole:				
ck mflns?				

Lacaira Regularmenta		 	
	_		

Date	
0/2 6/ 1553	Spird 12/1/2" hare A drid to 570; Set 3-5/8" CLE @ 570' & could w/ 100 to cont. Orifled 9" hale to 1995 & test 3" cup @ same w/ 50 to cont. Orifle 6 hale to 0 @ 1007.
9/19/1951	1935-1005 that with 199 at p. Nico-giverin Character at BTD. Herial E.C. (21) Cay for their from 1937-1007 and performed from 1963-407 and 1997-1007; July 47-377 the in 2005, All of pump E. prod equip. March 33 Mills in 34 bry on
9/22/1753	9/17/1957 PCH w/ Lbg. Capped well with 2000s WOG yalve, We'll 14'd (wheepnomical to produce, well on
3/7/1973	materflood project)
3/29/1979	Bradenhead was piped to surface w/ a valve to staffed for pressure checks in accordance w/ OCD
9/3/1964	Riff m/ tipg to 1860', Dump ZIGOS 2D/2D sand, PU to 1004' & let sand settle, first & tag sand @ 1810', Dump 30 set ami on sand, PU to 500', Revalle, POH m/ tag, RDMD, Well is TA'd,
	Plus & Abandon Procedures
	Rise m/ sing. Tag cmi (9 3715" of-, chr; 4415.
	Spot 10to com @ 1300, WOC Ling.
	Perl T' cog @ \$47'. Die emi to jurfeen ineife & aut mf approx 1551e emi.
	Cul off web heef and inital dry hole marker.
-	
 	
	<u> </u>

Proposed Wellbare Diagram



Spud Date: W3D Update 9/36/1853 9/34/3018, L. William

tumes 4 413

30 DIS-03231

Hole Stre: Surf Ceg: Certaint Bland: Depth: TOC: 12-1/1" 9-5/8", 178, 1-55 50-52 570' N/A

Hote Site: Int. Sec. 2", 204, 355 Coment Bigart. 50 111 Retains TOE: N/A

Well Nother

API No:

| Data||18 ad Pariferiations | 1,062 - 2,004" start with 130 gas nitro-africants | 1,062 - 2,004" start with 130 gas nitro-africants

Acid or Freque Trestment Details

9/20/1953

1,962'-2,004' shot with 190 ats nitro-gives in

Spot JOre end @ 1300

Ore 155 or cont to work

9-5/4", 140 set @ 570 Pert @ \$45

Tubing Detail		
ideas	Description:	
	2-9/8°	
Phi Depth		

Red Detail (rop to horrorm)		
Rodi	Description	

Pumping Unit:

Tag cmt @ 1715" of-

30 secretion top of seed send according

7", 204, 141 @ 1915"

1,951' 69'

1,954'-2,001'

Prod Cag; Copercity [bb//t]; Coment Bland Heturns; IOC; Depth

2007

5-1/2", 17#

0074

TD: 2,007

Satif

Open Hote from 1915'-2007'

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

Requirements for dry hole markers in Prairie Chicken Habitat <u>Well Identification Markers</u> Conditions of Approval (COA)

The BLM Carlsbad Field Office (CFO) Conditions of Approval (COA) have required that ground level dry hole markers be placed on wells within the Lesser Prairie Chicken habitat area. Onshore Order 2.III.G.10 allows for surface caps to be installed at the base of the cellar of a minimum of 3 feet below the restored ground level. Therefore, these markers shall be set a minimum of 3 feet below the restored ground level. All markers shall be identified by GPS coordinates.

The dry hole markers will be to the following specifications. The operator will construct the markers as follows:

- 1. A steel plate 1/4 inch thick shall be placed on the wellbore, welded in place and with a weep hole.
- 2. Aluminum data plates may be bolted to the steel plate with minimum ¼ inch bolts and locking nuts or self tapping fine threaded screws. A minimum of one in each corner is to be installed on each plate.
- 3. An 8 inch x 8 inch aluminum plate, which is 12 gauge or .080 sign material (1/8 inch aluminum plate may be used in place of the .080 plate) with the required information for that well stamped or engraved in a minimum 3/8 inch tall letter or number.
- 4. The following information will be stamped or engraved on the 8 inch X 8 inch aluminum plate in the following order.
 - a. First row: Operator's name
 - b. Second row: Well name and number
 - c. Third row: Legal location to include ¼ ¼, Section, Township, and range. If the legal location cannot be placed on one row it can be split into two rows with the ¼ ¼ (example: 1980 FNL 1980 FWL) being on the top row.
 - d. Fourth row: Lease Number and API number.
 - i. Example marker plate: (attached)

Notification to NMOCD of this marker type will be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground level dry hole marker was installed and GPS coordinates recorded as required in the COAs from the BLM.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- 1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Inspection & Enforcement

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909, 575-361-2648 (Cell)

Mike Burton Environmental Protection Specialist 575-234-2226

Jeffery Robertson
Natural Resource Specialist
575-234-2230

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Doug Hoag Civil Engineering Technician 575-234-5979

Linda Denniston Environmental Protection Specialist 575-234-5974

Solomon Hughes Natural Resource Specialist 575-234-5951

Permitting

Cody Layton Natural Resource Specialist 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Todd Suter Surface Protection Specialist 575-234-5987

Tanner Nygren Natural Resource Specialist 575-234-5975

Amanda Lynch Natural Resource Specialist 575-234-5922

Legion Brumley Environmental Protection Specialist 575-234-5957

Realty, Compliance

Randy Pair Environmental Protection Specialist 575-234-6240