

Submit 1 Copy To Appropriate District Office
District I -- (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II -- (575) 748-1283
811 S. First St., Artesia, NM 88210
District III -- (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV -- (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-41731
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Mewbourne Oil Company		6. State Oil & Gas Lease No. B-7717-13
3. Address of Operator PO Box 5270, Hobbs NM 88241		7. Lease Name or Unit Agreement Name Zircon "I" HE State
4. Well Location Unit Letter <u>H</u> : <u>1700</u> feet from the <u>North</u> line and <u>260</u> feet from the <u>East</u> line Section <u>1</u> Township <u>19S</u> Range <u>29E</u> NMPM Eddy County		8. Well Number 2H
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3420' GL		9. OGRID Number 14744
		10. Pool name or Wildcat Turkey Track Bone Spring 60660

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☒
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☒
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐


OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/01/13.. TD'd 12 1/4" hole @ 1504'. Ran 1504' of 9 3/4" 36# J55 LT&C csg. Cemented with 350 sks BJ Lite Class "C" w/additives. Mixed @ 13.5 #/g w/ 1.49 yd. Tail w/200 sks Class C w/1% CaCl2. Mixed @ 14.8#/g w/1.33 yd. Plug down @ 1:45 A.M. 12/01/13. Did not circ cmt. Slow rate lift pressure 400 @ 2 BPM. Ran temp survey indicating TOC @ 300'. PU 1" pipe & tag @ 290'. Cmt in 1 stage w/122 sks Class C neat. Circ 10 sks cement to pit. At 9:00 P.M. 12/01/13, tested csg to 1500# for 30 min, held OK. WOC. Drilled out with 8 3/4" bit.

Spud Date: 11/27/2013

Rig Release Date:



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Regulatory DATE 12/06/13

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: [Signature] TITLE Dist H Supervisor DATE 12/9/13

Conditions of Approval (if any):

4