Submit 1 Copy To Appropriate District State of New Me	xico	- Form C-103	
Office District 1 – (575) 393-6161 Energy, Minerals and Nat	BesonverD	Revised July 18, 2013	
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.	
District II - (575) 748-1283 811 S. First St., Artesia, NM 88210 OIL CONSERVATION	UDIVISION 13	30-015-38512	
811 S. First St., Artesia, NM 88210 District III – (505) 334-6178 1220 South St. Frau	ncis Dr.	5 Indicate Type of Lease	
1000 Bio Branco Bd. Arton NM 97410	IQCO ARTESI	STATE FEE	
$\frac{\text{District IV}}{\text{District IV}} = (505) 476-3460$ Santa Fe, NM 87410 Santa Fe, NM 87410	1303	6. State Oil & Gas Lease No.	
1220 S. St. Francis Dr., Santa Fe, NM 87505			
SUNDRY NOTICES AND REPORTS ON WELLS	3	7. Lease Name or Unit Agreement Name	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PL		ENRON STATE	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FO	OR SUCH		
PROPOSALS.)         1. Type of Well: Oil Well         Image: Contract of Contra	1	8. Well Number #16	
2. Name of Operator		9. OGRID Number 281994	
LRE OPERATING, LLC		3. OOKID Number 281334	
3. Address of Operator		10. Pool name or Wildcat	
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401		Red Lake, Glorieta-Yeso NE (96836)	
, , , , , , , , , , , , , , , , , , ,		Red Lake, Queen-Grayburg-San Andres (51300)	
4. Well Location			
Unit Letter D(Lot#1) : 990 feet from the North line and 940 feet from the West line			
Section 31 Township 17-S	Range 28-E	NMPM Eddy County	
11. Elevation (Snow whether DR, RRD, R1, OR, etc.)			
3636' GL		and the second	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
		<u> </u>	
<u> </u>	CASING/CEMENT	JOB []	
CLOSED-LOOP SYSTEM	OTHER: Reco	omplete to San Andres & DHC	
13. Describe proposed or completed operations. (Clearly state all pertinent details,	1		
SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore of	diagram of proposed comp	etion or recompletion.	
On 11/25/13, MIRUSU. TOH w/rods, pump & tbg. Set 5-1/2" CB			
lower San Andres (SA) @ 2752', 60', 68', 76', 84', 94', 2802', 10'	, 18 <sup>7</sup> , 26', 34', 42', {	50', 58', 66', 74', 84', 94', 2903', 14', 24',	
34', 42', 52', 60', 68', 76', 84', 94', 3002', 10', 18', 26', 34' w/1-0.4			
	HCL acid & 51 perf balls. Fraced lower SA w/67,134# 16/30 Arizona & 16,265# 16/30 resin coated sand in 20# X-linked gel.		
Set 5-1/2" CBP @ 2731'. PT csg & CBP to 3500 psi-OK. Perfed middle SA @ 2400', 08', 20', 28', 38', 46', 52', 64', 72', 82',			
		0', 08', 20', 28', 38', 46', 52', 64', 72', 82',	
	14', 22', 32', 42', 5	D', 08', 20', 28', 38', 46', 52', 64', 72', 82', 2', 60', 68', 78', 86', 94', 2702', 10' w/1-	
0.41" spf. Total 36 holes. Treated perfs w/3374 gal 15% HCL ac	14', 22', 32', 42', 5	D', 08', 20', 28', 38', 46', 52', 64', 72', 82', 2', 60', 68', 78', 86', 94', 2702', 10' w/1-	
0.41" spf. Total 36 holes. Treated perfs w/3374 gal 15% HCL ac 19,976# 16/30 resin coated sand in 20# X-linked gel.	14', 22', 32', 42', 5 cid & 54 perf balls.	0', 08', 20', 28', 38', 46', 52', 64', 72', 82', 2', 60', 68', 78', 86', 94', 2702', 10' w/1- Fraced w/79,890# 16/30 Arizona &	
Set 5-1/2" CBP @ 2385'. PT csg to 3500 psi-OK. Perfed upper	14', 22', 32', 42', 5. cid & 54 perf balls. SA @ 2120', 27', 3	0', 08', 20', 28', 38', 46', 52', 64', 72', 82', 2', 60', 68', 78', 86', 94', 2702', 10' w/1- Fraced w/79,890# 16/30 Arizona & 4', 40', 52', 60', 67', 75', 82', 88', 96',	
0.41" spf. Total 36 holes. Treated perfs w/3374 gal 15% HCL ac 19,976# 16/30 resin coated sand in 20# X-linked gel. Set 5-1/2" CBP @ 2385'. PT csg to 3500 psi-OK. Perfed upper 2204', 12', 19', 28', 36', 44', 52', 58', 70', 80', 90', 98', 2307', 16',	14', 22', 32', 42', 5 cid & 54 perf balls. SA @ 2120', 27', 3 24', 32', 40', 48', 5	0', 08', 20', 28', 38', 46', 52', 64', 72', 82', 2', 60', 68', 78', 86', 94', 2702', 10' w/1- Fraced w/79,890# 16/30 Arizona & 4', 40', 52', 60', 67', 75', 82', 88', 96', 6', 62', 70' w/1-0.41" spf. Total 32 holes.	
0.41" spf. Total 36 holes. Treated perfs w/3374 gal 15% HCL ac 19,976# 16/30 resin coated sand in 20# X-linked gel. Set 5-1/2" CBP @ 2385'. PT csg to 3500 psi-OK. Perfed upper 2204', 12', 19', 28', 36', 44', 52', 58', 70', 80', 90', 98', 2307', 16', Treated perfs w/3523 gal 15% HCL acid & 48 perf balls. Fraced	14', 22', 32', 42', 5 cid & 54 perf balls. SA @ 2120', 27', 3 24', 32', 40', 48', 5	0', 08', 20', 28', 38', 46', 52', 64', 72', 82', 2', 60', 68', 78', 86', 94', 2702', 10' w/1- Fraced w/79,890# 16/30 Arizona & 4', 40', 52', 60', 67', 75', 82', 88', 96', 6', 62', 70' w/1-0.41" spf. Total 32 holes.	
0.41" spf. Total 36 holes. Treated perfs w/3374 gal 15% HCL ac 19,976# 16/30 resin coated sand in 20# X-linked gel. Set 5-1/2" CBP @ 2385'. PT csg to 3500 psi-OK. Perfed upper 2204', 12', 19', 28', 36', 44', 52', 58', 70', 80', 90', 98', 2307', 16', Treated perfs w/3523 gal 15% HCL acid & 48 perf balls. Fraced sand in 20# X-linked gel.	14', 22', 32', 42', 5 cid & 54 perf balls. SA @ 2120', 27', 3 24', 32', 40', 48', 5 w/67,676# 16/30 A	0', 08', 20', 28', 38', 46', 52', 64', 72', 82', 2', 60', 68', 78', 86', 94', 2702', 10' w/1- Fraced w/79,890# 16/30 Arizona & 4', 40', 52', 60', 67', 75', 82', 88', 96', 6', 62', 70' w/1-0.41" spf. Total 32 holes. rizona & 22,313# 16/30 resin coated	
0.41" spf. Total 36 holes. Treated perfs w/3374 gal 15% HCL ac 19,976# 16/30 resin coated sand in 20# X-linked gel. Set 5-1/2" CBP @ 2385'. PT csg to 3500 psi-OK. Perfed upper 2204', 12', 19', 28', 36', 44', 52', 58', 70', 80', 90', 98', 2307', 16', Treated perfs w/3523 gal 15% HCL acid & 48 perf balls. Fraced sand in 20# X-linked gel. On 11/8/13, drilled CBPs @ 2385', 2731' & 3180' & CO to PBTD3	14', 22', 32', 42', 5. sid & 54 perf balls. SA @ 2120', 27', 3 24', 32', 40', 48', 5 w/67,676# 16/30 A 3596'. On 12/10/13	0', 08', 20', 28', 38', 46', 52', 64', 72', 82', 2', 60', 68', 78', 86', 94', 2702', 10' w/1- Fraced w/79,890# 16/30 Arizona & 4', 40', 52', 60', 67', 75', 82', 88', 96', 6', 62', 70' w/1-0.41" spf. Total 32 holes. rizona & 22,313# 16/30 resin coated 3, landed 2-7/8" 6.5# J-55 tbg @ 3533'.	
0.41" spf. Total 36 holes. Treated perfs w/3374 gal 15% HCL ac 19,976# 16/30 resin coated sand in 20# X-linked gel. Set 5-1/2" CBP @ 2385'. PT csg to 3500 psi-OK. Perfed upper 2204', 12', 19', 28', 36', 44', 52', 58', 70', 80', 90', 98', 2307', 16', Treated perfs w/3523 gal 15% HCL acid & 48 perf balls. Fraced sand in 20# X-linked gel. On 11/8/13, drilled CBPs @ 2385', 2731' & 3180' & CO to PBTD2 Ran pump & rods. Released completion rig on 12/10/13. Compl	14', 22', 32', 42', 5 5 5 5 5 6 5 7 5 7 5 5 7 5 5 7 5 7 5 7 5	0', 08', 20', 28', 38', 46', 52', 64', 72', 82', 2', 60', 68', 78', 86', 94', 2702', 10' w/1- Fraced w/79,890# 16/30 Arizona & 4', 40', 52', 60', 67', 75', 82', 88', 96', 6', 62', 70' w/1-0.41" spf. Total 32 holes. rizona & 22,313# 16/30 resin coated 3, landed 2-7/8" 6.5# J-55 tbg @ 3533'.	
0.41" spf. Total 36 holes. Treated perfs w/3374 gal 15% HCL ac 19,976# 16/30 resin coated sand in 20# X-linked gel. Set 5-1/2" CBP @ 2385'. PT csg to 3500 psi-OK. Perfed upper 2204', 12', 19', 28', 36', 44', 52', 58', 70', 80', 90', 98', 2307', 16', Treated perfs w/3523 gal 15% HCL acid & 48 perf balls. Fraced sand in 20# X-linked gel. On 11/8/13, drilled CBPs @ 2385', 2731' & 3180' & CO to PBTD3	14', 22', 32', 42', 5 5 5 5 5 6 5 7 5 7 5 5 7 5 5 7 5 7 5 7 5	0', 08', 20', 28', 38', 46', 52', 64', 72', 82', 2', 60', 68', 78', 86', 94', 2702', 10' w/1- Fraced w/79,890# 16/30 Arizona & 4', 40', 52', 60', 67', 75', 82', 88', 96', 6', 62', 70' w/1-0.41" spf. Total 32 holes. rizona & 22,313# 16/30 resin coated 3, landed 2-7/8" 6.5# J-55 tbg @ 3533'.	
0.41" spf. Total 36 holes. Treated perfs w/3374 gal 15% HCL ac 19,976# 16/30 resin coated sand in 20# X-linked gel. Set 5-1/2" CBP @ 2385'. PT csg to 3500 psi-OK. Perfed upper 2204', 12', 19', 28', 36', 44', 52', 58', 70', 80', 90', 98', 2307', 16', Treated perfs w/3523 gal 15% HCL acid & 48 perf balls. Fraced sand in 20# X-linked gel. On 11/8/13, drilled CBPs @ 2385', 2731' & 3180' & CO to PBTD2 Ran pump & rods. Released completion rig on 12/10/13. Compl <i>two oil pools have a blanket DHC order (19.15.12.11E): ART-46</i>	14', 22', 32', 42', 5 cid & 54 perf balls. SA @ 2120', 27', 3 24', 32', 40', 48', 5 w/67,676# 16/30 A 3596'. On 12/10/13 eted as a comming <u>09N.</u>	0', 08', 20', 28', 38', 46', 52', 64', 72', 82', 2', 60', 68', 78', 86', 94', 2702', 10' w/1- Fraced w/79,890# 16/30 Arizona & 4', 40', 52', 60', 67', 75', 82', 88', 96', 6', 62', 70' w/1-0.41" spf. Total 32 holes. rizona & 22,313# 16/30 resin coated 3, landed 2-7/8" 6.5# J-55 tbg @ 3533'.	
0.41" spf. Total 36 holes. Treated perfs w/3374 gal 15% HCL ac         19,976# 16/30 resin coated sand in 20# X-linked gel.         Set 5-1/2" CBP @ 2385'. PT csg to 3500 psi-OK. Perfed upper 2204', 12', 19', 28', 36', 44', 52', 58', 70', 80', 90', 98', 2307', 16',         Treated perfs w/3523 gal 15% HCL acid & 48 perf balls. Fraced sand in 20# X-linked gel.         On 11/8/13, drilled CBPs @ 2385', 2731' & 3180' & CO to PBTD2         Ran pump & rods. Released completion rig on 12/10/13. Compl two oil pools have a blanket DHC order (19.15.12.11E): ART-464         Spud Date:       8/11/11         Drilling Rig	14', 22', 32', 42', 5 cid & 54 perf balls. SA @ 2120', 27', 3 24', 32', 40', 48', 5 w/67,676# 16/30 A 3596'. On 12/10/1; eted as a comming <u>09N.</u> Release Date:	2', 08', 20', 28', 38', 46', 52', 64', 72', 82', 2', 60', 68', 78', 86', 94', 2702', 10' w/1- Fraced w/79,890# 16/30 Arizona & 4', 40', 52', 60', 67', 75', 82', 88', 96', 6', 62', 70' w/1-0.41" spf. Total 32 holes. rizona & 22,313# 16/30 resin coated 3, landed 2-7/8" 6.5# J-55 tbg @ 3533'. led Yeso / San Andres oil well. <u>These</u> 8/19/11	
0.41" spf. Total 36 holes. Treated perfs w/3374 gal 15% HCL ac         19,976# 16/30 resin coated sand in 20# X-linked gel.         Set 5-1/2" CBP @ 2385'. PT csg to 3500 psi-OK. Perfed upper 2204', 12', 19', 28', 36', 44', 52', 58', 70', 80', 90', 98', 2307', 16',         Treated perfs w/3523 gal 15% HCL acid & 48 perf balls. Fraced sand in 20# X-linked gel.         On 11/8/13, drilled CBPs @ 2385', 2731' & 3180' & CO to PBTD2         Ran pump & rods. Released completion rig on 12/10/13. Compl two oil pools have a blanket DHC order (19.15.12.11E): ART-464         Spud Date:       8/11/11         Drilling Rig	14', 22', 32', 42', 5 cid & 54 perf balls. SA @ 2120', 27', 3 24', 32', 40', 48', 5 w/67,676# 16/30 A 3596'. On 12/10/1; eted as a comming <u>09N.</u> Release Date:	2', 08', 20', 28', 38', 46', 52', 64', 72', 82', 2', 60', 68', 78', 86', 94', 2702', 10' w/1- Fraced w/79,890# 16/30 Arizona & 4', 40', 52', 60', 67', 75', 82', 88', 96', 6', 62', 70' w/1-0.41" spf. Total 32 holes. rizona & 22,313# 16/30 resin coated 3, landed 2-7/8" 6.5# J-55 tbg @ 3533'. led Yeso / San Andres oil well. <u>These</u> 8/19/11	
0.41" spf. Total 36 holes. Treated perfs w/3374 gal 15% HCL ac 19,976# 16/30 resin coated sand in 20# X-linked gel. Set 5-1/2" CBP @ 2385'. PT csg to 3500 psi-OK. Perfed upper 2204', 12', 19', 28', 36', 44', 52', 58', 70', 80', 90', 98', 2307', 16', Treated perfs w/3523 gal 15% HCL acid & 48 perf balls. Fraced sand in 20# X-linked gel. On 11/8/13, drilled CBPs @ 2385', 2731' & 3180' & CO to PBTD2 Ran pump & rods. Released completion rig on 12/10/13. Compl <i>two oil pools have a blanket DHC order (19.15.12.11E): ART-46</i> Spud Date: 8/11/11 Drilling Rig I hereby certify that the information above is true and complete to the b	14', 22', 32', 42', 5 cid & 54 perf balls. SA @ 2120', 27', 3 24', 32', 40', 48', 5 w/67,676# 16/30 A 3596'. On 12/10/1; eted as a comming <u>09N.</u> Release Date:	2', 08', 20', 28', 38', 46', 52', 64', 72', 82', 2', 60', 68', 78', 86', 94', 2702', 10' w/1- Fraced w/79,890# 16/30 Arizona & 4', 40', 52', 60', 67', 75', 82', 88', 96', 6', 62', 70' w/1-0.41" spf. Total 32 holes. rizona & 22,313# 16/30 resin coated 3, landed 2-7/8" 6.5# J-55 tbg @ 3533'. led Yeso / San Andres oil well. <u>These</u> 8/19/11 and belief.	
0.41" spf. Total 36 holes. Treated perfs w/3374 gal 15% HCL ac 19,976# 16/30 resin coated sand in 20# X-linked gel. Set 5-1/2" CBP @ 2385'. PT csg to 3500 psi-OK. Perfed upper 2 2204', 12', 19', 28', 36', 44', 52', 58', 70', 80', 90', 98', 2307', 16', Treated perfs w/3523 gal 15% HCL acid & 48 perf balls. Fraced sand in 20# X-linked gel. On 11/8/13, drilled CBPs @ 2385', 2731' & 3180' & CO to PBTD2 Ran pump & rods. Released completion rig on 12/10/13. Compl <i>two oil pools have a blanket DHC order (19.15.12.11E): ART-46</i> Spud Date: 8/11/11 Drilling Rig I hereby certify that the information above is true and complete to the b	14', 22', 32', 42', 5 sid & 54 perf balls. SA @ 2120', 27', 3 24', 32', 40', 48', 5 w/67,676# 16/30 A 3596'. On 12/10/13 eted as a comming <u>09N.</u> Release Date: est of my knowledge	2', 08', 20', 28', 38', 46', 52', 64', 72', 82', 2', 60', 68', 78', 86', 94', 2702', 10' w/1- Fraced w/79,890# 16/30 Arizona & 4', 40', 52', 60', 67', 75', 82', 88', 96', 6', 62', 70' w/1-0.41" spf. Total 32 holes. rizona & 22,313# 16/30 resin coated 3, landed 2-7/8" 6.5# J-55 tbg @ 3533'. led Yeso / San Andres oil well. <u>These</u> 8/19/11 and belief.	
0.41" spf. Total 36 holes. Treated perfs w/3374 gal 15% HCL ac         19,976# 16/30 resin coated sand in 20# X-linked gel.         Set 5-1/2" CBP @ 2385'. PT csg to 3500 psi-OK. Perfed upper 2204', 12', 19', 28', 36', 44', 52', 58', 70', 80', 90', 98', 2307', 16',         Treated perfs w/3523 gal 15% HCL acid & 48 perf balls. Fraced sand in 20# X-linked gel.         On 11/8/13, drilled CBPs @ 2385', 2731' & 3180' & CO to PBTDD:         Ran pump & rods. Released completion rig on 12/10/13. Compl two oil pools have a blanket DHC order (19.15.12.11E): ART-464         Spud Date:       8/11/11         Drilling Rig         I hereby certify that the information above is true and complete to the b         SIGNATURE       Mike Pippin         E-mail address	14', 22', 32', 42', 5 cid & 54 perf balls. SA @ 2120', 27', 3 24', 32', 40', 48', 5 w/67,676# 16/30 A 3596'. On 12/10/13 eted as a comming <u>09N.</u> Release Date: est of my knowledge <u>bleum Engineer - Ag</u>	D', 08', 20', 28', 38', 46', 52', 64', 72', 82',         2', 60', 68', 78', 86', 94', 2702', 10' w/1-         Fraced w/79,890# 16/30 Arizona &         4', 40', 52', 60', 67', 75', 82', 88', 96',         6', 62', 70' w/1-0.41" spf. Total 32 holes.         rizona & 22,313# 16/30 resin coated         3, landed 2-7/8" 6.5# J-55 tbg @ 3533'.         Ided Yeso / San Andres oil well. These         8/19/11         and belief.         DATE 12/12/13	
0.41" spf. Total 36 holes. Treated perfs w/3374 gal 15% HCL ac 19,976# 16/30 resin coated sand in 20# X-linked gel. Set 5-1/2" CBP @ 2385'. PT csg to 3500 psi-OK. Perfed upper 2 2204', 12', 19', 28', 36', 44', 52', 58', 70', 80', 90', 98', 2307', 16', Treated perfs w/3523 gal 15% HCL acid & 48 perf balls. Fraced sand in 20# X-linked gel. On 11/8/13, drilled CBPs @ 2385', 2731' & 3180' & CO to PBTD2 Ran pump & rods. Released completion rig on 12/10/13. Compl two oil pools have a blanket DHC order (19.15.12.11E): ART-460 Spud Date: 8/11/11 Drilling Rig I hereby certify that the information above is true and complete to the b SIGNATURE Miller Complexity of the information above is true and complete to the b	14', 22', 32', 42', 5 cid & 54 perf balls. SA @ 2120', 27', 3 24', 32', 40', 48', 5 w/67,676# 16/30 A 3596'. On 12/10/13 eted as a comming <u>09N.</u> Release Date: est of my knowledge <u>bleum Engineer - Ag</u>	D', 08', 20', 28', 38', 46', 52', 64', 72', 82',         2', 60', 68', 78', 86', 94', 2702', 10' w/1-         Fraced w/79,890# 16/30 Arizona &         4', 40', 52', 60', 67', 75', 82', 88', 96',         6', 62', 70' w/1-0.41" spf. Total 32 holes.         rizona & 22,313# 16/30 resin coated         3, landed 2-7/8" 6.5# J-55 tbg @ 3533'.         Ided Yeso / San Andres oil well. These         8/19/11         and belief.         DATE 12/12/13	
0.41" spf. Total 36 holes. Treated perfs w/3374 gal 15% HCL ac 19,976# 16/30 resin coated sand in 20# X-linked gel. Set 5-1/2" CBP @ 2385'. PT csg to 3500 psi-OK. Perfed upper 2 2204', 12', 19', 28', 36', 44', 52', 58', 70', 80', 90', 98', 2307', 16', Treated perfs w/3523 gal 15% HCL acid & 48 perf balls. Fraced sand in 20# X-linked gel. On 11/8/13, drilled CBPs @ 2385', 2731' & 3180' & CO to PBTD3 Ran pump & rods. Released completion rig on 12/10/13. Compl two oil pools have a blanket DHC order (19.15.12.11E): ART-460 Spud Date: 8/11/11 Drilling Rig I hereby certify that the information above is true and complete to the b SIGNATURE Mike Pippin E-mail address For State Use Only	14', 22', 32', 42', 5 cid & 54 perf balls. SA @ 2120', 27', 3 24', 32', 40', 48', 5 w/67,676# 16/30 A 3596'. On 12/10/13 eted as a comming <u>09N.</u> Release Date: est of my knowledge <u>bleum Engineer - Ag</u>	D', 08', 20', 28', 38', 46', 52', 64', 72', 82',         2', 60', 68', 78', 86', 94', 2702', 10' w/1-         Fraced w/79,890# 16/30 Arizona &         4', 40', 52', 60', 67', 75', 82', 88', 96',         6', 62', 70' w/1-0.41" spf. Total 32 holes.         rizona & 22,313# 16/30 resin coated         3, landed 2-7/8" 6.5# J-55 tbg @ 3533'.         led Yeso / San Andres oil well. These         8/19/11         and belief.         ent       DATE 12/12/13         belief.         and belief.         DATE 12/12/13	
0.41" spf. Total 36 holes. Treated perfs w/3374 gal 15% HCL ac         19,976# 16/30 resin coated sand in 20# X-linked gel.         Set 5-1/2" CBP @ 2385'. PT csg to 3500 psi-OK. Perfed upper 2204', 12', 19', 28', 36', 44', 52', 58', 70', 80', 90', 98', 2307', 16',         Treated perfs w/3523 gal 15% HCL acid & 48 perf balls. Fraced sand in 20# X-linked gel.         On 11/8/13, drilled CBPs @ 2385', 2731' & 3180' & CO to PBTDD:         Ran pump & rods. Released completion rig on 12/10/13. Compl two oil pools have a blanket DHC order (19.15.12.11E): ART-464         Spud Date:       8/11/11         Drilling Rig         I hereby certify that the information above is true and complete to the b         SIGNATURE       Mike Pippin         E-mail address	14', 22', 32', 42', 5 cid & 54 perf balls. SA @ 2120', 27', 3 24', 32', 40', 48', 5 w/67,676# 16/30 A 3596'. On 12/10/13 eted as a comming <u>09N.</u> Release Date: est of my knowledge <u>bleum Engineer - Ag</u>	D', 08', 20', 28', 38', 46', 52', 64', 72', 82',         2', 60', 68', 78', 86', 94', 2702', 10' w/1-         Fraced w/79,890# 16/30 Arizona &         4', 40', 52', 60', 67', 75', 82', 88', 96',         6', 62', 70' w/1-0.41" spf. Total 32 holes.         rizona & 22,313# 16/30 resin coated         3, landed 2-7/8" 6.5# J-55 tbg @ 3533'.         Ided Yeso / San Andres oil well. These         8/19/11         and belief.         DATE 12/12/13	

4.