

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-41530
1. Type of Well: Oil Well ☐ Gas Well ☒ Other SWD		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator Caza Operating, LLC		6. State Oil & Gas Lease No. VB-1139
3. Address of Operator 200 North Loraine, Suite 1550, Midland, Texas 79701		7. Lease Name or Unit Agreement Name Forehand Ranch 27 State
4. Well Location Unit Letter B : 500 feet from the North line and 1650 feet from the East line Section 27 Township 23-S Range 27-E NMPM County Eddy		8. Well Number 5 SWD
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3158 GR		9. OGRID Number 249099
		10. Pool name or Wildcat SWD; Bell Canyon- Cherry Canyon

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: Perf & Stimulate ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11-20-2013 Run CBL, Gr, CCL from 3488' to surface. Good Bond. Perforate 5-1/2" casing from 3350-70' (2spf) 120 spiral phasing w/ 3-1/8" casing gun .42" EHD. Acidize perms w/ 1500 gals 15% HCL NEFE.

12-10-2013 Schlumberger Fracture Stimulated. Cherry Canyon perms (3350-70) down 5-1/2" casing w/ 860 bbls 20-lb Flex gel. Propped w/ 208,740 lbs 16/30 Jordan. 16/30 sand staged .5 to 6 ppg. AIR 58.3 BPM @ 2166 psi. Max Rate 59.3 BPM @ 2571 psi.

Spud Date:

10-29-2013

Rig Release Date:

11-08-2013

RECEIVED

JAN 29 2014

ARTESIA

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Richard L. Wright

TITLE Operations Manager

DATE 1-10-2013

Type or print name Richard L. Wright

E-mail address: rwright@cazapetro.com

PHONE: 432 682 7424

For State Use Only

APPROVED BY:

[Signature]

TITLE

[Signature]

DATE

1/31/14

Conditions of Approval (if any):