*					
Form 3160-5 (August 2007) DF	UNITED STATES OCD Artesia DEPARTMENT OF THE INTERIOR			FORM APPROVED OMB No. 1004-0137 Expires: July 31, 2010	
BUREAU OF LAND MANAGE			5. Lease Serial No. NM 014103	5. Lease Serial No.	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.			6. If Indian, Allotte	6. If Indian, Allottee or Tribe Name	
	MIT IN TRIPLICATE – Other i	instructions on page 2.	7. If Unit of CA/Ag	reement, Name and/or No.	
				8. Well Name and No. Littlefield AB Federal #5 9. API Well No. 30-015-20001	
			9. API Well No. 30-015-20001		
3a. Address 3b. Pho 333 West Sheridan Avenue, Oklahoma City, OK 73102-5015 3b.		3b. Phone No. (include area code 405-552-4615	·	10. Field and Pool or Exploratory Area Shugart;Yates-7RS-QU-Grayburg	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 330' FSL & 710' FWL; SEC 22-T18S-R31E			11. Country or Pari Eddy, NM	11. Country or Parish, State Eddy, NM	
12. CHE	ECK THE APPROPRIATE BO	X(ES) TO INDICATE NATURE	OF NOTICE, REPORT OR O	THER DATA	
TYPE OF SUBMISSION		ТҮР	E OF ACTION		
Notice of Intent	Acidize	Deepen Fracture Treat	Production (Start/Resume) Reclamation	Well Integrity	
Subsequent Report	Casing Repair	New Construction III Plug and Abandon	Recomplete Temporarily Abandon	Other	
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal		
determined that the site is ready f		e filed only after all requirements		val, a Form 3160-4 must be filed once een completed and the operator has	
determined that the site is ready f Actual Plug & Abandonment 1. 2/12/14-MIRU plugging rig. PO 2. Tagged CIBP @ 3,500'. Spot 2 3. Spot 25 sx CI C cement @ 2,20 4. Spot 40 sx cement @ 860'. Tag 5. Perfed sqz hole @ 250'. 6. Sqzd cement to surface on 8-5// 7. Wellbore plugged out on 2/17/14	for final inspection.) OH w/existing tubulars. 25 sx Cl C cement on existing 00'. Tagged TOC @ 1,975. (19 ged TOC @ 543'. (Salt top (18" x 5-1/2" annulus. Cement 4.	CIBP @ 3,500'. (Calc PBD @ Salt base @ 2,124'.) @ 810'. 8-5/8" shoe @ 631')	, including reclamation, have b / with fractional for the second se	een completed and the operator has	
determined that the site is ready f Actual Plug & Abandonment 1. 2/12/14-MIRU plugging rig. PO 2. Tagged CIBP @ 3,500'. Spot 2 3. Spot 25 sx CI C cement @ 2,20 4. Spot 40 sx cement @ 860'. Tag 5. Perfed sqz hole @ 250'. 6. Sqzd cement to surface on 8-5// 7. Wellbore plugged out on 2/17/14	for final inspection.) OH w/existing tubulars. 25 sx Cl C cement on existing 00'. Tagged TOC @ 1,975. (19 ged TOC @ 543'. (Salt top (18" x 5-1/2" annulus. Cement 4.	CIBP @ 3,500'. (Calc PBD @ Salt base @ 2,124'.) @ 810'. 8-5/8" shoe @ 631')	, including reclamation, have b / 2006 (2006) (2006	tal of 86 sx CI C cement.	
determined that the site is ready f Actual Plug & Abandonment 1. 2/12/14-MIRU plugging rig. PO 2. Tagged CIBP @ 3,500'. Spot 2 3. Spot 25 sx CI C cement @ 2,20 4. Spot 40 sx cement @ 860'. Tag 5. Perfed sqz hole @ 250'. 6. Sqzd cement to surface on 8-5/0 7. Wellbore plugged out on 2/17/14 8. Ground level marker set on 2/27	for final inspection.) OH w/existing tubulars. 5 sx Cl C cement on existing 0'. Tagged TOC @ 1,975. (ged TOC @ 543'. (Salt top ('8" x 5-1/2" annulus. Cement 4. 7/14.	CIBP @ 3,500'. (Calc PBD @ Salt base @ 2,124'.) @ 810'. 8-5/8" shoe @ 631')	, including reclamation, have b / 2006 (2006) (2006	tal of 86 sx CI C cement.	
determined that the site is ready f Actual Plug & Abandonment 1. 2/12/14-MIRU plugging rig. PO 2. Tagged CIBP @ 3,500'. Spot 2 3. Spot 25 sx CI C cement @ 2,20 4. Spot 40 sx cement @ 860'. Tag 5. Perfed sqz hole @ 250'. 6. Sqzd cement to surface on 8-5// 7. Wellbore plugged out on 2/17/14 8. Ground level marker set on 2/27 RECLAMAT	for final inspection.) OH w/existing tubulars. 25 sx Cl C cement on existing 00'. Tagged TOC @ 1,975. (gged TOC @ 543'. (Salt top ('8" x 5-1/2" annulus. Cement 4. 7/14.	CIBP @ 3,500'. (Calc PBD @ Salt base @ 2,124'.) @ 810'. 8-5/8" shoe @ 631')	, including reclamation, have b (1997) (1997	tal of 86 sx CI C cement.	
determined that the site is ready f Actual Plug & Abandonment 1. 2/12/14-MIRU plugging rig. PO 2. Tagged CIBP @ 3,500'. Spot 2 3. Spot 25 sx CI C cement @ 2,20 4. Spot 40 sx cement @ 860'. Tag 5. Perfed sqz hole @ 250'. 6. Sqzd cement to surface on 8-5/4 7. Wellbore plugged out on 2/17/14 8. Ground level marker set on 2/27 RECLAMAT DUE	for final inspection.) OH w/existing tubulars. 25 sx Cl C cement on existing 00'. Tagged TOC @ 1,975. (gged TOC @ 543'. (Salt top ('8" x 5-1/2" annulus. Cement 4. 7/14.	CIBP @ 3,500'. (Calc PBD @ Salt base @ 2,124'.) @ 810'. 8-5/8" shoe @ 631')	, including reclamation, have b (2009) (200)	tal of 86 sx CI C cement.	
determined that the site is ready f Actual Plug & Abandonment 1. 2/12/14-MIRU plugging rig. PO 2. Tagged CIBP @ 3,500'. Spot 2 3. Spot 25 sx CI C cement @ 2,20 4. Spot 40 sx cement @ 860'. Tag 5. Perfed sqz hole @ 250'. 6. Sqzd cement to surface on 8-5/4 7. Wellbore plugged out on 2/17/14 8. Ground level marker set on 2/27 RECLAMAT DUE	for final inspection.) OH w/existing tubulars. 25 sx Cl C cement on existing 00'. Tagged TOC @ 1,975. (gged TOC @ 543'. (Salt top ('8" x 5-1/2" annulus. Cement 4. 7/14.	CIBP @ 3,500'. (Calc PBD @ Salt base @ 2,124'.) @ 810'. 8-5/8" shoe @ 631') ed inside 5-1/2" casing to surfa	s Technician	tal of 86 sx CI C cement.	
determined that the site is ready f Actual Plug & Abandonment 1. 2/12/14-MIRU plugging rig. PO 2. Tagged CIBP @ 3,500'. Spot 2 3. Spot 25 sx Cl C cement @ 2,20 4. Spot 40 sx cement @ 860'. Tag 5. Perfed sqz hole @ 250'. 6. Sqzd cement to surface on 8-5// 7. Wellbore plugged out on 2/17/14 8. Ground level marker set on 2/27 Net DUE INDE 14. Thereby certify that the foregoing is Name (Printed/Typed) Ronnie Slack	for final inspection.) OH w/existing tubulars. 25 sx CI C cement on existing 00'. Tagged TOC @ 1,975. (gged TOC @ 543'. (Salt top (78" x 5-1/2" annulus. Cement 4. 7/14.	CIBP @ 3,500'. (Calc PBD @ Salt base @ 2,124'.) @ 810'. 8-5/8" shoe @ 631') ed inside 5-1/2" casing to surfa	s Technician	een completed and the operator has 3/17/2014 ALL TOT PEOCHE MELTOCO tal of 86 sx CI C cement. site of the well bore. The infance infit is completed.	
determined that the site is ready f Actual Plug & Abandonment 1. 2/12/14-MIRU plugging rig. PO 2. Tagged CIBP @ 3,500'. Spot 2 3. Spot 25 sx Cl C cement @ 2,20 4. Spot 40 sx cement @ 860'. Tag 5. Perfed sqz hole @ 250'. 6. Sqzd cement to surface on 8-5// 7. Wellbore plugged out on 2/17/14 8. Ground level marker set on 2/27 RECLAMAT DUE 14. I hereby certify that the foregoing is Name (Printed/Typed) Ronnie Slack	for final inspection.) OH w/existing tubulars. 25 sx CI C cement on existing 00'. Tagged TOC @ 1,975. (gged TOC @ 543'. (Salt top (78" x 5-1/2" annulus. Cement 4. 7/14.	CIBP @ 3,500'. (Calc PBD @ Salt base @ 2,124'.) @ 810'. 8-5/8" shoe @ 631') ed inside 5-1/2" casing to surfa Title Operation Date <u>3</u> FOR FEDERAL OR STA	s Technician	een completed and the operator has 3/17/2014 ALL TOT PEOCHE tal of 86 sx CI C cement. gina of the well hore. 1 is induince until is completed, EPTED FOR RECORD	
determined that the site is ready f Actual Plug & Abandonment 1. 2/12/14-MIRU plugging rig. PO 2. Tagged CIBP @ 3,500'. Spot 2 3. Spot 25 sx Cl C cement @ 2,20 4. Spot 40 sx cement @ 860'. Tag 5. Perfed sqz hole @ 250'. 6. Sqzd cement to surface on 8-5/0 7. Wellbore plugged out on 2/17/14 8. Ground level marker set on 2/27 RECLAMAT DUE 14. I hereby certify that the foregoing is Name (Printed/Typed) Ronnie Slack Signature Amme J Approved by Conditions of approval, if any, are attached hat the applicant holds legal or equitable	for final inspection.) OH w/existing tubulars. 5 sx Cl C cement on existing 10'. Tagged TOC @ 1,975. (19ged TOC @ 543'. (Salt top (18" x 5-1/2" annulus. Cement 4. 7/14. ION Strue and correct. Wath THIS SPACE F ed. Approval of this notice does not be a subject title to those rights in the subject	CIBP @ 3,500'. (Calc PBD @ Salt base @ 2,124'.) @ 810'. 8-5/8" shoe @ 631') ed inside 5-1/2" casing to surfa Title Operation Date 3 COR FEDERAL OR STA	s Technician	een completed and the operator has 3/17/2014 ALL TOT PEOCHE MELTOCO tal of 86 sx CI C cement. site of the well bore. The infance infit is completed.	
determined that the site is ready f Actual Plug & Abandonment 1. 2/12/14-MIRU plugging rig. PO 2. Tagged CIBP @ 3,500'. Spot 2 3. Spot 25 sx Cl C cement @ 2,20 4. Spot 40 sx cement @ 860'. Tag 5. Perfed sqz hole @ 250'. 6. Sqzd cement to surface on 8-5/8 7. Wellbore plugged out on 2/17/14 8. Ground level marker set on 2/27 RECLAMAT DUE 14. I hereby certify that the foregoing is Name (<i>Printed/Typed</i>) Ronnie Slack Signature Approved by Conditions of approval, if any, are attached hat the applicant holds legal or equitable ntille the applicant to conduct operations	for final inspection.) OH w/existing tubulars. IS sx CI C cement on existing 10'. Tagged TOC @ 1,975. (10ged TOC @ 543'. (Salt top (18" x 5-1/2" annulus. Cement 4. 7/14. ION CON THIS SPACE F cd. Approval of this notice does n title to those rights in the subject s thereon. 3 U.S.C. Section 1212, make it a c	CIBP @ 3,500'. (Calc PBD @ Salt base @ 2,124'.) @ 810'. 8-5/8" shoe @ 631') ed inside 5-1/2" casing to surfa Title Operation Date 3 COR FEDERAL OR STA	including reclamation, have b	een completed and the operator has 3/17/2014 ALL TOT PEOCHE tal of 86 sx CI C cement. gina of the well hore. 1 is induince until is completed, EPTED FOR RECORD	

•

