Form 3160-5

FORM APPROVED UNITED STATES MAR 1 4 2014 (August 2007) OMB NO. 1004-0135 DEPARTMENT OF THE INTERIOR Expires: July 31, 2010 BUREAU OF LAND MANAGEMENT Lease Serial No SUNDRY NOTICES AND REPORTS ON WENISHOOD ARTESIA NMNM13232 Do not use this form for proposals to drill or to re-enter-an 6. If Indian, Allottee or Tribe Name abandoned well. Use form 3160-3 (APD) for such proposals. 7. If Unit or CA/Agreement, Name and/or No. SUBMIT IN TRIPLICATE - Other instructions on reverse side. 1. Type of Well 8. Well Name and No. USA 9 FEDERAL 3 ☑ Oil Well ☐ Gas Well ☐ Other Name of Operator
 CHI OPERATING INC PAM CORBETT API Well No: Contact: E-Mail: pamc@chienergyinc.com 30-015-33268 3b. Phone No. (include area code) Ph: 432-685-5001 10. Field and Pool, or Exploratory BONE SPRINGS 3a. Address P.O. BOX 1799 MIDLAND, TX 79701 Fx: 432-687-2662 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, and State Sec 1 T19S R29E Mer NMP 660FNL 1650FWL EDDY COUNTY, NM 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION ☐ Acidize . □ Deepen ☐ Production (Start/Resume) □ Water Shut-Off Notice of Intent ☐ Alter Casing ☐ Fracture Treat □ Reclamation ■ Well Integrity ☐ Subsequent Report Casing Repair ■ New Construction Other ☐ Recomplete ☐ Final Abandonment Notice Change Plans □ Plug and Abandon ☐ Temporarily Abandon ☐ Convert to Injection □ Plug Back □ Water Disposal 13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) ALBERTAL FOR 18 STIT IN PROCEDURE TO PLUG & ABANDON RU DD PU. Circ hole with mud laden fluid. POOH with pkr and prod tbg. Set CIBP @ 6,250', spot 35' of cement on to abandon perfs. W/Dump Ba: / or Siot 255x A/ug. Free point and attempt to cut 4 1/2" csg @ 5,400'. POOH LD csg Spot 150' cement plug half in and half out @ 5,400'. Tag Spot 150' cement plug @ 2,400'. Tag Spot 400' cement plug @ 1000'-200' across 13 3/8" casing hole. Tag Plus from 4727'- 4577 (Top Bone Spring)

Tag Add plus from 3215'-3085'(Top

Delaware) NOC Tag. Spot 60' surf plug Cut off well head. Install dry hole marker and reclaim location. & plug from 1274-1174. (B/solt) SEE ATTACHED FOR certify that the foregoing is 14. I hereby Electronic Submission #234134 verified by the BLM Well Information System RECLAMATION PROCEDURE
For CHI OPERATING INC, sent to the Carlsbad RECLAMATION PROCEDURE
Committed to AFMSS for processing by DEBORAH HAM on 03/07/2014 () ATTACHED Name (Printed/Typed) SONNY MANN Title FIELD SUPERVISOR (Electronic Submission) Signature Date 01/31/2014 THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease

Title

which would entitle the applicant to conduct operations thereon. Office Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. USA 9 No. 3
(Current Wellbore)
660 FNL&1650 FWL
Sec 1-T19S-R29E
PPI 30-015-332-68

MMNM132-32

7-7/8" hole
4-1/2# 11.6# J55 @ 6602'

Perfs: 6303-6405'
Bone Spring

### **Proposed Plugging Procedure: Revised**

Cmt w/150 sx Class C TOC @ 5610' by CBL

RU DD PU. Circ hole w/mud laden fluid. POOH w/pkr & prod tbg. Set CIBP @6250', spot 35' of cmt on to abandon perfs. Free point & attempt to cut 4 1/2" csg @ 5400'. POOH LD csg. Spot 150' cmt plug half in & half out @ 5400". Tag Spot 150' cmt plug @2400'. Tag Spot 400' cement plug from 600-200' across 13-3/8 casing shoe. Tag Spot 60' surf plug. Cut off well head. Install dry hole marker & reclaim location.

## BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

### Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.
- 5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient:

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

- 6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration conditions of approval will be developed and furnished to you.



# United States Department of the Interior

### **BUREAU OF LAND MANAGEMENT**

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

#### Interim Reclamation Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses.

Interim reclamation consists of minimizing the footprint of disturbance by reclaiming all portions of the well site not needed for production operations. The portions of the cleared well site not needed for operational and safety purposes are recontoured to a final or intermediate contour that blends with the surrounding topography as much as possible. Sufficient level area remains for setup of a workover rig and to park equipment. Topsoil is respread over areas not needed for all-weather operations. Production facilities should be clustered to maximize the opportunity for interim reclamation. In order to inspect and operate the well or complete workover operations, it may be necessary to drive, park, and operate on restored, interim vegetation within the previously disturbed area. This is generally acceptable provided damage is repaired and reclaimed following use.

To reduce final reclamation costs; maintain healthy, biologically active topsoil; and to minimize habitat, visual, and forage loss during the life of the well, all salvaged topsoil should be spread over the area of interim reclamation, rather than stockpiled.

- 1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). Interim reclamation is to be completed within 6 months of well completion.
- 3. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with interim reclamation as per approved APD or Sundry Notice. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
- 4. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 5. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909 (Office), 575-361-2648 (Cell)

Linda Denniston Environmental Protection Specialist 575-234-5974

Jennifer Van Curen Environmental Protection Specialist 575-234-5905.

Mike Burton Environmental Protection Specialist 575-234-2226

Jeffery Robertson Natural Resource Specialist

Solomon Hughes Natural Resource Specialist 575-234-5951

Douglas Hoag
Civil Engineering Technician
575-234-5979