Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREALL OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-013
Expires: July 31, 201

DEPARTMENT OF THE INTERIOR RUREAU OF LAND MANAGEMENT					Expires: July 31, 2010			
SUNDRY	5. Lease Serial No.		NM 15007					
abandoned we	II. Use form 3160-3 (AP	D) for such p	roposals.		6. If Indian, Allottee o	r Tribe Name		
SUBMIT IN TRI	PLICATE - Other instruc	ctions on rev	erse side.	 	7. If Unit or CA/Agree	ement, Name and/or No.		
Type of Well ☐ Gas Well ☐ Oth	ner				8. Well Name and No. GLENWOOD 28 I	FEDERAL COM 002		
2. Name of Operator CIMAREX ENERGY CO OF C	Contact: COLORA B@ Mail: DEYLER@	DAVID A EYL MILAGRO-RE	.ER S.COM		9. API Well No. 30-015-36140			
3a. Address 600 N. MARIENFELD, SUITE MIDLAND, TX 79701	600	3b. Phone No. (include area code) Ph: 432-687-3033			10. Field and Pool, or Exploratory ABO: COUNTY LINE TANK			
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description	1)			11. County or Parish,	and State		
Sec 28 T16S R29E Mer NMP	EDDY COUNTY, NI			′, NM				
12. СНЕСК АРРГ	ROPRIATE BOX(ES) TO	O INDICATE	NATURE OF 1	NOTICE, RI	EPORT, OR OTHE	R DATA		
TYPE OF SUBMISSION	TYPE OF ACTION							
Notice of Intent	☐ Acidize	☐ Deep	en	☐ Product	ion (Start/Resume)	☐ Water Shut-Off		
_	☐ Alter Casing	☐ Frac	☐ Fracture Treat ☐		ation	■ Well Integrity		
☐ Subsequent Report	Casing Repair	□ New	☐ New Construction ☐ F		olete	☐ Other		
☐ Final Abandonment Notice	☐ Change Plans	Plug and Abandon		□ Temporarily Abandon				
	☐ Convert to Injection ☐ Plug Back ☐ Water							
13. Describe Proposed or Completed Ope If the proposal is to deepen directions Attach the Bond under which the wor following completion of the involved testing has been completed. Final Al determined that the site is ready for fi	ally or recomplete horizontally, rk will be performed or provide I operations. If the operation re pandonment Notices shall be fil	give subsurface l the Bond No. on sults in a multiple	locations and measu file with BLM/BIA completion or reco	red and true vo Required su ompletion in a	ertical depths of all pertin bsequent reports shall be new interval, a Form 316	ent markers and zones. filed within 30 days 0-4 shall be filed once		
1) SET 7" CIBP @ 6,450'; CIF 2) PUMP 50 SXS.CMT. @ 5,9 3) PUMP 45 SXS.CMT. @ 5,2 4) PUMP 40 SXS.CMT. @ 2,6 5) CUT X PULL 7" CSG. @ +/ 6) PUMP 45 SXS.CMT. @ 1,8 7) PUMP 45 SXS.CMT. @ 42 8) CIRC. TO SURF. 25 SXS.0 9) DIG OUT X CUT OFF WEL	930'-5,780'(T/ABO). 228'-5,078'(T/TUBB). 905'-2,476'(T/S.A., 9-5/8"('-1,800'. 955'-1,745'(7"CSG.STUB 0'-320'(13-3/8"CSG.SHO CMT. @ 63'-3'.	CSG.SHOE); \); WOC X TAG E); WOC X TA	WOC X TAG CN CMT. PLUG. AG CMT. PLUG.	_{ит} . С		OF APPROVAL		
DURING THIS PROCEDURE THE REQUIRED DISPOSAL,						CONTENTS TO		
	· .		CR		d kar specied //	2/14		
14. I hereby certify that the foregoing is	Electronic Submission # For CIMAREX ENE Committed to AFMSS	RGY CO OF C	DLORADO, sent by JAMES AMC	to the Carisi S on 04/24/2	oad	ITION PROCEDURE		
Name (Printed/Typed) DAVID A	EYLEK		Title AGENT	- -				
Signature (Electronic S	Submission)		Date 04/17/2	014				
·	THIS SPACE FO	OR FEDERA	L OR STATE	OFFICE U	SE			
Approved By James	Title SE	PS		5-1-14 Date				
Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to conduct the applicant the appli	uitable title to those rights in the	s not warrant or e subject lease	Office CFC	2.				
Title 18 U.S.C. Section 1001 and Title 43	U.S.C. Section 1212, make it a	crime for any pe	rson knowingly and	willfully to m	ake to any department or	agency of the United		



Well:

Location: County, State

Glenwood 28 Fed Com #2 Sec. 28-T16S-R29E Eddy, NM

Surface Location: Bottomhole Loc:

660, ENF 330, EFF 990, ENF 330, EFF

GL: KB:

3651"

Tubing: Superintendent: 2 7/8"

Engineer:

API:

30-015-36140

Field: Objective: TVD/MD:

County Line Tank

7426/11 200 TVD MD

End of 4-1/2" liner @ 10,890' MD

fole Size	Formation Tops Other	. Quantity	Description	Length.	Setting Depth					
4	20" @ 40'	: ·	KB.	18.00	18.00					
↑ 3 181		. 189	2.7/8° L-80:	6222.93	6240.90					
17 1/2"		1	75 X 2.7/8* TAC w/carbide slips	2,45	6243.38					
		5	278"180	164:82	6408.20					
	13 3/8"; 48#; H40; STC @ 370!	1	27/8" STD SN	1.10	8409.30					
	13 3/8", 48#, H40, STC @ 370!	- 	2 7/8" X 3 1/2" X-over	0.75	6410.0					
370 🔹 🔏	420 sxs cmt, circl cmt	. 1	3 1/2" Echometer DH Gas Separator	5.55	6415.60					
1		1	2.7/8" X 3 1/2" X-over	0.75	5416.3					
12 1/2"		1	2 7/8" Mud Anchor	32.95	6449.3					
*** ***		1	2.7/8" Bull Plug	0.25	6449.50					
		<u></u>		1	, ,9779,00					
	7" csg TOC @ 1900'	Quantity	. Description	Length	Setting Depth					
		. 1	1.1/20 X-22: SMPR	22,00	22,0					
	9-5/8", 40#, J55, LTC @ 2536	2.	1* Pony Rods 4:6	. 10:00						
		84	1" N97 Rods	2190	2132.00					
	630 SXS CM, CHC; CM	80	7/8" N97 Rods	2000.00 1800.00	4132.00 5932.00					
2536'		18	111/21C-bars	450.00	6382.00					
		1	1.1/2* OOT RH Rel	1,00	6383.00					
		.1	1° X-1° Lift Sub	1.00	6384:0X					
		1	2" X 1/1/2" x 20' HHBC Frac Pump	20.00	::6404;00					
X X										
				•						
	4-1/2" Liner Top = 6491'									
	Window from 6714'-6723'									
	•									
	· .									
					D.11200 MD					
	7426'.TVD	7426',TVD 6 1/8" Hole Size								
	4-1/2" 11:6# F	4-1/2" 11:6# P110 LTC @ 6,491' to 10,890' MD, No Cmt								
	·			,						
7426'	7", 26\$, P110, LTC @ 7425,									
	800 sxs cmt, TOC @ 1900'									

4/14/2014

41/7/140 3AG

CHARA

Glenwood 28 Fed Com #2

Location: County, State Sec. 28-T16S-R29E Eddy, NM

Bottomhole Loc:

Surface Location: 660' FNL 330' FWL 860' FNL 330' FEL

3633

KB:

3651

2-7/8"

Tubing: Superintendent:

Engineer:

30-015-36140

Field: Objective: County Line Tank

7426/11,200' TVD MD TVD/MD:

End of 4-1/2" liner @:10,890' MD

Formation Tops. Hole Size Other 20" @ 40' CIRC. 25 sxs. cmr. 0 63 -3 17 1/2" 13 3/8", 48#, H40, STC @ 370' 420 sxs cmt, circl cmt 370 Pump 45 5x5 cmT. @ 420'- 320'- 716 12 1/2" CUT X PULL 7" est. @ 1,8001 Pump 45 5x4. cm7 CP 1855'- 1745'-TAG 9-5/8", 40#, J55, LTC @ 2536" 835 sxs cmt, circl cmt Pump 40 5x5.cm. 0 2605'-2476'- TAG (SA) -2536 8:3/4" Pump 45 5x5. cm. 6 5228'-5078' Pump 50 5x5. cmf, @ 5930 - 5780 Pump 25 5 xs cm T. @ 6450'-6350! Window from 6714-6723" - SET 7" CTBP @ 6450! TO 11200 MD 4-1/2" 11.6# P110 LTC @ 6,491 to 10,890' MD; No Cmt 7", 26#, P110, LTC @ 7426, 7426' 800 sxs cmt, TOC @ 1900°

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.
- 5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient.
- *Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.
- 6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash</u>: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration conditions of approval will be developed and furnished to you.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Interim Reclamation Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses.

Interim reclamation consists of minimizing the footprint of disturbance by reclaiming all portions of the well site not needed for production operations. The portions of the cleared well site not needed for operational and safety purposes are recontoured to a final or intermediate contour that blends with the surrounding topography as much as possible. Sufficient level area remains for setup of a workover rig and to park equipment. Topsoil is respread over areas not needed for all-weather operations. Production facilities should be clustered to maximize the opportunity for interim reclamation. In order to inspect and operate the well or complete workover operations, it may be necessary to drive, park, and operate on restored, interim vegetation within the previously disturbed area. This is generally acceptable provided damage is repaired and reclaimed following use.

To reduce final reclamation costs; maintain healthy, biologically active topsoil; and to minimize habitat, visual, and forage loss during the life of the well, all salvaged topsoil should be spread over the area of interim reclamation, rather than stockpiled.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3); Surface Use Plan of
 Operations must include adequate measures for stabilization and reclamation of disturbed lands.
 Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD
 process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). Interim reclamation is to be completed within 6 months of well completion.
- 3. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with interim reclamation as per approved APD or Sundry Notice. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
- 4. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 5. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met.

If there are any questions, please feel free to contact any of the following specialists:

w.

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909 (Office), 575-361-2648 (Cell)

Linda Denniston Environmental Protection Specialist 575-234-5974

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Mike Burton Environmental Protection Specialist 575-234-2226

Jeffery Robertson Natural Resource Specialist

Solomon Hughes Natural Resource Specialist 575-234-5951

Douglas Hoag Civil Engineering Technician 575-234-5979