

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-42055
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VA-836
7. Lease Name or Unit Agreement Name Cedar Canyon 16 State
8. Well Number 10H
9. OGRID Number 16696
10. Pool name or Wildcat Pierce Crossing Bone Springs, E.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

OXY USA Inc.

3. Address of Operator

P.O. Box 50250 Midland, TX 79710

4. Well Location

Unit Letter C : 260 feet from the north line and 1470 feet from the west line
Section 16 Township 24S Range 29E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

2927' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

5/15/14 drill 7-7/8" pilot hole to 10372' 5/26/14, condition hole. Cut cores from 9711-9867', RIH w/ logs. Pump cmt plug w/ 440sx (88bbl) 50/50 Poz/H cmt 14.4ppg 1.12 yield from 10358-9316', followed by 330sx (56bbl) 50/50 Poz/H cmt 17.5ppg .946 yield from 9316-8465', PUH, WOC 5/28/14.

5/29/14, RIH & tag cmt @ 8521', drill, wash & ream to 8600'. Kickoff lateral @ 8600', drill to 14477'M 9856'V, 6/8/14. RIH w/ 5-1/2" 17# P110 BTC csg & set @ 14477', ECP @ 3220'. Pump 20BFW spacer w/ red dye followed by 20bbl gel spacer, then cmt w/ 650sx (270bbl) C Tuned Light w/ additives 9.76ppg 3.46 yield, HES couldn't get weight correct, stopped pumping, pumped out all cement out of hole. Pump 20bbl FW spacer, then cmt w/ 700sx (431bbl) C Tuned Light w/ additives 9.76ppg 3.46 yield followed by 820sx (238bbl) Super H w/ additives 13.2ppg, 1.63 yield with good returns while cementing, circ 2sx (1bbl) cmt to surface. Inflate ECP, pressure up to 4030#. Install wellhead, test to 5200#, tested good. RD Rel Rig 6/12/14.

Spud Date:

5/10/14

Rig Release Date:

6/12/14

NM OIL CONSERVATION

ARTESIA DISTRICT

JUN 18 2014

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

RECEIVED

SIGNATURE David Stewart TITLE Sr. Regulatory Advisor DATE 6/16/14

Type or print name David Stewart E-mail address: david.stewart@oxy.com PHONE: 432-685-5717

For State Use Only

APPROVED BY: RD Wade TITLE District Supervisor DATE 6/24/14

Conditions of Approval (if any):