Office District 1- (575) 393-6161 Energy, Mi	ate of New Mexico	Form C-103
	inerals and Natural Resources	Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240		WELL API NO. 30-015-20993
District II- (575) 748-1283 1301 W. Grand Ave., Artesia, NM 8821 0 OIL CON	ISERVATION DIVISION	5. Indicate Type of Lease
<u>District III</u> - (505) 334-6178	South St. Francis Dr.	STATE FEE S
1 000 Rio Brazos Rd., Aztec, NM 8741 0 District IV- (505) 476-3460	anta Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	1/4"	Fee
87505 CUNDRY NOTICES AND REPO	PES ON WELLS	7. Lease Name or Unit Agreement Name
SUNDRY NOTICES AND REPORTS ON WELL\$ (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A		7. Lease Name of Omt Agreement Name
DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMI"		Pit SWD
PROPOSALS.)	ther SWD	8. Well Number 1
1. Type of Well: Oil Well Gas Well Ol. 2. Name of Operator	ther SWD	9. OGRID Number
Mack Energy Corporati	ion	9. OGRID Number 013837
3. Address of Operator		10. Pool Name or Wildcat
P.O. Box 960 Artesia, NM 88210		SWD; Bell Canyon, Cherry Canyon
4. Well Location		
Unit Letter C 831 feet from	om the North line and	1980 feet from the West line
Section 4 Towns	200	NMPM County Eddy
	(Show whether DR, RKB, RT, GR etc.,	
	3142'	
12. Check Appropriate Box	x to Indicate Nature of Notice,	Report or Other Data
NOTICE OF INTENTION TO	. L CLID	OCCOUENT DEPONT OF
		SEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABATEMPORARILY ABANDON CHANGE PLAN		
	=	
PULL OR ALTER CASING MULTIPLE COM	MPL CASING/CEMEN	i jor 🗀
DOWNHOLE COMMINGLE		
CLOSED-LOOP SYSTEM Re-Entr	V N OTHER	
OTHER: Re-Entry OTHER: Note that the state of the state all pertinent details, and give pertinent dates, including estimated date		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion		
of starting any proposed work). SEE RULE 19.15	.7.14 NMAC. For Multiple Completion	
of starting any proposed work). SEE RULE 19.15 or recompletion. Mack Energy proposes to do the following re-entry process.	.7.14 NMAC. For Multiple Completion edure.	
of starting any proposed work). SEE RULE 19.15 or recompletion. Mack Energy proposes to do the following re-entry process. 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABLE	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS.	
of starting any proposed work). SEE RULE 19.15 or recompletion. Mack Energy proposes to do the following re-entry process. ALL PLUGS WE DRILL OUT ARE QUESTIONABI Drill out cmt plug @ surface, 310'-410, ' 986'-1080', 164'	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS.	
of starting any proposed work). SEE RULE 19.15 of recompletion. Mack Energy proposes to do the following re-entry process. ALL PLUGS WE DRILL OUT ARE QUESTIONABI Drill out cmt plug @ surface, 310'-410, ' 986'-1080', 164' 2. TD +/- 4200'. Test Casing to 1500#.	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS.	
of starting any proposed work). SEE RULE 19.15 of recompletion. Mack Energy proposes to do the following re-entry process. ALL PLUGS WE DRILL OUT ARE QUESTIONABI Drill out cmt plug @ surface, 310'-410, '986'-1080', 164'. 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175'	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'.	s: Attach wellbore diagram of proposed completion
of starting any proposed work). SEE RULE 19.15 of recompletion. Mack Energy proposes to do the following re-entry procedure. 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABID Drill out cmt plug @ surface, 310'-410, '986'-1080', 164'. 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175'. 4. PU 7" 26# J-55. Set casing @ 4150'. Cement Lead 200.	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'. Osx 35/65 Poz C, Tail 300sx PVL.	
of starting any proposed work). SEE RULE 19.15 of recompletion. Mack Energy proposes to do the following re-entry procedures 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABI Drill out cmt plug @ surface, 310'-410, '986'-1080', 164' 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175' 4. PU 7" 26# J-55. Set casing @ 4150'. Cement Lead 200 5. Shoot perforation across the Bell Canyon and Cherry Company of the starting of the starting of the starting and the start	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'. Osx 35/65 Poz C, Tail 300sx PVL.	RECEIVED
of starting any proposed work). SEE RULE 19.15 of recompletion. Mack Energy proposes to do the following re-entry procedure. 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABID Drill out cmt plug @ surface, 310'-410, '986'-1080', 164'. 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175'. 4. PU 7" 26# J-55. Set casing @ 4150'. Cement Lead 200.	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'. Osx 35/65 Poz C, Tail 300sx PVL. Canyon interval 2117-3982'.	s: Attach wellbore diagram of proposed completion
of starting any proposed work). SEE RULE 19.15 of recompletion. Mack Energy proposes to do the following re-entry procedure 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABID Drill out cmt plug @ surface, 310'-410, '986'-1080', 164' 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175' 4. PU 7" 26# J-55. Set casing @ 4150'. Cement Lead 200 5. Shoot perforation across the Bell Canyon and Cherry Co. Acid procedure to follow after logs.	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'. Osx 35/65 Poz C, Tail 300sx PVL. Canyon interval 2117-3982'. c coated tbg.	RECEIVED APR 2 8 2014
of starting any proposed work). SEE RULE 19.15 of-recompletion. Mack Energy proposes to do the following re-entry procedure 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABID Drill out cmt plug @ surface, 310'-410, '986'-1080', 164' 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175' 4. PU 7" 26# J-55. Set casing @ 4150'. Cement Lead 200 5. Shoot perforation across the Bell Canyon and Cherry 6. Acid procedure to follow after logs. 7. RIH w/7" Nickel plated Arrow set Pkr. & 2 7/8" Plasti	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'. Osx 35/65 Poz C, Tail 300sx PVL. Canyon interval 2117-3982'. c coated tbg.	RECEIVED
of starting any proposed work). SEE RULE 19.15 of-recompletion. Mack Energy proposes to do the following re-entry procedure 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABID Drill out cmt plug @ surface, 310'-410, '986'-1080', 164' 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175' 4. PU 7" 26# J-55. Set casing @ 4150'. Cement Lead 200 5. Shoot perforation across the Bell Canyon and Cherry 6. Acid procedure to follow after logs. 7. RIH w/7" Nickel plated Arrow set Pkr. & 2 7/8" Plasti	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'. Osx 35/65 Poz C, Tail 300sx PVL. Canyon interval 2117-3982'. c coated tbg.	RECEIVED APR 2 8 2014
of starting any proposed work). SEE RULE 19.15 of-recompletion. Mack Energy proposes to do the following re-entry proced 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABI Drill out cmt plug @ surface, 310'-410, ' 986'-1080', 164' 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175' 4. PU 7" 26# J-55. Set casing @ 4150'. Cement Lead 200 5. Shoot perforation across the Bell Canyon and Cherry Color of the Secondary of the Seco	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'. Osx 35/65 Poz C, Tail 300sx PVL. Canyon interval 2117-3982'. c coated tbg.	RECEIVED APR 2 8 2014
of starting any proposed work). SEE RULE 19.15 of-recompletion. Mack Energy proposes to do the following re-entry procedure 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABID Drill out cmt plug @ surface, 310'-410, '986'-1080', 164' 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175' 4. PU 7" 26# J-55. Set casing @ 4150'. Cement Lead 200 5. Shoot perforation across the Bell Canyon and Cherry 6. Acid procedure to follow after logs. 7. RIH w/7" Nickel plated Arrow set Pkr. & 2 7/8" Plasti	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'. Osx 35/65 Poz C, Tail 300sx PVL. Canyon interval 2117-3982'. c coated tbg.	RECEIVED APR 2 8 2014
of starting any proposed work). SEE RULE 19.15 of-recompletion. Mack Energy proposes to do the following re-entry proced 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABI Drill out cmt plug @ surface, 310'-410, ' 986'-1080', 164' 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175' 4. PU 7" 26# J-55. Set casing @ 4150'. Cement Lead 200 5. Shoot perforation across the Bell Canyon and Cherry Color of the Secondary of the Seco	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'. Osx 35/65 Poz C, Tail 300sx PVL. Canyon interval 2117-3982'. c coated tbg.	RECEIVED APR 2 8 2014
of starting any proposed work). SEE RULE 19.15 of-recompletion. Mack Energy proposes to do the following re-entry proced 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABI Drill out cmt plug @ surface, 310'-410, ' 986'-1080', 164' 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175' 4. PU 7" 26# J-55. Set casing @ 4150'. Cement Lead 200 5. Shoot perforation across the Bell Canyon and Cherry 6 6. Acid procedure to follow after logs. 7. RIH w/7" Nickel plated Arrow set Pkr. & 2 7/8" Plasti 8. Circulate packer fluid. Test casing to 500# for 30 min. Spud Date:	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'. Osx 35/65 Poz C, Tail 300sx PVL. Canyon interval 2117-3982'. Ic coated tbg. Rig Release Date:	RECEIVED APR 2 8 2014 NMOCD ARTESIA
of starting any proposed work). SEE RULE 19.15 of-recompletion. Mack Energy proposes to do the following re-entry proced 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABI Drill out cmt plug @ surface, 310'-410, ' 986'-1080', 164' 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175' 4. PU 7" 26# J-55. Set casing @ 4150'. Cement Lead 200 5. Shoot perforation across the Bell Canyon and Cherry Color of the Secondary of the Seco	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'. Osx 35/65 Poz C, Tail 300sx PVL. Canyon interval 2117-3982'. Ic coated tbg. Rig Release Date:	RECEIVED APR 2 8 2014 NMOCD ARTESIA
of starting any proposed work). SEE RULE 19.15 of-recompletion. Mack Energy proposes to do the following re-entry proced 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABI Drill out cmt plug @ surface, 310'-410, ' 986'-1080', 164' 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175' 4. PU 7" 26# J-55. Set casing @ 4150'. Cement Lead 200 5. Shoot perforation across the Bell Canyon and Cherry 6. Acid procedure to follow after logs. 7. RIH w/7" Nickel plated Arrow set Pkr. & 2 7/8" Plasti 8. Circulate packer fluid. Test casing to 500# for 30 min. Spud Date:	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'. Osx 35/65 Poz C, Tail 300sx PVL. Canyon interval 2117-3982'. Ic coated tbg. Rig Release Date:	RECEIVED APR 2 8 2014 NMOCD ARTESIA e and belief.
of starting any proposed work). SEE RULE 19.15 of-recompletion. Mack Energy proposes to do the following re-entry proced 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABI Drill out cmt plug @ surface, 310'-410, ' 986'-1080', 164' 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175' 4. PU 7" 26# J-55. Set casing @ 4150'. Cement Lead 200 5. Shoot perforation across the Bell Canyon and Cherry 6 6. Acid procedure to follow after logs. 7. RIH w/7" Nickel plated Arrow set Pkr. & 2 7/8" Plasti 8. Circulate packer fluid. Test casing to 500# for 30 min. Spud Date:	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'. Osx 35/65 Poz C, Tail 300sx PVL. Canyon interval 2117-3982'. Ic coated tbg. Rig Release Date:	RECEIVED APR 2 8 2014 NMOCD ARTESIA
of starting any proposed work). SEE RULE 19.15 of-recompletion. Mack Energy proposes to do the following re-entry proced. 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABID Drill out cmt plug @ surface, 310'-410, ' 986'-1080', 164' 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175' 4. PU 7" 26# J-55. Set casing @ 4150'. Cement Lead 200' 5. Shoot perforation across the Bell Canyon and Cherry 6. Acid procedure to follow after logs. 7. RIH w/7" Nickel plated Arrow set Pkr. & 2 7/8" Plasti 8. Circulate packer fluid. Test casing to 500# for 30 min. Spud Date: I hereby certify that the information above is true slid of SIGNATURE Arrow Sherall She	27.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'. Description of the second of the seco	RECEIVED APR 2 8 2014 NMOCD ARTESIA e and belief. DATE 4-25-2014
of starting any proposed work). SEE RULE 19.15 of-recompletion. Mack Energy proposes to do the following re-entry proced. 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABID Drill out cmt plug @ surface, 310'-410, ' 986'-1080', 164'. 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175'. 4. PU 7" 26# J-55. Set casing @ 4150'. Cement Lead 200. 5. Shoot perforation across the Bell Canyon and Cherry Co. 6. Acid procedure to follow after logs. 7. RIH w/7" Nickel plated Arrow set Pkr. & 2 7/8" Plasting. 8. Circulate packer fluid. Test casing to 500# for 30 min. Spud Date: I hereby certify that the information above is true slid of the start of t	.7.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'. Osx 35/65 Poz C, Tail 300sx PVL. Canyon interval 2117-3982'. Ic coated tbg. Rig Release Date:	RECEIVED APR 2 8 2014 NMOCD ARTESIA e and belief. DATE 4-25-2014
of starting any proposed work). SEE RULE 19.15 of-recompletion. Mack Energy proposes to do the following re-entry proced. 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABID Drill out cmt plug @ surface, 310'-410, '986'-1080', 164'. 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175'. 4. PU 7" 26# J-55. Set casing @ 4150'. Cement Lead 200. 5. Shoot perforation across the Bell Canyon and Cherry 6. Acid procedure to follow after logs. 7. RIH w/7" Nickel plated Arrow set Pkr. & 2 7/8" Plasting. 8. Circulate packer fluid. Test casing to 500# for 30 min. Spud Date: I hereby certify that the information above is true slid of the state of the sta	27.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'. Description of the second of the seco	RECEIVED APR 2 8 2014 NMOCD ARTESIA e and belief. DATE 4-25-2014 PHONE: (575)748-1288
of starting any proposed work). SEE RULE 19.15 of-recompletion. Mack Energy proposes to do the following re-entry proced. 1. ALL PLUGS WE DRILL OUT ARE QUESTIONABID Drill out cmt plug @ surface, 310'-410, ' 986'-1080', 164'. 2. TD +/- 4200'. Test Casing to 1500#. 3. Set CIBP @ 4175'. 4. PU 7" 26# J-55. Set casing @ 4150'. Cement Lead 200. 5. Shoot perforation across the Bell Canyon and Cherry Co. 6. Acid procedure to follow after logs. 7. RIH w/7" Nickel plated Arrow set Pkr. & 2 7/8" Plasting. 8. Circulate packer fluid. Test casing to 500# for 30 min. Spud Date: I hereby certify that the information above is true slid of the start of t	27.14 NMAC. For Multiple Completion edure. LE DUE TO NO RECORDS. 9'-1743'. Description of the second of the seco	RECEIVED APR 2 8 2014 NMOCD ARTESIA e and belief. DATE 4-25-2014