Form 3160-5 (August 2007)

OCD Artesia

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

SUNDRY NOTICES AND REPORTS ON WELLS

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

5.	Lease Serial No.		
	NMNM78213		

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.					6. If Indian, Allottee or Tribe Name			
SUBMIT IN TRI	PLICATE - Other instructi	ons on reverse sid	de.	7. If Unit or CA/Agr	eement, Name and/or No.			
1. Type of Well				8. Well Name and No WALT CANYON				
Oil Well Gas Well Oth 2. Name of Operator		JLIE THORNTON	<u> </u>	9. API Well No.	,			
YATES PETROLEUM CORPO	ORATIONE-Mail: JThornton@	/atespetroleum.com		30-015-32997-	00-S1			
3a. Address 105 SOUTH FOURTH STREE ARTESIA, NM 88210	T .	3b. Phone No. (include Ph: 575-748-4190 Fx: 575-748-4585	area code)	10. Field and Pool, o INDIAN BASIN	r Exploratory I-UPPER PENN ASSOC			
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description)			11. County or Parish	, and State			
Sec 3 T22S R24E SWNE 186	5FNL 2002FEL	·		EDDY COUNT	Y, NM			
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATE NATU	RE OF NOTICE, R	EPORT, OR OTHE	ER DATA			
TYPE OF SUBMISSION			TYPE OF ACTION	`				
Notice of Intent	☐ Acidize	Deepen	☐ Product	ion (Start/Resume)	■ Water Shut-Off			
	☐ Alter Casing	☐ Fracture Trea	t 🔲 Reclam	ation	■ Well Integrity			
☐ Subsequent Report	Casing Repair	■ New Constru	ction 🔲 Recomp	olete	□ Other			
☐ Final Abandonment Notice	Change Plans	Plug and Aba	andon, Tempor	arily Abandon				
	Convert to Injection	Plug Back	■ Water I	Disposal				
Attach the Bond under which the worfollowing completion of the involved testing has been completed. Final Al determined that the site is ready for f Yates Petroleum plans to plug 1. MI RU all H2S safety equip 2. Set CIBP at 8,152 ft and ca 3. Spot 35 sx Class H cement 4. Perforate at 6,002 ft. Pump unable to inject into the perfor reset the plug. POOH. 5. Perforate at 4,002 ft. Pump unable to inject into the perfor reset the plug. 6. Perforate at 2,940 ft. Pump 6. Perforate at 2,940 ft. Pump	operations. If the operation resulpandonment Notices shall be filed in in inspection.) grand abandon this well as function in the shall be filed in inspection. grand abandon this well as function in the shall be filed	ts in a multiple complet only after all requirement ollows: Dad the hole with places the stage tool displace it down to 5 ne casing. WOC and displace it down to 5 ne casing. WOC and	ion or recompletion in a nts, including reclamation SE ugging mud. and the Wolfcamp to 1,822 ft. If we were d tag, if necessary 3,822 ft. If we were d tag, if necessary	new interval, a Form 31 n, have been completed E ATTACHE ONDITIONS (pp. NM OIL (ARTI SE RECLAMATION ATTA	D FOR OF APPROVAL CONSERVATION ESIA DISTRICT P 1 2 2014 N PROCEDURE EMETIVED			
14. I hereby certify that the foregoing is	true and correct	 _		arce	pted for record			
	Electronic Submission #25	EUM CORPORÁTIO	N, sent to the Carlsba	adí	NMOCDICS			
Name(Printed/Typed) JULIE TH	ORNTON	Title	REGULATORY RE	PORTING TECH	712			
Signature (Electronic S	Submission)	Date	08/14/2014	Accepte	d for record . MOCD			
	THIS SPACE FOR	R FEDERAL OR	STATE OFFICE U	SE	·			
Approved By (BLM Approver Not Conditions of approval, if any, are attache certify that the applicant holds legal or equ	d. Approval of this notice does no				Date 09/05/2014			
which would entitle the applicant to condu	ict operations thereon.	Office	Carlsbad					
Title 18 U.S.C. Section 1001 and Title 43	U.S.C. Section 1212, make it a cr	ime for any person know	vingly and willfully to m	ake to any department o	r agency of the United			

Additional data for EC transaction #257129 that would not fit on the form

32. Additional remarks, continued

unable to inject into the perforations spot a 180 ft inside the casing. This will leave a plug across the Bone Springs top. WOC and tag, if necessary reset the plug.

7. Perforate at 2,000 ft. Pump a 75 sx Class C plug and displace it down to 1,820 ft. If we were unable to inject into the perforations spot a 180 ft inside the casing. This will leave a plug across the Bone Springs top. WOC and tag, if necessary reset the plug.


8. Perforate at 1,656 ft. Pump a 75 sx class C plug and displace it down to 1,476 ft. If we were unable to inject into the perforations spot a 180 ft inside the casing. This will leave a plug across the casing shoe. WOC and tag, if necessary reset the plug.

9. Perforate the 7 inch casing at 150 ft. Tie on to it and establish an injection rate. Pump 65 sx of Class C and circulate it back to the surface. Do not displace the cement; this will leave a plug inside and outside of the casing from to surface to 150 ft forming the surface plug. WOC and tag, if necessary reset the plug.

10. Remove all surface equipment and weld dry hole marker per regulations.

NOTE: Wellbore Schematics Attached.

	Walt Canyon AM		ELD: Indian ddy County				-
L 3,896'		KB:_					-
-		MPLETION DATE: 11/17/03		ASING PRO	GRAM		⊐
	API 30-015-32997		9-5/8" 36# J	55		1,606	
-					·	<u></u>	
		-	7" 26# L8	0 LT&C		8560	85,
		1,)		,	Bef	ore	
1-3/4" Hole		()		,]
		9-5/8" @ 1,606' w/ 1,060 sx (circ)		Yeso Bone S WC Penn	Spring /	1,950'	
							_
		•					
,							
				•			
		(A 70. ← TÔC @,+/-£,830 by CBL 11,-26-03					
8-3/4" Hole		<i>'</i>					
		\					,
,	/4 /	DV Packer Tool @ 7,952' MD			•		
· .							
		Canyon Perfs: 8202' – 8,288' (172) 30,000 gal 20% HCl. 12-3-03					
		Bad casing at 8,431					
		DV Packer Tool @ 8,544'					
	PBTD: 8,513' TD: 8,682'	7" @ 8.566" 85 6 3 1 st Stage 200 sx 2 nd Stage 1,210 sx			Not to JMH 6-23-14	Scale	



BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

- 6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration conditions of approval will be developed and furnished to you.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of
 Operations must include adequate measures for stabilization and reclamation of disturbed lands.
 Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD
 process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909, 575-361-2648 (Cell)

Solomon Hughes Natural Resource Specialist 575-234-5951

Jeffery Robertson Natural Resource Specialist 575-234-2230

Duncan Whitlock Environmental Protection Specialist 575-234-5926

Linda Denniston Environmental Protection Specialist 575-234-5974 Cody Layton Supervisory Multi Resources 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Amanda Lynch Natural Resource Specialist 575-234-5922

Jessie Rice Natural Resource Specialist 575-234-5913

Indra Dahal Natural Resource Specialist 575-234-5996