Form 3160-5 (August 2007)

# UNITED STATES DEPARTMENT OF THE INTERIOR

OCD Artesia	FORM APPROVED
1	OMB NO. 1004-0135
	Expires: July 31, 2010

BUREAU OF LAND MANAGEMENT  SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.		5. Lease Serial No. NMNM111946	
		6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on reverse side.		7. If Unit or CA/Agreement, Name and/or No.	
Type of Well	Well Name and No.     TOMBSTONE FEDERAL 1		
2. Name of Operator Contact: COG OPERATING LLC E-Mail: kcastillo	9. API Well No. 30-015-338		
3a. Address ONE CONCHO CENTER 600 W ILLINOIS AVE MIDLAND, TX 79701	3b. Phone No. (include area code) Ph: 432-685-4332	10. Field and Pool, or Exploratory CEMETARY MORROW	
4. Location of Well (Footage, Sec., T., R., M., or Survey Descripti	ion)	11. County or Parish, and State	
Sec 35 T19S R25E Mer NMP 660FSL 1650FEL	•	EDDY COUNTY, NM	
12. CHECK APPROPRIATE BOX(ES)	TO INDICATE NATURE OF NO	TICE, REPORT, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION		
■ Notice of Intent ■ Acidize ■ Alter Casing ■ Casing Repair	Fracture Treat	☐ Production (Start/Resume) ☐ Water Shut-Off ☐ Reclamation ☐ Well Integrity ☐ Recomplete ☐ Other	
☐ Final Abandonment Notice ☐ Change Plans ☐ Convert to Injectio		☐ Temporarily Abandon ☐ Water Disposal	
13. Describe Proposed or Completed Operation (clearly state all pertir If the proposal is to deepen directionally or recomplete horizontall Attach the Bond under which the work will be performed or provifollowing completion of the involved operations. If the operation testing has been completed. Final Abandonment Notices shall be determined that the site is ready for final inspection.)	ly, give subsurface locations and measured de the Bond No. on file with BLM/BIA. For results in a multiple completion or recomp filed only after all requirements, including	and true vertical depths of all pertinent markers and zones. tequired subsequent reports shall be filed within 30 days eletion in a new interval, a Form 3160-4 shall be filed once reclamation, have been completed, and the operator has	
COG Operating LLC respectfully requests an extension electronic submission #230014.	on to the attached recompletion pe	9-16-14	
We intend to begin the work in mid November 2014.  Work to be complete.  Maximul MAS		15,2015. RECEIVED	
011/211 44 00113		79 391110101101	
For COG	#263979 verified by the BLM Well In OPERATING LLC, sent to the Carls for processing by JENNIFER MASOI	bad	
Name(Printed/Typed) KANICIA CASTILLO	Title PREPARE	APPROVED	
Signature (Electronic Submission)	Date 09/16/2014	Anna	
THIS SPACE F	OR FEDERAL OR STATE OF	FICE USE VEP 1 200	
Approved By	Title	BUREAU OF LAND MANAGEMENT  CARLSBAD FIELD OFFICE	
onditions of approval, if any, are attached. Approval of this notice do rtify that the applicant holds legal or equitable title to those rights in thick would entitle the applicant to conduct operations thereon.		SAME OF THE OF THE	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Form 3160-5 FORM APPROVED **UNITED STATES** (August 2007) OMB NO. 1004-0135 DEPARTMENT OF THE INTERIOR Expires: July 31, 2010 **BUREAU OF LAND MANAGEMENT** 5. Lease Serial No. SUNDRY NOTICES AND REPORTS ON WELLS NMNM111946 Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals. 6. If Indian, Allottee or Tribe Name 7. If Unit or CA/Agreement, Name and/or No. SUBMIT IN TRIPLICATE - Other instructions on reverse side. 8. Well Name and No. 1. Type of Well TOMBSTONE FEDERAL 1 Oil Well 68 Gas Well Other Name of Operator Contact: KANICIA CASTILLO 9. API Well No 30-015-338 COG OPERATING LLC E-Mail: kcastillo@conchoresources.com 3b. Phone No. (include area code) Ph: 432-685-4332 10. Field and Pool, or Exploratory CEMETARY MORROW 3a. Address
ONE CONCHO CENTER 600 W. ILLINOIS AVENUE MIDLAND, TX 79701 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, and State EDDY COUNTY, NM Sec 35 T19S R25E Mer NMP 660FSL 1650FEL 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION ☐ Production (Start/Resume) ■ Water Shut-Off ☐ Acidize ☐ Deepen Motice of Intent ☐ Well Integrity ☐ Alter Casing ☐ Fracture Treat □ Reclamation ■ Subsequent Report ☐ Casing Repair ■ New Construction □ Recomplete □ Other ☐ Final Abandonment Notice □ Change Plans □ Plug and Abandon ☐ Temporarily Abandon Convert to Injection Plug Back ■ Water Disposal 13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof.

If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones.

Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has SEE ATTACHED FOR CONDITIONS OF APPRO determined that the site is ready for final inspection.) COG Operating LLC respectfully requests to recomplete to the Bone Spring and reclassify this well as an oil well. Please see attached procedure. MIRU CU. Load hole. ND wellhead, NU BOP. TOH with tubing, laying down.
 Rig up wireline. RIH with CIBP and set at 9420??. Dump 35?? of cement on plug.
 Pick up and TIH with 2???? tubing to PBTD. Circulate hole with 3% KCl water. TOH.
 Perforate Bone Spring with 3???? casing guns, premium charges, 120⁰ phasing, 3 SPF in the following intervals: 6542??, 6562??, 6575??, 6589??, 6596??, 6603??, 6613??, 6624??, 6710??, 6720??, 6734??, 6740??, 6746??, 6755?? 14. I hereby certify that the foregoing is true and correct Electronic Submission #230014 verified by the BLM Well Information System
For COG OPERATING LLC, sent to the Carlebad
Committed to AFMSS for processing by JOHNNY DICKERSON on 01/17/2014 () PREPARER Name (Printed/Typed) KANICIA CASTILLO 12/18/2013 **V D D D O VYE L** Signature (Electronic Submission) THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\_Approved Ву

FEB

AU OF LAN

### Additional data for EC transaction #230014 that would not fit on the form

#### 32. Additional remarks, continued

Rig down wireline.
5.) TIH with tubing and tension packer. Set packer at 6500??. Swab well and report results.
6.) Rig up a pumping service company. Acidize interval with 3000 gallons of 15% HCl and 72 ball sealers at 5 BPM. Over displace 5 bbls.
7.) Swab back load.
8.) If shows warrant, move in pumping service company to frac the Bone Spring 9.) Flow back frac
10.) Install artificial lift.

Tombstone Federal 1 30-015-338 90 90 COG Operating, LLC. January 28, 2014 Conditions of Approval

Notify BLM at 575-361-2822 a minimum of 24 hours prior to commencing work.

Work to be completed by April 28, 2014.

- 1. Operator shall place CIBP at 9,420' with 25sx Class H Cement on top to cover the top of the Morrow formation. Tag required at a minimum of 9,220' or shallower.
- 2. Must conduct a casing integrity test to max treating pressure before perforating and fracturing. Submit results to BLM. Notify BLM if test fails.
- 3. Prior to abandoning the Bone Spring formation the operator must submit an NOI to properly plug back the Wolfcamp formation, as it cannot be done at this time due to the proximity of Bone Spring perforations.
- 4. Before casing or a liner is added or replaced, prior BLM approval of the design is required. Use notice of intent Form 3160-5.
- 5. Surface disturbance beyond the originally approved pad must have prior approval.
- 6. Closed loop system required.
- 7. All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of work over operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area. Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.
- 8. Operator to have H2S monitoring equipment on location.
- 9. A minimum of a 3000 (3M) BOP to be used. All blowout preventer (BOP) and related equipment (BOPE) shall comply with reasonable well control requirements. A two ram system with a blind ram and a pipe ram designed for the size of the work string shall be adequate. Tapered work strings will require an additional pipe ram. The manifold shall comply with Onshore Oil and Gas Order #2 Attachment I (3M Diagrams of Choke Manifold Equipment). The accumulator system shall have an immediately available power source to close the rams and retain 200 psi above pre-charge. The pre-charge test shall follow requirements in Onshore Order #2.

- 10. Subsequent sundry required detailing work done, a C-102 form, and completion report for the new formations. Operator to include well bore schematic of current well condition when work is complete.
- 11. See attached for general requirements.

JAM 012814

# BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

## **General Requirements for Plug Backs**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from this approval.

If you are unable to plug back the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged back. Failure to do so will result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plug back operations. For wells in Eddy County, call 575-361-2822.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. Before pumping cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either **Neat Class "C"**, for up to 7,500 feet of depth or **Neat Class "H"**, for deeper than 7,500 feet plugs.

- 6. <u>Subsequent Plug back Reporting</u>: Within 30 days after plug back work is completed, file one original and three copies of the Subsequent Report, Form 3160-5 to BLM. The report should give in detail the manner in which the plug back work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. <u>Show date work was completed</u>.
- 7. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.