

Submit 1 Copy To Appropriate District Office

District I - (575) 393-6161

1625 N. French Dr., Hobbs, NM 88240

District II - (575) 748-1283

811 S. First St., Artesia, NM 88210

District III - (505) 334-6178

1000 Rio Brazos Rd., Aztec, NM 87410

District IV - (505) 476-3460

1220 S. St. Francis Dr., Santa Fe, NM

87505

## OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

OCT 23 2014  
RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		4. WELL API NO. 30-015-32374
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator Lynx Petroleum Consultants, Inc.		6. State Oil & Gas Lease No.
3. Address of Operator P.O. Box 1708, Hobbs, NM 88241		7. Lease Name or Unit Agreement Name Walterthon Fee
4. Well Location Unit Letter <u>D</u> : <u>855</u> feet from the <u>North</u> line and <u>660</u> feet from the <u>West</u> line Section <u>21</u> Township <u>22S</u> Range <u>27E</u> NMPM County <u>Lea</u>		8. Well Number <u>002</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. OGRID Number 13645
		10. Pool name or Wildcat OTIS; ATOKA (GAS)

## 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
 DOWNHOLE COMMINGLE ☐

OTHER

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
 COMMENCE DRILLING OPNS. ☐ P AND A ☐  
 CASING/CEMENT JOB ☐

OTHER: ☒ PLUGBACK

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

7/9/14 MIRU PU.

7/10/14 Kill well with 2% KCL TFW. ND wellhead. NU BOP. Release pkr. TOO H with tbg.

7/12/14 RU wireline. Run and set CIPB @ 11430'. Capped with 35' cement. TIH with tbg. Opri ended to 10,880'. Circulate and load hole with 2% KCL TFW. Test casing to 1500 psi; held ok.

7/15/14 Perforate Atoka, 10870-76', with 4 jsfp.

7/16/14 Set 4 1/2" production pkr. Setup as follows: pump out plug, profile nipple, 6' tailpipe, pkr., profile nipple, and on/off tool. Set pkr. @ 10730'. TIH w/ 2 3/8" tbg. Latch pkr. ND BOP. NU tree. RU kill truck and pump out plug. Displace spot acid.

7/18/14 Swab

7/22/14 Acidize with 1000 gals. 15% HCL-NE-FE acid. Flush with 2% KCL TFW.

7/23/14 ND BOP. Land tbg and NU tree. Test annulus to 1000 psig for 15 min. RU kill truck. Pump out plug and displace spot acid.

7/24/14 Swab

7/26/14 Run tbg. rods, and pump. Set 2 3/8", 4.7#, N-80 EUE tbg. @ 10,200'. Return to production.

7/28/14 24-hr. test: 0 BO, 30 MCF; and 0 BW.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Debbie McKelvey TITLE Agent DATE 10/17/14Type or print name Debbie McKelvey E-mail address: debmckelvey@earthlink.net PHONE: 575-392-3575

For State Use Only

APPROVED BY: [Signature] TITLE [Signature] DATE 10/24/14

Conditions of Approval (if any):

# Atoka Recompletion

7/2014

Elevation: 3115'GL KB: +17'

17-1/2" Hole

352' - 13-3/8", ST&C Casing

Cemented w/475 sxs. Circulated to Surf.

12-1/4" Hole

1772' - 9-5/8", J-55, 36#, ST&C Casing.

Cemented w/700 sxs. Circulated to Surface

8-3/4" Hole

9000' - 7", P-110 & N-80, 23#, LT&C Casing.

Cemented w/1250 sxs. Circulated to Surface

TOC by Tmp Svy 8365'

6-1/8" Hole

2-3/8", 4.7#/ft, N-80, EUE tubing @ 10,790'

4-1/2" x 2-3/8" AS1-X-10K packer

Perfs/Atoka 10,870'-76'

C.I.B.P. @ 11430' capped w/35' cement

Perfs/Morrow 11466'-76'

C.I.B.P. @ 11575'

Perfs/Morrow 11670'-72', 11735'-42', 11751'-59',  
11819'-22'

12030' - 4 1/2", 11.6#, P-110

Cement w/315 sxs. Class 'H'

T.D. @ 12030'

Lynx Petroleum Cons.

Walterthon Fee No. 2

855' FNL & 660' FWL

Sec. 21, T-22S, R-27E

Eddy County, N.M.