Orm 3160-5 UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS			OMB	1 APPROVED NO. 1004-0135 12 July 31, 2010	
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals. =			6. If Indian, Allottee	<ul><li>6. If Indian, Allottee or Tribe Name</li><li>7. If Unit or CA/Agreement, Name and/or No.</li></ul>	
			7. If Unit or CA/Agr		
I. Type of Well ☐ Gas Well ☐ Other			8. Well Name and No PURE GOLD A I	8. Well Name and No. PURE GOLD A FEDERAL 4	
2. Name of Operator OXY USA INC.	Contact: DAVID STEWART E-Mail: david_stewart@oxy.com		9. API Well No. 30-015-27388		
<ul> <li>3a. Address</li> <li>P.O. BOX 50250</li> <li>MIDLAND, TX 79710</li> </ul>		3b. Phone No. (include area code Ph: 432-685-5717 Fx: 432-685-5742	e) 10. Field and Pool, o SAND DUNES	10. Field and Pool, or Exploratory SAND DUNES DELAWARE, W.	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			11. County or Parish	11. County or Parish, and State	
Sec 21 T23S R31E NWSW 1 32.287210 N Lat, 103.790250			EDDY COUNT	Y, NM	
12. CHECK APP	ROPRIATE BOX(ES) TO	) INDICATE NATURE OF	NOTICE, REPORT, OR OTHE	ER DATA	
TYPE OF SUBMISSION		ТҮРЕ С	TYPE OF ACTION		
Notice of Intent	□ Acidize	Deepen	Production (Start/Resume)	□ Water Shut-Of	
	□ Alter Casing	Fracture Treat	Reclamation	Well Integrity	
Subsequent Report	Casing Repair	□ New Construction	Recomplete	□ Other	
Final Abandonment Notice	🖞 🗖 Change Plans	🛛 Plug and Abandon	Temporarily Abandon		
· · · · · · · · · · · · · · · · · · ·	Convert to Injection	Plug Back	Water Disposal		
following completion of the involve testing has been completed. Final A determined that the site is ready for	d operations. If the operation re- bandonment Notices shall be fil- final inspection.)	sults in a multiple completion or re- ed only after all requirements, inclu	A. Required subsequent reports shall b completion in a new interval, a Form 31 iding reclamation, have been completed	60-4 shall be filed once	
TD-8100' PBTD-7586' Perl	fs-5934-6649' CIBP-7586	5' 7700'			
13-3/8" 54# csg @ 697' w/ 61 8-5/8" 32# csg @ 4075' w/ 12 5-1/2" 17# csg @ 8100', DVT *5/93 Perf @ 4460' sqz 600s;	275sx, 11" hole, TOC-Surf @ 6187' w/ 1100sx, 7-7/8	Circ	NM OIL CON	SERVATION	
1. RIH & set CIBP @ 6593', M 2. M&P 25sx cmt @ 6268-611 3. RIH & set CIBP @ 5884', M 4. M&P 25sx cmt @ 5125-49 5. M&P 25sx cmt @ 4532-43	06' WOC-Tag A&P 25sx cmt 75' WOC-Tag		ACCEPTED TO 12/10/ NECEPTED TO 12/10/ NECCD	cord	
14. I hereby certify that the foregoing i	Electronic Submission #	271017 verified by the BLM W Y USA INC., sent to the Carls	ell Information System		
	Name (Printed/Typed) DAVID STEWART		Title SR. REGULATORY ADVISOR		
Name (Printed/Typed) DAVID S			Date 10/15/2014		
	Submission)	Date 10/15/	2014		
	Submission)	Date 10/15/ DR FEDERAL OR STATE			
Signature (Electronic	Submission)	DR FEDERAL OR STATE		Date	
	Submission) THIS SPACE FC ed. Approval of this notice does juitable title to those rights in the	DR FEDERAL OR STATE		Date	

\*\* OPERATOR-SUBMITTED \*\* OPERATOR-SUBMITTED \*\* OPERATOR-SUBMITTED \*\*

## Additional data for EC transaction #271017 that would not fit on the form

## 32. Additional remarks, continued

6. M&P 35sx cmt @ 4125-3880' WOC-Tag 7. M&P 25sx cmt @ 2380-2250' WOC-Tag 8. M&P 25sx cmt @ 750-645' WOC-Tag 9. Perf @ 190', sqz 60sx cmt to Surface

## 10# MLF between plugs

Above ground steel tanks will be utilized

OXY USA Inc. - Proposed Pure Gold A Federal #4 API No. 30-015-27388

60sx @ 190'-Surface

25sx @ 750-645' WOC-Tag

25sx @ 2380-2250' WOC-Tag

35sx @ 4125-3880' WOC-Tag

25sx @ 5125-4975' WOC-Tag

. and Some property and the 19 second

CIBP @ 5884' w/ 25sx

CIBP @ 6593' w/ 25sx

25sx @ 6268-6106' WOC-Tag

25sx @ 4532-4386' WOC-Tag

13-3/8" csg @ 697' w/ 615sx-TOC-Surf-Circ

17-1/2" hole @ 697'

Perf @ 190'

11" hole @ 4075' 8-5/8" csg @ 4075' w/ 1275sx-TOC-Surf-Circ

\*5/93-Perf @ 4460' sqz 600sx TOC-190' TS

Perfs @ 5934-5950'

Perfs @ 6643-6649'

7-7/8" hole @ 8100' 5-1/2" csg @ 8100' DVT @ 6187' W/ 1100sx-TOC-\*4480'-CBL

Perfs @ 7636-7658' Perfs @ 7755-7904'

8/04-CIBP @ 7586'

8/04-CIBP @ 7700' w/ 10' cmt

PB-8065'

50 96*4*0 依喻 TD-8100'

