Form \$1.60-5 (August 2007)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

5. Lease Serial.No. NMLC067849

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an
handoned well. Use form 3160-3 (APD) for such proposals

abandoned well. Use form 3160-3 (APD) for such proposals.					6. If Indian, Allottee or Tribe Name			
SUBMIT IN TRIPLICATE - Other instructions on reverse side.					7. If Unit or CA/Agreement, Name and/or No.			
Type of Well     Gas Well					8. Well Name and No. EAGLE 34 L FEDERAL 79			
Name of Operator Contact: MIKE PIPPIN     LIME ROCK RESOURCES II-A,L.P. E-Mail: mike@pippinflc.com				9. API Well No. 30-015-42522				
3a. Address C/O MIKE PIPPIN 3104 N. SU FARMINGTON, NM 87401	one No. (include area code) 05-327-4573		10. Field and Pool, or Exploratory RED LAKE,GL-YSO NE 96836					
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				11. County or Parish, and State				
Sec 34 T17S R27E NWSW 2210FSL 330FWL					EDDY COUNTY, NM			
12. CHECK APPI	ROPRIATE BOX(ES) TO INDIC	CATE NATURE OF N	IOTICE, RE	EPOR	Г, OR OTHEF	R DATA		
TYPE OF SUBMISSION	TYPE OF ACTION							
Notice of Intent	☐ Acidize	<b>D</b> eepen	□ Producti	ion (Start/Resume)				
Subsequent Report     ■		Fracture Treat	□ Reclama	_			rity .	
	_ ,	New Construction	☐ Recomp			Other		
☐ Final Abandonment Notice	-	Plug and Abandon .		arily Abandon				
13. Describe Proposed or Completed Ope		Plug Back	☐ Water D			<del> </del>		
New Well Initial Completion. On 11/6/14, PT 5-1/2" csg to 5 10', 24', 42', 49', 55', 61', 67', 7 18', 28', 42', 60' w/1-0.42" spf. & fraced w/60,000# 100 mesh CBP & 5-1/2" csg to 4000 psi- 4005', 23', 30', 40', 50', 60', 70 w/1-0.42" spf. Total 28 holes. 247,740# 40/70 Ottawa sand ii psi-OK. Perfed Yeso @ 3442', 97', 3608', 18', 24', 30', 43', 54'	5000 psi. Perfed lower Yeso @ 4(75', 85', 96', 4512', 30', 38', 59', 7 Total 30 holes. On 11/7/14, treat & 198,400# 40/70 Ottawa sand i OK. Perfed Yeso @ 3900', 11', 16', 78', 86', 4103', 12', 26', 44', 52' Treated perfs w/1500 gal 15% H0 n slick water. Set 5-1/2" CBP @ 48', 61', 76', 82'', 92', 3506', 18', 16, 64', 68', 83', 96', 3710', 18', 30'	342', 47', 60', 69', 84', 93', 80', 92', 4600', 12', ed perfs w/1500 gal 15 n slick water. Set 5-1/28', 26', 34', 44', 56', 62', 64', 76', 88', 4200'	ng reclamation 94', 4402', 5% HCL acic " CBP @ 42 , 74', 93', 000# 100 me " csg to 400	, have t 1 255'. F esh &	PT NM OI	L CONSER RTESIA DISTREB 1 3 20	cord //3//5 RVATION	
14. Thereby certify that the foregoing is true and correct.  Electronic Submission #279424 verified by the BLM Well Information System  For LIME ROCK RESOURCES II-A,L.P., sent to the Carlsbad  Committed to AFMSS for processing by DEBORAH HAM on 01/29/20/45 CEPTED FOR RECORD								
Name(Printed/Typed) MIKE PIPF	PIN	Title PETROL	EUM ENGI	NEER				
Signature (Electronic S	ubmission)	Date 11/14/20	14		FEB 1	1 2015		
THIS SPACE FOR FEDERAL OR STATE OFFICE USE When Home								
Approved By		Title		RO	REAU OF LAND CARLSBAD F	MANAGEME		
Conditions of approval, if any, are attached ertify that the applicant holds legal or equi which would entitle the applicant to conduc	itable title to those rights in the subject le						. \	
Title 18 U.S.C. Section 1001 and Title 43 U.States any false, fictitious or fraudulent st	J.S.C. Section 1212, make it a crime for atements or representations as to any ma	any person knowingly and w tter within its jurisdiction.	villfully to mak	te to any	y department or a	gency of the Unit	ed	

## Additional data for EC transaction #279424 that would not fit on the form

## 32. Additional remarks, continued

spf. Total 31 holes. Treated perfs w/1500 gal 15% HCL acid & fraced w/30,500# 100 mesh & 265,700# 40/70 Ottawa sand in slick water. Set 5-1/2" CBP @ 3400'. PT CBP & 5-1/2" csg to 4000 psi-OK. Perfed upper Yeso @ 3043', 48', 56', 61', 74', 81', 89', 94', 3106', 17', 26', 44', 60', 70', 80', 86', 3210', 21', 29', 32', 45', 62', 71', 77', 83', 3307', 18', 28', 36', 44' w/1-0.42" spf. Total 30 holes. Treated perfs w/1500 gal 15% HCL & fraced w/29,640# 100 mesh & 236,050# 40/70 Ottawa sand in slick water. On 11/9/14, MIRUSU. CO after frac, drill out CBPs @ 3400', 3800', & 4255', & CO to PBTD @ 4699'. On 11/11/14, landed ESP on 2-7/8" 6.5# J-55 tbg @ 2920'. Released completion rig on 11/13/14.