



PHOENIX
TECHNOLOGY SERVICES

March 12, 2015

Oil Conservation Division
State of New Mexico
811 S. First St.
Artesia, New Mexico 88210

Dear District 2 - Artesia

Attention: Regulatory Department

Re: Apache Corporation
NFE Federal #35H
Eddy County, NM
API #30-015-42587
Job No. 1512836

JD 3/24/15
Accepted for record
N:1500

Enclosed please find the Survey Data Certification, and the original Plat and one copy of the Survey Report performed on the above referenced Well by Phoenix Technology Services, Inc. (P-5 No. 664171). Other information required by your office is as follows:

Name & Title of Surveyor	Drain Hole Number	Surveyed Depths		Dates Performed		Type of Survey
		From	To	Start	End	
Mike Miller	35H	4,872	10,216	02/24/15	03/02/15	MWD

A certified plat on which the bottom hole location is oriented both to the surface location and to the lease lines (or unit lines in case of pooling) is attached to the survey report. If any other information is required, please contact the undersigned at the letterhead address and phone number.

Best Regards,

Claudia Carreon

Claudia Carreon
Operations Administrator

Certified mail receipt number: 7014 2120 0004 3423 7224

Phoenix Technology Services SURVEY DATA CERTIFICATION



PHOENIX JOB NUMBER

1512836

OPERATOR

Apache

WELL NAME

NFE Federal #35H

COUNTY & STATE

Eddy County, NM

API WELL NUMBER

30-015-42587

PROPOSED DIRECTION

89.59

TIE-IN DATA						
MEASURED	VERTICAL			N-S	E-W	DATA
DEPTH	DEPTH	INCLIN	AZIMUTH	COORD	COORD	SOURCE
4,797 ft	4,796.45 ft	0.51	23.18	29.51 ft	11.14 ft	Gyro

FIRST	FIRST		
SURVEY	SURVEY		
DATE	DEPTH	INCLIN	AZIMUTH
24-Feb-15	4,872.00 ft	0.80	44.90

SURVEY INSTRUMENT
TYPE
Phoenix MWD

LAST	LAST		
SURVEY	SURVEY		
DATE	DEPTH	INCLIN	AZIMUTH
2-Mar-15	10,216.00 ft	89.10	88.30

TO THE BEST OF MY KNOWLEDGE I
CERTIFY THIS SURVEY DATA TO BE
TRUE AND CORRECT.

PROJECTED	PROJECTED		
TD SURVEY	TD SURVEY		
DATE	DEPTH	INCLIN	AZIMUTH
2-Mar-15	10,280.00 ft	89.10	88.30

Mike Miller

PRINT YOUR NAME ABOVE

Mike Miller

SIGN YOUR NAME ABOVE

MAGNETIC DECLINATION OR TOTAL GRID

TOTAL CORRECTION USED	
	7.17
DECLINATION OR GRID	GRID

3/2/2015

TODAY'S DATE

MWD SUPERVISOR 1

Mike Miller

DIRECTIONAL DRILLER 1

Steven Hawkins

MWD SUPERVISOR 2

Howard Chapman

DIRECTIONAL DRILLER 2

Brant Duplechain

12329 Cutten Rd., Houston, Texas 777066

(713)337-0600 (Voice), (713)337-0599 (Fax)



Apache Corporation

Eddy County, NM (NAD27 NME)

NFE Federal

#35H

WB1 / Job #1512836

Survey: Phoenix MWD Survey

Standard Survey Report

03 March, 2015



Company:	Apache Corporation	Local Co-ordinate Reference:	Well #35H
Project:	Eddy County, NM (NAD27 NME)	TVD Reference:	KB @ 3763.00usft (Capstar 119)
Site:	NFE Federal	MD Reference:	KB @ 3763.00usft (Capstar 119)
Well:	#35H	North Reference:	Grid
Wellbore:	WB1 / Job #1512836	Survey Calculation Method:	Minimum Curvature
Design:	Surveys (Capstar 119)	Database:	Compass 5000 GCR

Project:	Eddy County, NM (NAD27 NME)		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico East 3001		

Site:	NFE Federal		
Site Position:		Northing:	673,264.70 usft
From:	Map	Easting:	633,303.50 usft
Position Uncertainty:	0.00 usft	Slot Radius:	13-3/16 "
		Latitude:	32° 51' 0.49036 N
		Longitude:	103° 53' 57.34966 W
		Grid Convergence:	0.24 °

Well:	#35H		
Well Position	+N/-S	0.00 usft	Northing: 676,463.90 usft
	+E/-W	0.00 usft	Easting: 632,910.30 usft
Position Uncertainty	0.00 usft	Wellhead Elevation:	usft
		Latitude:	32° 51' 32.16272 N
		Longitude:	103° 54' 1.80514 W
		Ground Level:	3,752.00 usft

Wellbore:	WB1 / Job #1512836		
Magnetics	Model Name	Sample Date	Declination
	IGRF2015	2/23/2015	(°)
			7.40
			(°)
			60.62
			(nT)
			48,517

Design:	Surveys (Capstar 119)		
Audit Notes:			
Version:	1.0	Phase:	ACTUAL
		Tie On Depth:	0.00
Vertical Section:	Depth From (TVD)	+N/-S	+E/-W
	(usft)	(usft)	(usft)
	0.00	0.00	0.00
			89.59

Survey Program	Date	3/3/2015		
From	To	Survey (Wellbore)	Tool Name	Description
(usft)	(usft)			
100.00	4,797.00	Phoenix Gyro Survey (WB1 / Job #151283	NS-GYRO-MS	North sensing gyrocompassing m/s
4,872.00	10,280.00	Phoenix MWD Survey (WB1 / Job #15128	PHX+MWD+BGGM	PHX+MWD+BGGM v3:standard declination

Survey:									
Measured	Inclination	Azimuth	Vertical	+N/-S	+E/-W	Vertical	Dogleg	Build	Turn
Depth	(°)	(°)	Depth	(usft)	(usft)	Section	Rate	Rate	Rate
(usft)			(usft)			(usft)	(°/100usft)	(°/100usft)	(°/100usft)
4,797.00	0.51	23.18	4,796.45	29.51	-11.14	-10.93	0.00	0.00	0.00
Tie-on to Phoenix Gyro Survey									
4,872.00	0.80	44.90	4,871.45	30.19	-10.64	-10.42	0.50	0.39	28.96
First Phoenix MWD Survey									
4,904.00	3.50	85.20	4,903.43	30.43	-9.51	-9.29	9.17	8.44	125.94
4,936.00	7.30	89.20	4,935.28	30.54	-6.50	-6.28	11.93	11.88	12.50
4,967.00	11.10	88.70	4,965.87	30.63	-1.55	-1.33	12.26	12.26	-1.61
4,999.00	15.30	87.60	4,997.02	30.88	5.76	5.98	13.15	13.13	-3.44
5,030.00	19.80	86.80	5,026.57	31.34	15.09	15.31	14.54	14.52	-2.58

Company:	Apache Corporation	Local Co-ordinate Reference:	Well #35H
Project:	Eddy County, NM (NAD27 NME)	TVD Reference:	KB @ 3763.00usft (Capstar 119)
Site:	NFE Federal	MD Reference:	KB @ 3763.00usft (Capstar 119)
Well:	#35H	North Reference:	Grid
Wellbore:	WB1 / Job #1512836	Survey Calculation Method:	Minimum Curvature
Design:	Surveys (Capstar 119)	Database:	Compass 5000 GCR

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
5,062.00	23.60	85.70	5,056.30	32.13	26.89	27.12	11.94	11.88	-3.44
5,093.00	27.10	88.60	5,084.31	32.76	40.14	40.38	11.98	11.29	9.35
5,125.00	29.90	91.10	5,112.43	32.79	55.41	55.64	9.51	8.75	7.81
5,157.00	32.70	93.00	5,139.77	32.18	72.02	72.25	9.28	8.75	5.94
5,189.00	35.70	94.50	5,166.23	31.00	89.96	90.18	9.74	9.38	4.69
5,220.00	39.10	95.80	5,190.86	29.30	108.71	108.92	11.26	10.97	4.19
5,252.00	42.10	96.20	5,215.15	27.12	129.42	129.61	9.41	9.38	1.25
5,284.00	44.90	95.40	5,238.36	24.90	151.33	151.51	8.92	8.75	-2.50
5,315.00	47.10	94.80	5,259.89	22.92	173.54	173.70	7.23	7.10	-1.94
5,347.00	49.80	94.30	5,281.12	21.02	197.41	197.56	8.52	8.44	-1.56
5,379.00	53.70	93.10	5,300.93	19.41	222.48	222.62	12.54	12.19	-3.75
5,411.00	58.00	93.00	5,318.88	18.00	248.92	249.05	13.44	13.44	-0.31
5,442.00	62.50	93.10	5,334.26	16.57	275.79	275.90	14.52	14.52	0.32
5,474.00	66.90	93.00	5,347.94	15.03	304.67	304.77	13.75	13.75	-0.31
5,506.00	71.30	92.60	5,359.35	13.57	334.53	334.61	13.80	13.75	-1.25
5,537.00	74.70	91.60	5,368.41	12.49	364.15	364.23	11.39	10.97	-3.23
5,569.00	77.50	92.00	5,376.10	11.51	395.19	395.26	8.83	8.75	1.25
5,600.00	80.40	91.70	5,382.04	10.53	425.60	425.66	9.40	9.35	-0.97
5,649.00	84.70	91.90	5,388.39	9.00	474.15	474.20	8.78	8.78	0.41
5,680.00	87.90	91.50	5,390.39	8.08	505.07	505.11	10.40	10.32	-1.29
5,710.00	88.20	91.60	5,391.41	7.27	535.04	535.08	1.05	1.00	0.33
5,739.00	88.20	91.40	5,392.32	6.51	564.01	564.05	0.69	0.00	-0.69
5,829.00	88.50	90.60	5,394.91	4.94	653.96	653.98	0.95	0.33	-0.89
5,921.00	89.30	90.00	5,396.68	4.46	745.94	745.95	1.09	0.87	-0.65
6,012.00	89.60	90.30	5,397.55	4.23	836.94	836.95	0.47	0.33	0.33
6,108.00	87.60	89.80	5,399.90	4.14	932.90	932.91	2.15	-2.08	-0.52
6,203.00	87.80	89.30	5,403.71	4.89	1,027.82	1,027.83	0.57	0.21	-0.53
6,297.00	87.60	88.10	5,407.48	7.02	1,121.72	1,121.74	1.29	-0.21	-1.28
6,391.00	88.20	90.40	5,410.93	8.25	1,215.64	1,215.67	2.53	0.64	2.45
6,486.00	88.20	90.80	5,413.91	7.25	1,310.59	1,310.61	0.42	0.00	0.42
6,581.00	88.50	90.40	5,416.65	6.26	1,405.55	1,405.56	0.53	0.32	-0.42
6,676.00	88.40	90.00	5,419.22	5.93	1,500.51	1,500.52	0.43	-0.11	-0.42
6,771.00	88.00	88.80	5,422.20	6.92	1,595.46	1,595.47	1.33	-0.42	-1.26
6,866.00	88.00	88.90	5,425.52	8.83	1,690.38	1,690.40	0.11	0.00	0.11
6,961.00	87.70	88.00	5,429.08	11.39	1,785.28	1,785.31	1.00	-0.32	-0.95
7,055.00	88.20	89.70	5,432.44	13.28	1,879.19	1,879.24	1.88	0.53	1.81
7,150.00	87.70	88.80	5,435.84	14.52	1,974.12	1,974.18	1.08	-0.53	-0.95
7,244.00	88.60	89.90	5,438.88	15.59	2,068.07	2,068.13	1.51	0.96	1.17
7,338.00	90.80	91.70	5,439.37	14.27	2,162.05	2,162.09	3.02	2.34	1.91
7,433.00	90.90	91.80	5,437.96	11.37	2,256.99	2,257.02	0.15	0.11	0.11
7,528.00	89.50	90.30	5,437.63	9.63	2,351.97	2,351.98	2.16	-1.47	-1.58
7,623.00	88.40	88.60	5,439.37	10.54	2,446.95	2,446.96	2.13	-1.16	-1.79
7,717.00	88.60	88.70	5,441.83	12.76	2,540.89	2,540.91	0.24	0.21	0.11

Company:	Apache Corporation	Local Co-ordinate Reference:	Well #35H
Project:	Eddy County, NM (NAD27 NME)	TVD Reference:	KB @ 3763.00usft (Capstar 119)
Site:	NFE.Federal	MD Reference:	KB @ 3763.00usft (Capstar 119)
Well:	#35H	North Reference:	Grid
Wellbore:	WB1 / Job #1512836	Survey Calculation Method:	Minimum Curvature
Design:	Surveys (Capstar 119)	Database:	Compass 5000 GCR

Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
7,812.00	88.60	88.50	5,444.15	15.08	2,635.83	2,635.87	0.21	0.00	-0.21	
7,907.00	88.80	87.90	5,446.31	18.06	2,730.76	2,730.82	0.67	0.21	-0.63	
8,002.00	88.50	88.20	5,448.54	21.29	2,825.68	2,825.76	0.45	-0.32	0.32	
8,097.00	88.80	87.90	5,450.78	24.53	2,920.60	2,920.70	0.45	0.32	-0.32	
8,192.00	87.50	87.60	5,453.85	28.25	3,015.47	3,015.60	1.40	-1.37	-0.32	
8,287.00	87.60	89.10	5,457.91	30.99	3,110.34	3,110.48	1.58	0.11	1.58	
8,382.00	88.10	89.20	5,461.47	32.39	3,205.26	3,205.41	0.54	0.53	0.11	
8,476.00	88.00	88.90	5,464.67	33.95	3,299.20	3,299.35	0.34	-0.11	-0.32	
8,570.00	88.70	88.70	5,467.38	35.92	3,393.14	3,393.31	0.77	0.74	-0.21	
8,665.00	88.70	89.80	5,469.54	37.16	3,488.10	3,488.28	1.16	0.00	1.16	
8,760.00	89.10	89.70	5,471.36	37.58	3,583.08	3,583.26	0.43	0.42	-0.11	
8,856.00	89.30	89.20	5,472.70	38.50	3,679.07	3,679.25	0.56	0.21	-0.52	
8,952.00	89.40	90.30	5,473.79	38.92	3,775.06	3,775.24	1.15	0.10	1.15	
9,047.00	89.60	89.80	5,474.62	38.83	3,870.06	3,870.24	0.57	0.21	-0.53	
9,142.00	88.00	91.50	5,476.61	37.76	3,965.02	3,965.19	2.46	-1.68	1.79	
9,236.00	88.10	90.30	5,479.81	36.28	4,058.96	4,059.11	1.28	0.11	-1.28	
9,330.00	86.20	91.10	5,484.48	35.14	4,152.83	4,152.97	2.19	-2.02	0.85	
9,425.00	85.90	90.20	5,491.02	34.06	4,247.59	4,247.73	1.00	-0.32	-0.95	
9,520.00	87.90	90.70	5,496.16	33.32	4,342.45	4,342.57	2.17	2.11	0.53	
9,615.00	88.70	88.90	5,498.98	33.65	4,437.40	4,437.53	2.07	0.84	-1.89	
9,709.00	89.20	88.50	5,500.70	35.78	4,531.36	4,531.50	0.68	0.53	-0.43	
9,804.00	89.60	87.90	5,501.70	38.76	4,626.31	4,626.47	0.76	0.42	-0.63	
9,898.00	89.80	87.90	5,502.19	42.21	4,720.24	4,720.42	0.21	0.21	0.00	
9,992.00	89.70	87.80	5,502.60	45.73	4,814.18	4,814.38	0.15	-0.11	-0.11	
10,087.00	89.80	87.30	5,503.01	49.79	4,909.09	4,909.32	0.54	0.11	-0.53	
10,182.00	89.10	88.40	5,503.93	53.36	5,004.01	5,004.27	1.37	-0.74	1.16	
10,216.00	89.10	88.30	5,504.46	54.34	5,038.00	5,038.26	0.29	0.00	-0.29	
Last Phoenix MWD Survey										
10,280.00	89.10	88.30	5,505.47	56.24	5,101.96	5,102.23	0.00	0.00	0.00	
Projection to TD										

Survey Annotations					
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates			
		+N/-S (usft)	+E/-W (usft)	Comment	
4,797.00	4,796.45	29.51	-11.14	Tie-on to Phoenix Gyro Survey	
4,872.00	4,871.45	30.19	-10.64	First Phoenix MWD Survey	
10,216.00	5,504.46	54.34	5,038.00	Last Phoenix MWD Survey	
10,280.00	5,505.47	56.24	5,101.96	Projection to TD	

Checked By: _____	Approved By: _____	Date: _____
-------------------	--------------------	-------------

DISTRICT I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

DISTRICT II
811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720

DISTRICT III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

DISTRICT IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, New Mexico 87505

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number 30-015- 42587	Pool Code 96831	Pool Name Cedar Lake; Glorieta - Yeso
Property Code 308724	Property Name NFE FEDERAL	Well Number 35H
OGRID No. 873	Operator Name APACHE CORPORATION	Elevation 3752'

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	6	17-S	31-E		1010	SOUTH	155	EAST	EDDY

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	5	17-S	31-E		1010	SOUTH	330	EAST	EDDY

Dedicated Acres 160	Joint or Infill	Consolidation Code	Order No.
-------------------------------	-----------------	--------------------	-----------

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

	OPERATOR CERTIFICATION I hereby certify that the information herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. <u>Sorina L. Flores</u> 1/22/14 Signature Date <u>Sorina L. Flores</u> Printed Name <u>sorina.flores@apachecorp.com</u> E-mail Address
CORNER COORDINATES TABLE ① - Y=676775.0 N, X=633063.5 E ② - Y=676812.0 N, X=638343.2 E ③ - Y=675455.2 N, X=633070.9 E ④ - Y=675492.7 N, X=638350.7 E DETAIL	SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. APRIL 5, 2012 Date of Survey Signature of Professional Surveyor: <u>Ronald J. Eidson</u> 05/03/2012 RONALD J. EIDSON NEW MEXICO 3239 Professional Surveyor Certification Number: <u>3239</u> DSS JWSC W.O.: 12.11.0710