Submit 1 Copy To Appropriate District	Form C-103	
Office <u>District 1</u> – (575) 393-6161 1625 N. French Dr. Hobbs NM 88240 ARTESIA DISTRICT	Revised July 18, 2013	
1025 N. Henen Dr., 110003, NW 00240	WELL API NO.	
District II – (575) 748-1283 811 S. First St., Artesia, NM 88210 APR 2 612050NSERVATION DIVISION	30-015-27008	
<u>District III</u> – (505) 334-6178 1220 South St. Francis Dr.	5. Indicate Type of Lease	
1000 Rio Brazos Rd., Aztec, NM 87410	STATE X FEE	
District IV – (505) 476-3460 RECEIVED Santa Fe, NW 87505	6. State Oil & Gas Lease No.	
87505		
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	USA CACTUS 16 STATE	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	8. Well Number	
1. Type of Well: Oil Well X Gas Well Other	· 1	
2. Name of Operator	9. OGRID Number 4323	
CHEVRON U.S.A. INC.		
3. Address of Operator	10. Pool name or Wildcat	
15 SMITH ROAD MIDLAND, TEXAS 79705	BRUSHY CANYON	
4. Well Location Y- LAT 33.22369 X-LONG103.78377		
Unit Letter C : 330 feet from the NORTH line and	2310 feet from the WEST line	
Section 16 Township 24-S Range 31-E	NMPM County EDDY	
11. Elevation (Show whether DR, RKB, RT, GR, etc		
DF 3,492'		
12. Check Appropriate Box to Indicate Nature of Notice	Report or Other Data	
12. Check Appropriate Box to indicate Mature of Monee	, Report of Other Data	
NOTICE OF INTENTION TO: SUI	BSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK D PLUG AND ABANDON REMEDIAL WO		
PULL OR ALTER CASING		
	. —	
OTHER:		
13. Describe proposed or completed operations. (Clearly state all pertinent details, a	nd give pertinent dates, including estimated date	
	of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of	
proposed completion or recompletion. 13 3/8"- 626' TOC SURF, 8 5/8"- 4,250' TOC SURF, 5 1/2"- 8,450" TOC EST.		
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35		
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35		
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT	CEMENT ON TOP OF EACH.	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS	CEMENT ON TOP OF EACH.	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI	" CEMENT ON TOP OF EACH. . CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'.	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'-	" CEMENT ON TOP OF EACH. . CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD.	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMEN	CALLED LAURA W/ NMOCD. OT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405',	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMEN PERF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH	CALLED LAURA W/ NMOCD. OT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405',	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMEN PERF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION.	Y CEMENT ON TOP OF EACH. . CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMENT PERF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION. NIPPLE DOWN CUT & CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQ	Y CEMENT ON TOP OF EACH. . CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMEN PERF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION.	Y CEMENT ON TOP OF EACH. . CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMENT PERF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION. NIPPLE DOWN CUT & CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQ	POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/ UIRMENTS.	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMENT PERF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION. NIPPLE DOWN CUT & CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQ	CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/ UIRMENTS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging)	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMEN PERF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION. NIPPLE DOWN CUT & CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQ CLOSED LOOP SYSTEM USED, CLASS "C" CEMENT USED.	POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. WT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/ UIRMENTS.	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMENT PERF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION. NIPPLE DOWN CUT & CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQ	CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/ UIRMENTS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMEN PERF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION. NIPPLE DOWN CUT & CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQ CLOSED LOOP SYSTEM USED, CLASS "C" CEMENT USED.	CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/ UIRMENTS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under	
 4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMENT PROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMENT PREF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION. NIPPLE DOWN CUT & CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQ CLOSED LOOP SYSTEM USED, CLASS "C" CEMENT USED. 	 CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/ UIRMENTS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd state.nm.us/ocd.	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMEN PERF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION. NIPPLE DOWN CUT & CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQ CLOSED LOOP SYSTEM USED, CLASS "C" CEMENT USED.	 CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/ UIRMENTS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd state.nm.us/ocd.	
 4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMENT PROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMENT PREF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION. NIPPLE DOWN CUT & CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQ CLOSED LOOP SYSTEM USED, CLASS "C" CEMENT USED. 	 CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/ UIRMENTS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd state.nm.us/ocd.	
 4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'-PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'-04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMENT PERF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION. NIPPLE DOWN CUT & CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQ CLOSED LOOP SYSTEM USED, CLASS "C" CEMENT USED. 	 CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/ UIRMENTS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd state.nm.us/ocd. 	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMEN PERF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION. NIPPLE DOWN CUT & CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQ CLOSED LOOP SYSTEM USED, CLASS "C" CEMENT USED.	PCEMENT ON TOP OF EACH. CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/ UIRMENTS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrdstate.nm,us/ocd. ge and belief. ADATE04 / 23 / 15	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/2 7/8" TBG. 100 JTS 04/20/15 RIH W/2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMENT PRF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION. NIPPLE DOWN CUT & CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQ CLOSED LOOP SYSTEM USED, CLASS "C" CEMENT USED. Spud Date: Rig Release Date: I hereby certify that the information above is true and complete to the best of my knowled SIGNATURE THE Agent for Chevron U.S Type or primename Monty L. McCarver E-mail address: monty.mccarver@cjes.c	PCEMENT ON TOP OF EACH. CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/ UIRMENTS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrdstate.nm,us/ocd. ge and belief. ADATE04 / 23 / 15	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMEN PERF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION. NIPPLE DOWN CUT & CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQ CLOSED LOOP SYSTEM USED, CLASS "C" CEMENT USED.	PCEMENT ON TOP OF EACH. CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/ UIRMENTS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrdstate.nm,us/ocd. ge and belief. ADATE04 / 23 / 15	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMENT PERF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION. NIPPLE DOWN CUT & CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQ CLOSED LOOP SYSTEM USED, CLASS "C" CEMENT USED. Spud Date: Rig Release Date: I hereby certify that the information above is true and complete to the best of my knowled SIGNATURE Type or printname Monty L. McCarver E-mail address: monty.mccarver@cjes.c For State Use Only	PCEMENT ON TOP OF EACH. CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/ UIRMENTS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd. ge and belief. ADATE04 / 23 / 15 omPHONE: _713-325-6288	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMENT PERF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION. NIPPLE DOWN CUT & CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQ CLOSED LOOP SYSTEM USED, CLASS "C" CEMENT USED. Spud Date: I hereby certify that the information above is true and complete to the best of my knowled SIGNATURE THELE_Agent for Chevron U.S Type or printhameMonty L. McCarver_ E-mail address:monty.mccarver@cjes.c For State Use Only APPROVED BY:	PCEMENT ON TOP OF EACH. CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/ UIRMENTS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrdstate.nm,us/ocd. ge and belief. ADATE04 / 23 / 15	
4,000', PERFS 6,015'-6,020', TD- 8,450', CIBP'S @ 7,950' & 5,950' W/ 35 04/18/15 MOVE IN & SPOT EQUIPMENT 04/19/15 NU FLOW BACK TANK, RIG UP, NU BOP, POOH W/ 2 7/8" TBG. 100 JTS 04/20/15 RIH W/ 2 3/8" WS, TAG CEMENT @ 5,904', CIR MUD TO SURF, MIX & SI 04/21/15 PERF @ 4,300' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 4,369'- PERF @ 3,855' UNABLE SQZ SPOT 30 SX CL "C" CEMENT FROM 3,905'- 04/22/15 RIH TAG @ 3,584', PERF 5 ½" @ 2,810', MIX & SQZ 70 SX CL "C" CEMENT PERF 5 ½" @ 520' CIR 173 SX CL "C" CEMENT FROM 400'- SURFACE ON BOTH NMOCD ABOUT PREVIOUS DAY OPERATION. NIPPLE DOWN CUT & CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQ CLOSED LOOP SYSTEM USED, CLASS "C" CEMENT USED. Spud Date: Rig Release Date: I hereby certify that the information above is true and complete to the best of my knowled SIGNATURE Type or printname Monty L. McCarver E-mail address: monty.mccarver@cjes.c For State Use Only	PCEMENT ON TOP OF EACH. CALLED LAURA W/ NMOCD. POT 25 SX CL "C" FROM 5,904'-5,660'. 4,070' OK BY RANDY DADE W/ NMOCD. 3,609' OK BY RANDY DADE W/ NMOCD. NT FROM 2,810'-2,510', WOC & TAG 2,405', STRINGS. CALLED RANDY DADE W/ UIRMENTS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd. ge and belief. ADATE04 / 23 / 15 omPHONE: _713-325-6288	

l