Office Office NM OIL CONSERVATION of New Mexico Winerals and Natural Resources	Form C-103
DISTRICT = (3/3) 393-0101 ADTES (A-019-03)	Revised August 1, 2011
	WELL API NO. 30-015-31912
District II – (575) 748-1283 811 S. First St., Artesia, NM 88210 MAY 2612 CONSERVATION DIVISION	5. Indicate Type of Lease
<u>District III</u> – (505) 334-6178 1220 South St. Francis Dr.	STATE STEE
1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> – (505) 476-3460 RECEIVED Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	V-2705
87505	7. Lagar Nama an Unit Agreement Nama
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name Graham AKB State
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	
PROPOSALS.)	8. Well Number
1. Type of Well: Oil Well Gas Well Other P&A	
2. Name of Operator	9. OGRID Number 025575
Yates Petroleum Corporation 3. Address of Operator	10. Pool name or Wildcat
105 South Fourth Street, Artesia, NM 88210	Lost Tank; Delaware
4. Well Location	
i a	2310 feet from the West line
Section 2 Township 22S Range 31E	NMPM Eddy County
11. Elevation (Show whether DR, RKB, RT, GR, etc.	
3514' GR	The second secon
12. Check Appropriate Box to Indicate Nature of Notice,	Report or Other Data
12. Check Appropriate Box to indicate Nature of Notice,	Report of Other Data
NOTICE OF INTENTION TO: SUB	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR	K ☐ ALTERING CASING ☐
TEMPORARILY ABANDON	LLING OPNS. □ PANDA 🛛
. PULL OR ALTER CASING : □ MULTIPLE COMPL 🛠 🖸 📑 CASING/CEMEN	FJOB BARY TO THE STORE OF THE
DOWNHOLE COMMINGLE	
	RESOURCE DATE LIGHTAN 1962
OTHER: OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and the complete operations) of the complete operations.	
of starting any proposed work). SEE RULE 19:15:7:14 NMAC:- For Multiple Corproposed completion or recompletion.	npietions: Attach wellbore diagram of
proposed completion of recompletion.	
5/11/15 – NU BOP.	
5/12/15 – Presure tested casing to 500 psi for 5 min, held good. Pumped 40 bbls fresh water	r down tubing. Released packer. Dropped
1.5" ball, pressured up to 1250 psi. Set a CIBP at 6149'. Circulated 130 bbls fresh water.	
good. Spotted 25 sx Class "C" Neat cement on CIBP. Calc TOC is 5891'. Spotted 40 bbls	
sx Class "C" Neat cement from 4176'-3165'. Reverse circulated 30 bbls fresh water.	· ·
5/13/15 – Tagged TOC at 3090'. Spotted 120 sx Class "C" cement with 2% CaCl from 309	00'-1880'. WOC 4 hrs. Tagged TOC at 1880'.
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'.	
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 – Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx	
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 – Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx ND BOP. Topped well off with 5 sx.	Class "C" Neat cement from 60' up to surface.
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 – Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx	Class "C" Neat cement from 60' up to surface. IS PLUGGED AND ABANDONED. Approved for plugging of well here only.
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 – Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx ND BOP. Topped well off with 5 sx.	Class "C" Neat cement from 60' up to surface. IS PLUGGED AND ABANDONED. Approved for plugging of well here only. Lability under bond is retained pending receipt.
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 – Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx ND BOP. Topped well off with 5 sx.	Class "C" Neat cement from 60' up to surface. IS PLUGGED AND ABANDONED. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C. 103 (Subsequent Report of Well Plugging)
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 – Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx ND BOP. Topped well off with 5 sx.	Class "C" Neat cement from 60' up to surface. IS PLUGGED AND ABANDONED. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 – Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx ND BOP. Topped well off with 5 sx. 5/18/15 – Dug up anchors and cellar. Cut off wellhead. Installed dry hole marker. WELL	Class "C" Neat cement from 60' up to surface. IS PLUGGED AND ABANDONED. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C. 103 (Subsequent Report of Well Plugging)
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 – Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx ND BOP. Topped well off with 5 sx.	Class "C" Neat cement from 60' up to surface. IS PLUGGED AND ABANDONED. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 – Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx ND BOP. Topped well off with 5 sx. 5/18/15 – Dug up anchors and cellar. Cut off wellhead. Installed dry hole marker. WELL	Class "C" Neat cement from 60' up to surface. IS PLUGGED AND ABANDONED. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 – Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx ND BOP. Topped well off with 5 sx. 5/18/15 – Dug up anchors and cellar. Cut off wellhead. Installed dry hole marker. WELL Spud Date: Rig Release Date:	Class "C" Neat cement from 60' up to surface. IS PLUGGED AND ABANDONED. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.hm.us/ocd.
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 – Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx ND BOP. Topped well off with 5 sx. 5/18/15 – Dug up anchors and cellar. Cut off wellhead. Installed dry hole marker. WELL Spud Date: Rig Release Date:	Class "C" Neat cement from 60' up to surface. IS PLUGGED AND ABANDONED. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C 103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.hm.us/ocd.
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 – Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx ND BOP. Topped well off with 5 sx. 5/18/15 – Dug up anchors and cellar. Cut off wellhead. Installed dry hole marker. WELL Spud Date: Rig Release Date: I hereby certify that the information above is true and complete to the best of my knowledges.	Class "C" Neat cement from 60' up to surface. IS PLUGGED AND ABANDONED. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C 103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.hm.us/ocd.
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 — Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx ND BOP. Topped well off with 5 sx. 5/18/15 — Dug up anchors and cellar. Cut off wellhead. Installed dry hole marker. WELL Spud Date: Rig Release Date: I hereby certify that the information above is true and complete to the best of my knowledges.	Class "C" Neat cement from 60' up to surface. IS PLUGGED AND ABANDONED. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmard.state.htm.us/ocd.
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 – Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx ND BOP. Topped well off with 5 sx. 5/18/15 – Dug up anchors and cellar. Cut off wellhead. Installed dry hole marker. WELL Spud Date: Rig Release Date: Title Regulatory Reporting S	Class "C" Neat cement from 60' up to surface. IS PLUGGED AND ABANDONED. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C 103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.hm.us/ocd.
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 – Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx ND BOP. Topped well off with 5 sx. 5/18/15 – Dug up anchors and cellar. Cut off wellhead. Installed dry hole marker. WELL Spud Date: Rig Release Date: Title Regulatory Reporting S	Class "C" Neat cement from 60' up to surface. IS PLUGGED AND ABANDONED. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmard.state.hm.us/ocd. 1
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 – Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx ND BOP. Topped well off with 5 sx. 5/18/15 – Dug up anchors and cellar. Cut off wellhead. Installed dry hole marker. WELL Spud Date: Rig Release Date: Title Regulatory Reporting S Type or print name: Tina Huerta E-mail address: tinah@yatespetroleum	Class "C" Neat cement from 60' up to surface. IS PLUGGED AND ABANDONED. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmard.state.hm.us/ocd. 1
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 – Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx ND BOP. Topped well off with 5 sx. 5/18/15 – Dug up anchors and cellar. Cut off wellhead. Installed dry hole marker. WELL Spud Date: Rig Release Date: Title Regulatory Reporting S	Class "C" Neat cement from 60' up to surface. IS PLUGGED AND ABANDONED. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C 103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.hm.us/ocd. e and belief. [C] " [D] " [D]
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 – Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx ND BOP. Topped well off with 5 sx. 5/18/15 – Dug up anchors and cellar. Cut off wellhead. Installed dry hole marker. WELL Spud Date: Rig Release Date: Title Regulatory Reporting S Type or print name Tina Huerta E-mail address: tinah@yatespetroleum For State Use Only APPROVED BY: TITLE Title Total Date: TITLE	Class "C" Neat cement from 60' up to surface. IS PLUGGED AND ABANDONED. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmard.state.hm.us/ocd. 1
Spotted 120 sx Class "C" cement with 2% CaCl from 1880'-675'. 5/14/15 — Tagged TOC at 606'. Circulated 20 bbls salt water gel to surface. Spotted 15 sx ND BOP. Topped well off with 5 sx. 5/18/15 — Dug up anchors and cellar. Cut off wellhead. Installed dry hole marker. WELL Spud Date: Rig Release Date: Title Regulatory Reporting S Type or print name Tina Huerta E-mail address: tinah@yatespetroleum For State Use Only	Class "C" Neat cement from 60' up to surface. IS PLUGGED AND ABANDONED. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C 103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.hm.us/ocd. e and belief. [C] " [D] " [D]