Form 3160-5 (Augus 2007)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RY NOTICES AND MANAGEMENT

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS JUN Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals RECEIVED					NMNM0107697		
					6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE - Other instructions on reverse side.					7. If Unit or CA/Agreement, Name and/or No.		
1. Type of Well ☑ Oil Well ☐ Gas Well ☐ Other					8. Well Name and No. SCREWDRIVER 24 FEDERAL COM 2H		
2. Name of Operator Contact: STORMI DAVIS COG OPERATING LLC E-Mail: sdavis@concho.com					9. API Well No. 30-015-42914		
3a. Address 2208 WEST MAIN ARTESIA, NM 88210			o. (include area code) 48-6946		10. Field and Pool, or Exploratory LUSK; BONE SPRING, WEST		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					11. County or Parish, and State		
Sec 24 T19S R31E Mer NMP SESE 900FSL 190FEL					EDDY COUNTY, NM		
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATI	E NATURE OF N	NOTICE, RI	EPORT, OR OTHE	R DATA	
TYPE OF SUBMISSION	TYPE OF ACTION					* 'y.	
☐ Notice of Intent	☐ Acidize	Dec	-		ion (Start/Resume)	Water Shut-Off	
Subsequent Report	☐ Alter Casing ☐ Fracture Treat ☐ Reclam						
	_				orarily Abandon Drilling Operations		
☐ Final Abandonment Notice							
	☐ Convert to Injection ☐ Plug Back ☐ Water I						
13. Describe Proposed or Completed Op If the proposal is to deepen direction. Attach the Bond under which the wo following completion of the involved testing has been completed. Final At determined that the site is ready for fi	ally or recomplete horizontally, rk will be performed or provide operations. If the operation re- pandonment Notices shall be file	give subsurface the Bond No. o sults in a multip	locations and measu n file with BLM/BIA le completion or reco	red and true ve Required sub mpletion in a r	rtical depths of all pertin psequent reports shall be new interval, a Form 316	ent markers and zones. filed within 30 days 0-4 shall be filed once	
2/2/15 Spud well. TD 20" hole in w/300 sx. Circ 319 sx to su w/10# brine - no loss of circ.	e @ 775'. Set 16" 65# J-5 rface. WOC 18 hrs. Tes	5 csg @ 77 ² t csg to 2000	1'. Cmt w/600 sx #. Drilled out 5' b	Class C. Ta elow FS	iled		
2/6/15 TD 14 3/4" hole @ 277 in w/400 sx. Circ 195 sx to su w/10# brine - no loss of circ.	70'. Set 11 3/4" 47# J-55 rface. WOC 18 hrs. Tes	csg @ 2765' csg to 1500	. Cmt w/950 sx 0 #. Drilled out 5' b	Class C. Tail pelow FS	ed		
2/9/15 TD 10 5/8" hole @ 435 w/350 sx Class C. Tailed in w w/250 sx. Circ 277 sx to surfa below FS w/10# brine - no loss	/250 sx. Circ 227 sx. Cn .ce. WOC 18 hrs. Test c	nt Stage 2 w/	550 sx Class C.	Tailed in	pe 1	o/17/15 iox record	
14. Thought postific that the forms - ' '	true and correct						
14. I hereby certify that the foregoing is	Electronic Submission #2	93790 verifie	d by the BLM Well	Information	System		
	For COG O Committed to AFMSS for	PERATING LI or processing	C, sent to the Ca	risbad \M on 05/15/2	ASCEPTED I	OR RECORD	
Name (Printed/Typed) STORMI	DAVIS		Title PREPA	RER		טוו וובטטווט	

MAY 28 2015 Signature (Electronic Submission) 03/04/2015 THIS SPACE FOR FEDERAL OR STATE OFFICE USE CARLSBAD FIELD OFFICE Approved By Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Additional data for EC transaction #293790 that would not fit on the form

32. Additional remarks, continued

 $2/21/15\,$ TD.7 7/8" lateral @ 13841' (KOP @ 8589'). Set 5 1/2" 17# P-110 csg @ 13841'. Cmt w/900 sx Class H. Tailed in w/1300 sx. Circ 159 sx to surface.

2/23/15 Rig released.