

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-03310
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No. LC-058582
7. Lease Name or Unit Agreement Name Ballard Grayburg San Andres Unit
8. Well Number #001P
9. OGRID Number 236183
10. Pool name or Wildcat Loco Hills Queen Grayburg SA
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3588 GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
Tandem Energy Corporation

3. Address of Operator
2700 Post Oak Blvd. Ste. 1000, Houston, TX 77056

4. Well Location
Unit Letter H : 2310 feet from the North line and 330 feet from the East line
Section 6 Township 18S Range 29E NMPM County Eddy

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☒ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Rig up pulling unit; TOH with packer and tubing
RIH with Pkr 6 joints of plastic coated tubing, isolation packer (This will be used to isolate the hole in the 4-1/2" liner), and plastic coated tubing to surface.
Set bottom packer 50' above the Jackson sand.
Test backside of isolation packer to 500 psi
Return well to injection

NM OIL CONSERVATION
ARTESIA DISTRICT

MAY 26 2015

Spud Date:

Rig Release Date:

RECEIVED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. Lockett TITLE Regulatory Specialist DATE 05/20/2015

Type or print name L. Kiki Lockett E-mail address: kikil@t5energy.com PHONE: 713-987-7326

For State Use Only

APPROVED BY: Rebecca / maw TITLE Compliance Officer DATE 6/16/15
Conditions of Approval (if any):