. #		~				
Form 3160-5 (August 2007) UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT OCD Artes			sia	FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010 5. Lease Serial No.		
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.				NMNM19848 6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE - Other instructions on reverse side.				7. If Unit or CA/Agreement, Name and/or No.		
1. Type of Well				8. Well Name and No. CYPRESS 33 FEDERAL COM 7H		
2. Name of Operator OXY USA INCORPORATED Contact: DAVID STEWART				9. API Well No. 30-015-42616-00-X1		
3a. Address 5 GREENWAY PLAZA STE 1 HOUSTON, TX 77046-0521	No. (include area code) 685.5717	ea code) 10. Field and Pool, or Exploratory CEDAR CANYON				
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				11. County or Parish, and State		
Sec 33 T23S R29E NENW 0150FNL 1900FWL 32.268056 N Lat, 103.991766 W Lon				EDDY COUNTY, NM		
12. CHECK APPI	ROPRIATE BOX(ES) TO INDICA	TE NATURE OF N	NOTICE, RI	EPORT, OR OTHE	R DATA	
TYPE OF SUBMISSION	TYPE OF ACTION			:	-	
X Notice of Intent		eepen racture Treat	Product	ion (Start/Resume)	☐ Water Shut-Off ☐ Well Integrity	
Subsequent Report		ew Construction	C Recomp		🔀 Other	
Final Abandonment Notice		lug and Abandon lug Back	 Temporarily Abandon Water Disposal 		Change to Original A PD	
If the proposal is to deepen direction Attach the Bond under which the wor following completion of the involved	eration (clearly state all pertinent details, incl ally or recomplete horizontally, give subsurfa rk will be performed or provide the Bond Nor i operations. If the operation results in a mult pandonment Notices shall be filed only after a inal inspection.)	ce locations and measu on file with BLM/BIA or reco	red and true ve Required sub moletion in a r	rtical depths of all pertin osequent réports shall be new interval, a Form 316	ent markers and zones. filed within 30 days 0-4 shall be filed once	
OXY USA Inc. respectfully rec	quests approval for the following cha	nges to the drilling	plan:	Acc	cepted for record,	
1. Extend the BHL approximately 170' past the east hardline to allow for our shoe track, see attached for amended C-102 plat and amended directional drilling plan.				AD NMOCD 4/27/13		
Proposed TD - 13592'M 8746'V				NM OIL CONSERVATION ARTESIA DISTRICT		
2. Adjust production casing and cementing to amended TMD.						
Production Casing 5-1/2" 17# L-80 BT&C new cs	g @ 0-13592'M, 7-7/8" hole w/ 9.2#	mud		APR O	6 2015	
				RECEIVED		
14. I hereby certify that the foregoing is	true and correct. Electronic Submission #261902 verif For OXY USA INCORPOR nmitted to AFMSS for processing by D		~ · · · ·		OR RECORD	
Name(Printed/Typed) DAVID ST	EWART	Title REGUL	ATORY AD	/ISOF		
Signature (Electronic S	Submission)	Date 09/08/20)14	MAR 3	1 2015	
	THIS SPACE FOR FEDER	RAL OR STATE	OFFICE US		am	
Approved By		Title		BUREAU OF LAN CARLSBAD	FIELO OFFICE	
Conditions of approval, if any, are attached certify that the applicant holds legal or equivient would entitle the applicant to condu	r		for C. l	walls		
Fitle 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent s	U.S.C. Section 1212, make it a crime for any statements or representations as to any matter	person knowingly and within its jurisdiction.	willfully to ma	ke to any department or a	agency of the United	

** BLM REVISED **

Additional data for EC transaction #261902 that would not fit on the form

32. Additional remarks, continued

Coll Rating (psi)-6290 Burst Rating (psi)-7740 SF Coll-1.56 SF Burst-1.25 SF Ten-1.74

Production Cement - Circulate cement w/ 660sx Tuned Light cmt w/ .125#/sx Poly-E-Flake + .80% HR-601 + 3#/sx Kol-Seal, 9.76ppg (10.2 downhole) 3.46 yield 788# 24hr CS 100% Excess followed by 830sx Super H cmt w/ 3#/sx salt + .3% CFR-3 + .5% Halad-344 + .1% HR-800 + 2#/sx Kol-Seal, 13.2ppg 1.65 yield 701# 24hr CS 40% Excess,

Description of Cement Additives: Salt (Accelerator); CFR-3 (Dispersant); Kol-Seal, Poly-E-Flake (Lost Circulation Additive); Halad-344 (Low Fluid Loss Control); HR-601, HR-800 (Retarder)

The above cement volumes could be revised pending the caliper measurement.