Form 3160-5 (August 2007)

### **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0137 Expires: July 31, 2010

5. Lease Serial No. NMNM11039

6. If Indian, Allottee or Tribe Name

# SUNDRY NOTICES AND REPORTS ON WELLS

	orm for proposals t Use Form 3160-3 (A			i <b>.</b>			
SUBMIT IN TRIPLICATE – Other instructions on page 2.					7. If Unit of CA/Agreement, Name and/or No.		
1. Type of Well		•					
Oil Well Gas W	ell Other				8. Well Name and No. BRUSHY 12-A FEDERAL 1		
Name of Operator     CHEVRON USA INC.     CONTACT: monty.mccarver@cjes.com					9. API Well No. 30-015-25615		
3a. Address				2)	10. Field and Pool or Exploratory Area		
15 SMITH RD. MIDLAND, TX. 79705		713-325-6288	}		BRUSHY DRAW DELAWARE		
4. Location of Well (Footage, Sec., T.R., M., or Survey Description)					11. Country or Parish, State		
SEC 12 T26S R29E MER NMP 2021 FNL 630 FWL.					EDDY COUNTY, NM		
12. CHEC	K THE APPROPRIATE BO	DX(ES) TO IND	ICATE NATURE	OF NOTIC	E, REPORT OR OTHE	R DATA	
TYPE OF SUBMISSION			TYP	E OF ACT	ON		
✓ Notice of Intent	Acidize	Deepe	en	Produ	ction (Start/Resume)	Water Shut-Off	
V Notice of Intent	Alter Casing	Fracti	ıre Treat	Recla	mation	Well Integrity	
Subsequent Penert	Casing Repair	☐ New (	Construction	Recor	mplete	Other	
Subsequent Report	Change Plans	Plug a	and Abandon	☐ Temp	orarily Abandon		
Final Abandonment Notice	Convert to Injection	Plug I	 Back	Water	er Disposal		
determined that the site is ready for 8 5/8" 24# @ 700' EST. TOC SURF, ESTIMATE START DATE 07 / 06 / 1  P & A PROCEDURE, NOTIFY BLM  1) SET 4 1/2" CIBP @ 3,200" W/  2) PERF & SQZ 40 SX CL "C" CMT.  3) PERF & SQZ DEEP PENETRATI VERIFY CMT TO SURFACE ON BC  4) CUT OFF WELLHEAD 3' BGL, IN BOND COVERAGE: CA 0329  NM OIL CONS  ARTESIA DI:  JUL 0 6	4 1/2" 10.5# 3,480' EST.  48 HOURS BEFORE MC  SX CL "C" CEMENT ON FROM 2,950'-2,750' (BA NG 235 SX CL "C" CMT I OTH STRINGS OF CASIN ISTALL REQUIRED DRY  ERVATION STRICT	OVE IN (575) 23 /31 TOP, 3 <del>,200-3</del> ASE LOWER S FROM 770' TO IG. HOLE MARKE	34-5909. 3000 (DELAWAI ALT) "WOC & T SURFACE. (SA	RE SAND TAG". ALADO, SI	& LIME ), CIR W/ MU HOE & ANHYDRITE ) AMATION. ACCO	D LADEN FLUID THRU TUBING.	
14. I hereby certify that the forces w	(End correct. Name (Printe	d/Typed)					
Monty L. McCarver			Title Agent for	Chevron L	JSA Inc.		
Signature			Date 6/	17/	15		
	THIS SPACE	FOR FEDE	RAL QR STA	TE OFF	ICE USE		
Conditions of approval, if any, are attached that the applicant holds legal or equitable tintitle the applicant to conduct operations to Title 180.S.C. Section 1001 and Title 43 licitities or fraudulent statements or representations.	tle to those rights in the subjective hereon.  U.S.C. Section 1212, make it a	ct lease which wo	ould Office erson knowingly and	CAE,		or agency of the United States any false,	

(Instructions on page 2)

### **GENERAL INSTRUCTIONS**

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

### SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13 - Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment.

### **NOTICES**

The Privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and grantingapproval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

### SUPPLEMENTAL DRILLING PLAN

# THE PETROLEUM CORPORATION OF DELAWARE

# BRUSHY 12 FEDERAL ##

SW/4, NW/4, Sec. 12, T-26-S, R-29-E

- ١. SURFACE FORMATION: Unconsolidated Sands of Quaternary Age.
- 2. ESTIMATED TOPS OF GEOLOGIC MARKERS (G.L. Elevation 2978'):

Anhydrite	675'	Delaware Sand	3135'
Salado	770'	Cherry Canyon	4050'
Base Lower Salt	2900'	Brushy Canyon	5200'
Delaware Lime	3100'	•	

#### 3. POSSIBLE HYDROCARBON BEARING ZONES:

Bell Canyon:

Oil & Gas

Cherry Canyon: Oil Brushy Canyon: Oil

#### 4. **CASING DESIGN:**

<u>Size</u>	<u>Interval</u>	Weight	<u>Grade</u>	Joint
8 5/8"	0 - 700'	24.0#	J-55	STC
5 ½"	0 - 5600'	15 <b>.</b> 5#	J-55	STC ·

Set DV Tool at 3600' & cement across Bell Canyon up into salt section.

- 5. PRESSURE CONTROL EQUIPMENT: Two Ram-Type Preventors. sketch of BOP arrangement is attached.
- 6. CIRCULATING MEDIUM:

0' - 700' Fresh water with gel or lime as needed for viscosity. 700' - 3100'


3100' - 5600'

Cut brine conditioned as necessary for control of viscosity and water loss.

- 7. **AUXILIARY EQUIPMENT:** Drill string safety valve.
- 8. TESTING, LOGGING AND CORING PROGRAMS: No coring or DST's are planned. Electric logs will include a compensated Neutron Log with Gamma Ray.
- 9. ABNORMAL PRESSURES, TEMPERATURES OF GAS: None anticipated.
- ANTICIPATED STARTING DATE: 10. It is planned that operations will commence as soon as possible. Duration of drilling, completion and testing operations should be two to six weeks.

# **Current Wellbore Schematic**

API#: 3001525615 Serial #: SPUD DATE: 6/14/1987 RIG RELEASE: 6/14/1987 1ST SALES GAS:



# **Current Wellbore Schematic**

WELL (PN): BRUSHY 12-A FEDERAL 1(CVX) (891208) FIELD OFFICE: HOBBS FIELD: BRUSHY DRAW DELAWARE STATE / COUNTY: NEW MEXICO / EDDY LOCATION: SEC 12-26S-29E, 2021 FNL & 630 FWL ROUTE: HOB-NM-ROUTE 32- LUIS TAVAREZ ELEVATION: GL: 2,978.5 KB: 2,984.5 KB Height: 6.0 DFPTHS: TD: 3 500 0

API#: 3001525615 Serial #: SPUD DATE: 6/14/1987 RIG RELEASE: 6/14/1987 1ST SALES GAS:

1ST SALES OIL: 7/1/1987 DEPTHS: TD: 3,500.0 Current Status: PRODUCING Bypass 1, 5/21/2013 8:39:36 AM .MD (ftKB) Vertical schematic (actual) -17.7 5.9 8.5 12.5 18.4 Casing Joints; 6.0-709.0; 703.00; 8 5/8; 8.097; 24.00; 1-1 709.0 Float Shoe; 709.0-710.0; 1.00; 8 5/8; 1-2 710.0 PERFYCIR 2355X FROM 770-SURFACE 1,468.5 PERFYSAZ 405X 2,950-2,750 TAG 1,791.0 2,338.9 2.419.9 CIBP@3,200 w/155x To 3,000 3,232.0 Perf; 3,232.0-3,238.0; 3/9/1994 3,237.9 Perf; 3,238.0-3,244.0; 7/13/1987 3,243.4 3,244.1 3,258.2 3,259.5 3,263.5 3,296.3 3,296.9 3,324.1 3,344.21 3.467.8 3,479.0 Float Shoe; 3,479.0-3,480.0; 1.00; 4 1/2; 2-2 3,480.0 3,500.0

# BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

## Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

J. Amos 3/6/11



# United States Department of the Interior

### **BUREAU OF LAND MANAGEMENT**

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

### **Reclamation Objectives and Procedures**

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of
  Operations must include adequate measures for stabilization and reclamation of disturbed lands.
  Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD
  process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909, 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Linda Denniston Environmental Protection Specialist 575-234-5974

Henryetta Price Environmental Protection Specialist 575-234-5951

Dara Glass Environmental Protection Specialist 575-234-5924

Shelly Tucker Environmental Protection Specialist 575-234-5979 Cody Layton Supervisory Multi Resources 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Jeffery Robertson Natural Resource Specialist 575-234-2230