

Submit To Appropriate District Office
Two Copies
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-105
July 17, 2008

1. WELL API NO.
30-015-42899

2. Type of Lease
 STATE FEE FED/INDIAN

3. State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

4. Reason for filing:
 COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only)
 C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)

5. Lease Name or Unit Agreement Name
JEFFERS 36 STATE

6. Well Number: #6

7. Type of Completion:
 NEW WELL WORKOVER DEEPENING PLUGBACK DIFFERENT RESERVOIR OTHER

8. Name of Operator: **LRE OPERATING, LLC**

9. OGRID: 281994

10. Address of Operator: c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401

11. Pool name or Wildcat:
Red Lake, Glorieta Yeso NE (96836)

12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County
Surface:	B	36	17-S	27E		890	North	1655	East	Eddy
BH:									t	

13. Date Spudded 5/25/15	14. Date T.D. Reached 5/29/15	15. Date Drilling Rig Released 5/30/15	16. Date Completed (Ready to Produce) 6/8/15	17. Elevations (DF and RKB, RT, GR, etc.): 3624' GR
-----------------------------	----------------------------------	---	---	--

18. Total Measured Depth of Well 3610'	19. Plug Back Measured Depth 3558'	20. Was Directional Survey Made? Yes	21. Type Electric and Other Logs Run Casing Holé Neutron
---	---------------------------------------	---	---

22. Producing Interval(s), of this completion - Top, Bottom, Name
3240'-3510' - Yeso

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24# J-55	429'	11"	450 sx CI C	0'
5-1/2"	17# J-55	3610'	7-7/8"	300 sx 35/65 Poz/C + 350 sx C	0'

24. LINER RECORD				25. TUBING RECORD			
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2-7/8"	3492'	

26. Perforation record (interval, size, and number)
Yeso: 3240'-3510', 46-0.42" holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.	
DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
3240'-3510'	1500 gals 7.5% HCL; fraced w/31,015# 100 mesh & 367,862# 40/70 Ottawa sand in slick water.

28. PRODUCTION

Date First Production READY	Production Method (<i>Flowing, gas lift, pumping - Size and type pump</i>) Pumping	Well Status (Prod. or Shut-in) Pumping					
Date of Test Within 30 days	Hours Tested	Choke Size	Prod'n For Test Period:	Oil - Bbl	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)	

29. Disposition of Gas (*Sold, used for fuel, vented, etc.*)
To Be Sold


30. Test Witnessed By:
Jerry Smith

31. List Attachments

32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.
33. If an on-site burial was used at the well, report the exact location of the on-site burial:

Latitude _____ Longitude _____ NAD 1927 1983

I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature:  Printed Name: Mike Pippin Title: Petroleum Engineer Date: 6/16/15

E-mail Address: mike@pippinllc.com



INSTRUCTIONS

JEFFERS 36 STATE #6 -- New Well

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn A"
T. Salt	T. Strawn	T. Kirtland	T. Penn. "B"
B. Salt	T. Atoka	T. Fruitland	T. Penn. "C"
T. Yates	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers 456'	T. Devonian	T. Cliff House	T. Leadville
T. Queen 980'	T. Silurian	T. Menefee	T. Madison
T. Grayburg 1490'	T. Montoya	T. Point Lookout	T. Elbert
San Andres 1751'	T. Simpson	T. Mancos	T. McCracken
T. Glorieta 3117'	T. McKee	T. Gallup	T. Ignacio Otzte
T. Yeso 3218'	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinebry	T. Gr. Wash	T. Dakota	
T. Tubb	T. Delaware Sand	T. Morrison	
T. Drinkard	T. Bone Springs	T. Todilto	
T. Abo	T.	T. Entrada	
T. Wolfcamp	T.	T. Wingate	
T. Penn	T.	T. Chinle	
T. Cisco (Bough C)	T.	T. Permian	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
 No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to..... feet.....
 No. 2, from.....to..... feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
			- On File -				