Form 3160-5 (August 1999)

DEPARTMENT OF THE INTERIOR DIV-DIST. 2 BUREAU OF LAND MANAGEMENT OF AVOIDING

FORM APPROVED OMB No. 1004-0135 Expires November 30, 2000

BUREAU OF LAND MANAGEMERING AVENUE						5. Lease Serial No.		
SUNDRY NOTICES AND REPORTS ON WELLS. Do not use this form for proposals to drill of to reside and abandoned well. Use Form 3160-3 (APD) for such proposals.					NM-93181 6. If Indian, Allottee or Tribe Name			
	RIPLICATE © their instruc	tions on re	Versieisje	e rstative strik	7. If Unit	or CA/Agreement, Na	me and/or No.	
1. Type of Well Oil Well Gas Well Other						8. Well Name and No. 1725 Fed Com #61		
2. Name of Operator LCX Energy, LLC					9. API We	9. API Well No. 30-015-34340		
3a. Address 110 N. Marienfeld Ste 200, Midland, TX 79701 3b. Phone No. (include area code) (432) 687-1575					10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)						Cottonwood Creek; Wolfcamp		
SL: 660' FNL & 760' FWL Sec. 6, T17S, R25E NOV 0 4 2005						11. County or Parish, State		
ALGET TAN-UOO						Eddy County, NM		
12. CHECK A	PPROPRIATE BOX(ES) TO	INDICATE 1	VATURE (OF NOTICE, R	EPORT, OI	R OTHER DATA	<u> </u>	
TYPE OF SUBMISSION TYPE OF ACTION								
☐ Notice of Intent		Deepen Fracture Tre		Production (Start	t/Resume)	Water Shut-Of Well Integrity	f	
Subsequent Report	\ -	New Constru	oction 📮	Recomplete		Other Spud	well &	
	I	Plug and Ab	-	• •	andon	ran casi	ng	
Final Abandonment Notice	Convert to Injection	Plug Back	<u>_</u>	Water Disposal		·		
Attach the Bond under which following completion of the in testing has been completed. I determined that the site is read 10/7/05 Spud well w follows: Pump 20 b & displace 55 bbls of Cement 1" - 1st stag @70'. Mix & pump Held 30 min. Actua 10/10/05 Ran 30 jts follows: Mix & pum (10-2-A) + additives 14.8# cement. Drop lead ret'd to pit. WO BOP & choke manif	bls FH20 spacer. Mix & fFH20. Bumped plug 50 e - Plug @160'. Mix & p down 20 bbls @ 14.8# & time WOC 15 hrs. 9 5/8" 36#, J55, ST&C c np 20 bbls FW gel spacer. @ 14.2# cement. Mix & plug & displace w/96.7 to C. Install wellhead & testold. Test BOP & all surfice.	de the Bond No esults in a multifiled only after 13 3/8" 48# pump 77 sl 00 psi over nump down a circ 10 bb sg. Tag bo . Mix & pu to pump tail obls of FH2 st to 1500 p	on file with ple completic all requirements. H-40 ST (cs-205 bb float. He float to pit. ttom @ lamp lead slurry of to. Bumposi. Held	BLM/BIA. Requision or recompletion ints, including recker. C&C casing. Dis of lead slueld 30 min. National Processing of 14.8#. WC WOC. Instance of 188 color of	Casing searcy & 47: No return of the control of the	at reports shall be file val, a Form 3160-4 sl been completed, and et @ 389'. Cen sks-200 bbls ta con cement. We ent 1" - 2nd sta d. Test to 150 294' TVD. 50 sks of Class Class "C" + add loat held ok. 1 choke manifold	d within 30 days hall be filed once the operator has mented as hil slurry OC age - Plug 00 psi. Cement as s RFC ditives @ 45 bbls of l. Test	
14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)					ACC	EFICUTOR	112001	
Sharon Hindman		1	itle Regu	latory Agent			2005	
Signature Sharon	Hindman	I	Date 11/01	1/2005		NOV - 2 2	2005	
en particular de la companya de la c	THIS SPACE FO	RIFEDERAL	OR STAT	E OFFICE USE	300 S 24.3	CATYLOUS		
Approved by			Title	•	L	ate		
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.							***	