Form 3160-5 (August 1999)

MINMED CHARGONS. DIV-DIST. 2 DEPARTMENT OF THEATTERIOR OF AVENUE

DEPARTMENT OF THE INTERIOR OF AVENUE

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

RECEIVED

NOV 1 7 2005

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

Expires: November 30, 2000

5.	Lease Serial No.
NM	-036975
6.	If Indian, Allottee or Tribe Name

abandoned well. Use Fort						
SUBMIT IN TRIPLICATE - Other instructions on reverse side					CA/Agreement, Name and/or N	
Type of Well Oil Well X Gas Well Other 2. Name of Operator Occidental Reputation Limited Reputations	8. Well Name and No. OPL Stent Federal #1					
Occidental Permian Limited Partners 3a. Address P.O. Box 50250. Midland. TX 79710-	3b. Phone No. (include are: 432-685-5717	157984 a code)	9. API Well No. 30-015-34333 10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 990 FSL 1400 FWL SESW(N) Sec 21 T24S R28E					Undsg. Malaga Morrow 11. County or Parish, State Eddy NM	
12. CHECK APPROPRIATE	BOX(ES) TO INI	DICATE NATURE OF N	OTICE, REPO	ORT, OR OT	HER DATA	
TYPE OF SUBMISSION		TYP	E OF ACTION			
Notice of Intent Subsequent Report Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injecti	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production Reclamatio Recomplet Temporaril Water Disp	e y Abandon	Water Shut-Off Well Integrity X Other Spud Set casing & cement	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

See Attached

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) David Stewart	Title Sr. R	egulatory Analyst							
fi stat	Date (1/2/05							
ACCEPTED FOR RECOTHIS SPACE FOR FEDERAL OR STATE OFFICE USE									
Approved by C SCD DAVID & CLASS	Title		Date						
Approved by Conditions of approval of this notice does not warrancertify that the applicant holds legal or equitable title to those rights in the subject which would entitle the applicant to conduct operations thereon.	nt or Office ease								

Title 18 U.S.C. Section 1901; and Title 43 S.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, figuriting or fraudulent statements or representations as to any matter within its jurisdiction.

OPL STENT FEDERAL #1

10/23/2005 CMIC: DOLLAHAN

McVAY HELD PRE-JOB SAFETY MEETING. McVAY RIG #8 SPUDDED WELL AT 6:30 AM, 10-22-2005. DRILLED 17 1/2" HOLE TO 192' AND STARTED LOOSING RETURNS, TOTAL LOSS AT 340'. DRY DRILL TO 650'. TIH FOR 13 3/8" SURFACE CSG. MIRU BULL ROGERS AND HELD A PRE-JOB SAFETY MEETING. TIH W/ TEXAS PATTERN SHOE, 1 JT, BAFFEL PLATE AND 14 JTS OF 13 3/8" 48# H40 STC TO 650'. MIRU HALLIBURTON SERVICES AND HELD A PRE-JOB SAFETY MEETING. CEMENTED CSG W/ 150 SK THIXOTROPIC, 425 HALLIBURTON LITE, AND 250 SK PREMUIM PLUS. DID NOT CIRC CEMENT. WAITING ON CEMENT FOR 1" AT REPORT TIME.

10/24/2005 CMIC: DOLLAHAN

MADE 3 ATTEMPS TO 1" CEMENT TO SURFACE WITH 185 SK OF PREMIUM PLUS W/ 3% CACL. 50 SK PER TRY ON FIRST TWO ATTEMPS. CIRC CMT ON 3rd. MADE CUT OFF AND WELD ON STARTING HEAD. NU BOPE AND TESTED TO 1000#. TIH W/ 12 1/4" BIT. DRILL CMT AND NEW FORMATION. DRILLING AHEAD AT REPORT TIME WITH NO PROBLEMS.

10/25/2005 CMIC: DOLLAHAN

CHG OUT SWIVEL PACKING AT REPORT TIME.

10/26/2005 CMIC: DOLLAHAN

DRILLING AHEAD AT REPORT TIME WITH NO PROBLEMS.

10/27/2005 CMIC: DOLLAHAN

DRILLING AHEAD AT REPORT TIME WITH NO PROBLEMS.

10/28/2005 CMIC: DOLLAHAN

DRILLED TO 2471' AND TOH FOR BHA AND BIT CHG. DRILLED TO 2704' PUMP SWEEP AND TOH FOR CSG. WAITING ON LD MACHINE AT REPORT TIME.

10/29/2005 CMIC: DOLLAHAN

MIRU LD MACHINE AND HELD A PRE-JOB SAFETY MEETING. TOH LD 8" DCS AND TOOLS. MIRU BULL ROGERS CASING CREW AND HELD A PRE-JOB SAFETY MEETING. TIH WITH GS, 1 JT, FC AND 62 JTS OF 9 5/8" 36# J-55 LTC CASING TO 2704. CIRC WELL AND MIRU HALLIBURTON SERVICES. HELD A PRE-JOB SAFETY MEETING AND CEMENT CASING WITH 650 SX INTERFILL "C" FB 200 SX PREMIUM PLUS. PLUG DOWN AT 3:45 PM, 10-28-2005, CIRC 175 SX TO PIT. NOTIFIED CLARK BENNETT WITH BLM BUT DID NOT WITNESS. SET SLIPS AND MADE CUTOFF. NU BOPE AND TESTING AT REPORT TIME WITH NO PROBLEMS.

10/30/2005 CMIC: DOLLAHAN

TESTED BOPE TO 5000# HIGH AND 250# LOW. PU BHA AND TIH. TESTED CASING TO 1500#, OK. DRILLED CEMENT AND FC TO 2704. DRILLING NEW FORMATION AT 1:45 PM, 10-29-2005. DRILLING AHEAD AT REPORT TIME WITH NO PROBLEMS.

64 OF 1 6- 13 507

MINE TO THE WARRENCE WARREN