Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD-ARTESIA

FORM APPROVED OMB No. 1004-0135

SUNDRY NOTICES	AND	DEDODTS	ONIMELI	
SUNDRY NOTICES		REPORTS		

Expires March 31, 2007

SUNDRY NOTICES AND REPORT Do not use this form for proposals to dri	5. Lease Serial No. NM-94589			
abandoned well. Use Form 3160-3 (APD) fo	6. If Indian, Allottee or Tribe Name			
SUBMIT IN TRIPLICATE - Other instru	uctions on reverse side	7. If Unit or CA/Agreement, Name and/or No.		
1. Type of Well Oil Well X Gas Well Other	RECEIVED	8. Well Name and No.		
2. Name of Operator	DEC 2 3 2005	Chosa ATR Federal #2		
Yates Petroleum Corporation	AND THAT SOLD	9. API Well No.		
3a. Address 105 S. 4th Str., Artesia, NM 88210	3b. Phone No. (include area code) 505-748-1471	30-015-34210		
4. Location of Well (Footage, Sec., T., R., M., OR Survey Description)	JUJ-740-14/1	10. Field and Pool, or Exploratory Area Undesignated Chosa Draw Morrow 11. County or Parish, State		
710'FSL & 710'FWL of Section 5-T25S-R26E (Unit M, SWSW)		Eddy County, New Mexico		
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA				
TYPE OF SUBMISSION	TYPE OF ACTION			
Notice of Intent Notice of Intent Subsequent Report Acidize Alter Casing Casing Repair Change Plans	Deepen Production (Fracture Treat Reclamation New Construction Recomplete Plug and Abandon Temporarily	Start/Resume) Water Shut-Off Well Integrity Other Surface and		
Final Abandonment Notice Convert to Injection	Plug Back Water Dispo	sal <u>casing</u>		
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days. following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandomment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 12/6/05 Resumed drilling at 10:00 AM. 12/7/05 Set 13-3/8" 48# H-40 ST&C casing at 390'. Cemented with 200 sx 35:65:6 "C" + 2% CaCl2 + 1/4# Celloflake (yld 2.01, wt 12.4). Tailed in with 200 sx "C" + 2% CaCl2 (yld 1.34, wt 14.8). Cement circulated to surface. Pressure tested casing to 600 psi for 30 min. WOC 27 hrs 45 min. Reduced hole to 12-1/4" and resumed drilling. 12/11/05 Set 9-5/8" 36# J-55 ST&C casing at 1818'. Cemented with 575 sx Halliburton Lite Premium Plus-SBM + 1/4# sx Flocele + 2% CaCl (yld 1.97, wt 12.5). Tailed in with 200 sx Premium Plus cement + 2% CaCl (yld 1.34, wt 14.8). Cement circulated to surface. WOC 18 hrs. Reduced hole to 8-3/4" and resumed drilling. DEC 2 1 2005 DEC 2 1 2005				
 I hereby certify that the foregoing is true and correct Name (Printed/Typed) 		ALEXIS C. SWOBODA PETROLEUM ENGINEER		
Tina Huerta	Title Regulatory Complia	ince Supervisor		
Signature (Sina) Hurta	Date December 12, 2005	;		
THIS SPACE	FOR FEDERAL OR STATE OFFICE USE			
Approved by	Title	Date		
Conditions of approval, if any, are attached. Approval of this notice doe certify that the applicant holds legal or equitable title to those rights in which would entitle the applicant to conduct operations thereon.				