Submit 3 Copies To Appropriate District Office		State of New Mexico Energy, Minerals and Natural Resources				Form C-103 Revised May 08, 2003	
District I 1625 N. French Dr., Hobbs, NM 87240					WELL API NO.		
District II 1301 W. Grand Ave., Artesia, NM 88210		OIL CONSERVATION DIVISION			30-015-34248 5. Indicate Type of Lease		
District III 1000 Rio Brazos Rd., Aztec, NM 87410		1220 South St. Francis Dr. Santa Fe, NM 87505			ATE	FEE X	
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87		, 141 41 07302			Oil & Gas Lease		
(DO NOT USE THIS FORM FOR PRODIFFERENT RESERVOIR. USE "APP PROPOSALS.)		EEPEN OR PL		7. Lease 1724 KII 8. Well N	NCAID	Agreement Name:	
1. Type of Well: Oil Well ☐ Gas Well 🗓] Other			o. Well I	111		
2. Name of Operator) Offici	RE(EINET	9. OGRII			
LCX ENERGY, LLC		FFA	1 0 2006		218885		
3. Address of Operator 110 N. MARIENFELD, SUITE	200. MIDLAND. TX 797	~~~	MULEON		name or Wildca EAGLE CREEK -		
4. Well Location					TOTAL STOCK		
Unit Letter D:_	feet from the	NORTH	line and	760	_ feet from the_	West line	
Section 11	Township	17S Rang	e 24E	NMPM	Cor	unty Eddy	
	11. Elevation (Show)	whether DR, I	KB, RT, GR, et	c.)			
12 Chaole	Annronriata Pay to I	3702' G		Donost (Other Det		
	Appropriate Box to In	ndicate Nat	•	•			
NOTICE OF IN PERFORM REMEDIAL WORK			SUB EDIAL WORK	SEQUE	NT REPOR	I OF: FERING CASING □	
	•				_		
TEMPORARILY ABANDON	CHANGE PLANS	_ con	MENCE DRILLI	ING OPNS.		JG AND ANDONMENT	
PULL OR ALTER CASING	MULTIPLE COMPLETION		ING TEST AND ENT JOB				
OTHER:		ОТН	ER:				
13. Describe proposed or complete of starting any proposed work or recompletion.							
2/1/06 - 2/2/06 DRILLED OUT CEMENT, 13 3/8" FLOAT, AND FORMATION TO 1292', SWEEP HOLE, POOH W/BIT. RU CASING CREW. RUN 36 JTS 9 5/8" 36# J55 STC CASING, TEXAS PATTERN GUIDE SHOE, INSERT FLOAT AT 1247.57', SET CASING AT 1292.21'. RAN 6 CENTRALIZERS. CIRCULATE THROUGH CASING. RIG UP CEMENTERS. CEMENT CASING W/440 SX 35/65 POZ CL C + ADDITIVES, WT. 12.4 PPG, TAIL IN W/ 200 SX CL C + 2% SL, WT. 14.8 PPG. DISPLACE W/97 BBLS FW. BUMP PLUG W/ 819 PSI, FLOAT HELD OK. CIRCULATE 132 SX CEMENT TO PIT. WOC 0.5 HOURS, ND BOPS, SET 9 5/8" SLIPS.							
2/3/06 NIPPLE UP BOPS. TEST BOPS 250 PSI LOW AND 3000 PSI, (ANNULAR 1500 PSI), HIGH OK. TIH, DRILLED CEMENT, FLOAT, SHOE. TESTED CASING 1000 PSI OK. TOTAL WOC 16.5 HRS BEFORE DRILLING ON CEMENT.							
I hereby certify that the information abo	ve is true and complete to the	best of my kn	owledge and belief	£.			
SIGNATURE Kanicie	Dand	TITLE	Regul at	ory Tech	DATE	2/7/06	
Type or print name KANICIA DAVID Telephone No. 432-848-0214							
(This space for State use)	FOR RECORDS O	NLY				FEB 1 3 2006	

FOR RECORDS ONLY

__ TITLE_

_ DATE _

APPROVED BY_______Conditions of approval, if any: