Submit 1 Copy TIMPORT District State of New Mexico	Form C-103
District 1 – (575) 393-610RTESIA DISTRICT Energy, Minerals and Natural Resources	Revised July 18, 2013 WELL API NO.
1625 N. French Dr., Hobbs, NM 88240 District II - (575) 748-1288 0 5 2015 OIL CONSERVATION DIVISION	30-015-41376
811 S. First St., Artesia, NM 88210 OIL CONSERVATION DIVISION	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztor Misitian	STATE FEE S
1220 S. St. Francis Dr., Santa Fe, NM	6. State Oil & Gas Lease No.
87505 SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	KAISER B 18B
1. Type of Well: Oil Well Gas Well Dother	8. Well Number #16
2. Name of Operator LIME ROCK RESOURCES II-A, L.P.	9. OGRID Number 277558
3. Address of Operator	10. Pool name or Wildcat
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401	Red Lake, Glorieta-Yeso NE (96836)
4. Well Location Unit Letter <u>B</u> : <u>380</u> feet from the <u>North</u> line and 2210	feet from the East line
Section 18 Township 18-S Range 27-E	NMPM Eddy County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3291' GL	
12. Check Appropriate Box to Indicate Nature of Notice, I	Report or Other Data
NOTICE OF INTENTION TO: SUB	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	
TEMPORARILY ABANDON 🔲 CHANGE PLANS 🔲 COMMENCE DRII	
PULL OR ALTER CASING D MULTIPLE COMPL CASING/CEMENT	JOB 🗌
CLOSED-LOOP SYSTEM X OTHER: OTHER: OTHER: Comp	etion 🕅
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates,	including estimated date of starting any proposed work).
SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed comp On 5/10/15 PT 5-1/2" csg to 5000 psi-OK. Perfed lower Yeso @ 4079', 4155', 4229	1 4303' 4377' & 4477' w/6-0 42" sof
Total 36 holes. On 9/17/15, treated w/1500 gal 15% HCL acid. Fraced Yeso w/60,	
sand in slick water. Spotted 500 gal 15% HCL for next frac stage.	
Set 5-1/2" CBP @ 4019' & 3970' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Ye	
32 holes. On 9/18/15, treated w/1568 gal 15% HCL acid & fraced w/33,179# 100 m	
slick water. Spotted 672 gal 15% HCL for next frac stage.	esh & 258,822# 40/70 Arizona sand in
Set 5-1/2" CBP @ 3510' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 3	106'-3432' w/1-0.42" spf. Total 29 holes.
	106'-3432' w/1-0.42" spf. Total 29 holes.
Set 5-1/2" CBP @ 3510' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 3 Treated w/1408 gal 15% HCL acid & fraced w/29,756# 100 mesh & 283,822# 40/70 gal 15% HCL for next frac stage.	106'-3432' w/1-0.42" spf. Total 29 holes. Arizona sand in slick water. Spotted 500
Set 5-1/2" CBP @ 3510' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 3 Treated w/1408 gal 15% HCL acid & fraced w/29,756# 100 mesh & 283,822# 40/70	106'-3432' w/1-0.42" spf. Total 29 holes. Arizona sand in slick water. Spotted 500 730'-3012' w/1-0.42" spf. Total 33 holes.
Set 5-1/2" CBP @ 3510' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 3 Treated w/1408 gal 15% HCL acid & fraced w/29,756# 100 mesh & 283,822# 40/70 gal 15% HCL for next frac stage. Set 5-1/2" CBP @ 3054' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 2 Treated w/1539 gal 15% HCL acid & fraced w/35,878# 100 mesh & 290,031# 40/70 On 9/19/15, MIRUSU. CO after frac, drilled out CBPs @ 3054', 3510', 3970' & 4019	106'-3432' w/1-0.42" spf. Total 29 holes. Arizona sand in slick water. Spotted 500 730'-3012' w/1-0.42" spf. Total 33 holes. Arizona sand in slick water.
Set 5-1/2" CBP @ 3510' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 3 Treated w/1408 gal 15% HCL acid & fraced w/29,756# 100 mesh & 283,822# 40/70 gal 15% HCL for next frac stage. Set 5-1/2" CBP @ 3054' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 2 Treated w/1539 gal 15% HCL acid & fraced w/35,878# 100 mesh & 290,031# 40/70	106'-3432' w/1-0.42" spf. Total 29 holes. Arizona sand in slick water. Spotted 500 730'-3012' w/1-0.42" spf. Total 33 holes. Arizona sand in slick water.
Set 5-1/2" CBP @ 3510' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 3 Treated w/1408 gal 15% HCL acid & fraced w/29,756# 100 mesh & 283,822# 40/70 gal 15% HCL for next frac stage. Set 5-1/2" CBP @ 3054' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 2 Treated w/1539 gal 15% HCL acid & fraced w/35,878# 100 mesh & 290,031# 40/70 On 9/19/15, MIRUSU. CO after frac, drilled out CBPs @ 3054', 3510', 3970' & 4019	106'-3432' w/1-0.42" spf. Total 29 holes. Arizona sand in slick water. Spotted 500 730'-3012' w/1-0.42" spf. Total 33 holes. Arizona sand in slick water.
Set 5-1/2" CBP @ 3510' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 3 Treated w/1408 gal 15% HCL acid & fraced w/29,756# 100 mesh & 283,822# 40/70 gal 15% HCL for next frac stage. Set 5-1/2" CBP @ 3054' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 2 Treated w/1539 gal 15% HCL acid & fraced w/35,878# 100 mesh & 290,031# 40/70 On 9/19/15, MIRUSU. CO after frac, drilled out CBPs @ 3054', 3510', 3970' & 4019 landed ESP on 2-7/8" 6.5# L-80 tbg @ 2674'. Released completion rig on 9/23/15.	106'-3432' w/1-0.42" spf. Total 29 holes. Arizona sand in slick water. Spotted 500 730'-3012' w/1-0.42" spf. Total 33 holes. Arizona sand in slick water.
Set 5-1/2" CBP @ 3510' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 3 Treated w/1408 gal 15% HCL acid & fraced w/29,756# 100 mesh & 283,822# 40/70 gal 15% HCL for next frac stage. Set 5-1/2" CBP @ 3054' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 2 Treated w/1539 gal 15% HCL acid & fraced w/35,878# 100 mesh & 290,031# 40/70 On 9/19/15, MIRUSU. CO after frac, drilled out CBPs @ 3054', 3510', 3970' & 4019 landed ESP on 2-7/8" 6.5# L-80 tbg @ 2674'. Released completion rig on 9/23/15. Bottom Hole @ 354' FNL & 2304' FEL Sec 18.	106'-3432' w/1-0.42" spf. Total 29 holes. Arizona sand in slick water. Spotted 500 730'-3012' w/1-0.42" spf. Total 33 holes. Arizona sand in slick water. 3', & CO to PBTD4650'. On 9/23/15,
Set 5-1/2" CBP @ 3510' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 3: Treated w/1408 gal 15% HCL acid & fraced w/29,756# 100 mesh & 283,822# 40/70 gal 15% HCL for next frac stage. Set 5-1/2" CBP @ 3054' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 2: Treated w/1539 gal 15% HCL acid & fraced w/35,878# 100 mesh & 290,031# 40/70 On 9/19/15, MIRUSU. CO after frac, drilled out CBPs @ 3054', 3510', 3970' & 4019 landed ESP on 2-7/8" 6.5# L-80 tbg @ 2674'. Released completion rig on 9/23/15. Bottom Hole @ 354' FNL & 2304' FEL Sec 18. Spud Date: 8/20/14	106'-3432' w/1-0.42" spf. Total 29 holes. Arizona sand in slick water. Spotted 500 '30'-3012' w/1-0.42" spf. Total 33 holes. Arizona sand in slick water. 2', & CO to PBTD4650'. On 9/23/15, and belief.
Set 5-1/2" CBP @ 3510' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 3 Treated w/1408 gal 15% HCL acid & fraced w/29,756# 100 mesh & 283,822# 40/70 gal 15% HCL for next frac stage. Set 5-1/2" CBP @ 3054' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 2' Treated w/1539 gal 15% HCL acid & fraced w/35,878# 100 mesh & 290,031# 40/70 On 9/19/15, MIRUSU. CO after frac, drilled out CBPs @ 3054', 3510', 3970' & 4019 landed ESP on 2-7/8" 6.5# L-80 tbg @ 2674'. Released completion rig on 9/23/15. Bottom Hole @ 354' FNL & 2304' FEL Sec 18. Spud Date: 8/20/14 Drilling Rig Release Date: 8/28/14 I hereby certify that the information above is true and complete to the best of my knowledge SIGNATURE Mike Pippin TITLE Petroleum Engineer - Age Type or print name Mike Pippin	106'-3432' w/1-0.42" spf. Total 29 holes. Arizona sand in slick water. Spotted 500 730'-3012' w/1-0.42" spf. Total 33 holes. Arizona sand in slick water. 3', & CO to PBTD4650'. On 9/23/15, and belief.
Set 5-1/2" CBP @ 3510' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 3:Treated w/1408 gal 15% HCL acid & fraced w/29,756# 100 mesh & 283,822# 40/70gal 15% HCL for next frac stage.Set 5-1/2" CBP @ 3054' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 2'Treated w/1539 gal 15% HCL acid & fraced w/35,878# 100 mesh & 290,031# 40/70On 9/19/15, MIRUSU. CO after frac, drilled out CBPs @ 3054', 3510', 3970' & 4019Ianded ESP on 2-7/8" 6.5# L-80 tbg @ 2674'. Released completion rig on 9/23/15.Bottom Hole @ 354' FNL & 2304' FEL Sec 18.Spud Date:8/20/14Drilling Rig Release Date:8/28/14I hereby certify that the information above is true and complete to the best of my knowledgeSIGNATUREMile Ward MarkTITLEPetroleum Engineer - Age	106'-3432' w/1-0.42" spf. Total 29 holes. Arizona sand in slick water. Spotted 500 730'-3012' w/1-0.42" spf. Total 33 holes. Arizona sand in slick water. 3', & CO to PBTD4650'. On 9/23/15, and belief.
Set 5-1/2" CBP @ 3510' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 3 Treated w/1408 gal 15% HCL acid & fraced w/29,756# 100 mesh & 283,822# 40/70 gal 15% HCL for next frac stage. Set 5-1/2" CBP @ 3054' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 2' Treated w/1539 gal 15% HCL acid & fraced w/35,878# 100 mesh & 290,031# 40/70 On 9/19/15, MIRUSU. CO after frac, drilled out CBPs @ 3054', 3510', 3970' & 4019 landed ESP on 2-7/8" 6.5# L-80 tbg @ 2674'. Released completion rig on 9/23/15. Bottom Hole @ 354' FNL & 2304' FEL Sec 18. Spud Date: 8/20/14 Drilling Rig Release Date: 8/28/14 I hereby certify that the information above is true and complete to the best of my knowledge SIGNATURE Mike Pippin TITLE Petroleum Engineer - Age Type or print name Mike Pippin	106'-3432' w/1-0.42" spf. Total 29 holes. Arizona sand in slick water. Spotted 500 730'-3012' w/1-0.42" spf. Total 33 holes. Arizona sand in slick water. 3', & CO to PBTD4650'. On 9/23/15, and belief.