| Form 3160-5 (August 2007) | | UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGENING ARTESIA DISTRICT ARTESIA DISTRICT Y NOTICES AND REPORTS ON WELLS 1 9 2015 | | TION | FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010 | | | |
|--|--|--|---|--|---|--|--|--|
| _ | | | | 5. | Lease Serial No. NMLC065680 | | | |
| Do not use this form for proposals to drill or to reducer abandoned well. Use form 3160-3 (APD) for such propos | | | | | If Indian, Allottee of | or Tribe Name | | |
| su | IBMIT IN TRI | PLICATE - Other instru | ctions on reverse side. | 7 | If Unit or CA/Agree | ement, Name and/or No. | | |
| 1. Type of Well Gas Well Other | | | | 8. Well Name and No. KEOHANE FEDERAL 2 | | | | |
| 2. Name of Operator ENDURANCE RI | Contact: | PEGGY REDMAN nduranceresoucesllc.com | 9. | 9. API Well No. 30-015-20594 | | | | |
| 3a. Address 203 WEST WALI MIDLAND, TX 7 | | UITE 1000 | 3b. Phone No. (include area code) Ph: 432-242-4680 |) 1 | 10. Field and Pool, or Exploratory SHUGART | | | |
| | ., R., M., or Survey Description | n) | 1 | 11. County or Parish, and State | | | | |
| Sec 23 T18S R3 | 30FWL | | EDDY CC | | DUNTY, NM | | | |
| 12. C | HECK APPI | ROPRIATE BOX(ES) T | O INDICATE NATURE OF N | NOTICE, REP | ORT, OR OTHE | R DATA | | |
| , TYPE OF SUBM | TYPE OF SUBMISSION | | | | TYPE OF ACTION | | | |
| □ Notice of Intent | | 🗖 Acidize | 🗖 Deepen | Production | (Start/Resume) | □ Water Shut-Off | | |
| - | | Alter Casing | Fracture Treat | Reclamation | , na | 🗖 Well Integrity | | |
| 🛛 Subsequent Rep | port | Casing Repair | New Construction | Recomplet | e | Other | | |
| Final Abandonment Notice | | Change Plans | 🛛 Plug and Abandon | 🗖 Temporari | ly Abandon | | | |
| | | Convert to Injection | Plug Back | 🗖 Water Disp | oosal | | | |
| following completion | n of the involved | operations. If the operation r | esults in a multiple completion or reco | Required subset ompletion in a new | interval, a Form 316 | 50-4 shall be filed once | | |
| testing has been com determined that the s 7/10/2015 MI&RI 2000 psi at roll or on paraffin 10' fro xylene. RIH with charges. POH wi on paraffin. POH circulate 140 bbl: mill past tight spo RIH with open er to pass 1080' wit | pleted. Final Al site is ready for f U Basic Ener ver. Pull on tu om surface. F 40' string sho ith 64 joints tu I, tools caked s. with hot oil ot in casing a nded tubing to th minimal rot | bandonment Notices shall be fi inal inspection.) gy. POH with rods. Atten ubing, tubing stuck. RIH v RIH with paraffin knife, ur of 2138' and stacked out. Jbing. RIH with swage, d in paraffin. RIH with mul er. SD for weekend. Pick t 600'. Drop 5' and tag, u o fish. Cannot pass 1080 ation. Tag fish at 2016' f | esults in a multiple completion or reco iled only after all requirements, include only after all requirements, include the with wireline to free point. Stace hable to make headway with kr Pull up to 2000' from surface, irill collars and jars. Tag at 600 le shoe, string mill and jars, rev c up tapered mill, string mill and inable to get past. Call BLM. O of from surface. POH and pick to rom surface. POH with tubing. for orders. Perforate 50' above a down casing @ one bpm at 1 | ompletion in a new ling reclamation, h Pressure up to sked out hife and set off ', beat down verse d jars, urders to up mule shoe, a BIH with oup A | ave been completed, | and the operator has AMATION -29-16 nosing of the well b | | |
| testing has been com determined that the s 7/10/2015 MI&RI 2000 psi at roll or on paraffin 10' fro xylene. RIH with charges. POH wi on paraffin. POH circulate 140 bbl: mill past tight spo RIH with open er to pass 1080' wit | pleted. Final Al site is ready for f U Basic Ener ver. Pull on tu om surface. F 40' string sho ith 64 joints tu I, tools caked s. with hot oil ot in casing a mded tubing to th minimal rot yuide, able to from surface. | bandonment Notices shall be fi inal inspection.) gy. POH with rods. Atten ubing, tubing stuck. RIH with 2138' and stacked out. ubing. RIH with swage, d in paraffin. RIH with mul er. SD for weekend. Pick t 600'. Drop 5' and tag, u o fish. Cannot pass 1080 ation. Tag fish at 2016' ft pass at 1080'. Call BLM POH. Test injection rate For ENDURAN Committed to AFMSS for | esults in a multiple completion or reco iled only after all requirements, includ npt to establish injection rate. F with wireline to free point. Stac hable to make headway with kr Pull up to 2000' from surface, irill collars and jars. Tag at 600 le shoe, string mill and jars, rev c up tapered mill, string mill and inable to get past. Call BLM. O ' from surface. POH and pick to rom surface. POH with tubing. | ompletion in a new ling reclamation, h Pressure up to ked out nife and set off ', beat down verse d jars, up mule shoe, a RIH with pup A e fish at 300 psi. RIH with in pup A e fish at 300 psi. RIH with Stop Si. at a 300 psi. RIH with a fish at a 300 psi. RIH with a fish at a fish at a 300 psi. RIH with a fish at a | ave been completed, L M C L / L J M C L / L J M C L / able ccepted as to pl iability under bo urface restoration ystem | and the operator has AMATION -29-16 | | |
| testing has been com determined that the s 7/10/2015 MI&RI 2000 psi at roll or on paraffin 10' fro xylene. RIH with charges. POH wi on paraffin. POH circulate 140 bbl: mill past tight spo RIH with open er to pass 1080' wit joint and cut lip g 2015' and 1965' 14. I hereby certify that Name (<i>Printed/Typed</i>) | pleted. Final Al inte is ready for f U Basic Enern ver. Pull on tu om surface. F 40' string shu ith 64 joints tu I, tools caked s. with hot oil ot in casing a nded tubing to th minimal rot guide, able to from surface. | andonment Notices shall be fi inal inspection.) gy. POH with rods. Atten ubing, tubing stuck. RIH with rot 2138' and stacked out. ubing. RIH with swage, d in paraffin. RIH with mul er. SD for weekend. Pick t 600'. Drop 5' and tag, u o fish. Cannot pass 1080 ation. Tag fish at 2016' fi pass at 1080'. Call BLM POH. Test injection rate For ENDURAN Committed to AFMSS fo SIRGO III | esults in a multiple completion or reco iled only after all requirements, includ npt to establish injection rate. F with wireline to free point. Stac nable to make headway with kr Pull up to 2000' from surface, irill collars and jars. Tag at 600 is shoe, string mill and jars, rec up tapered mill, string mill and inable to get past. Call BLM. O from surface. POH and pick to rom surface. POH with tubing. for orders. Perforate 50' above a down casing @ one bpm at 1 #313111 verified by the BLM We ICE RESOURCES LLC, sent to to processing by LINDA DENNIS Title ENGIN | ompletion in a new ling reclamation, h Pressure up to ked out hife and set off ', beat down verse d jars, up mule shoe, a RIH with pup A e fish at 300 psi. RIH w still Information S the Carlsbad STON on 09/09/2 EER | ave been completed, L M C L / L J M C L / L J M C L / able ccepted as to pl iability under bo urface restoration ystem | and the operator has AMATION -29-16 | | |
| testing has been com determined that the s 7/10/2015 MI&RI 2000 psi at roll or on paraffin 10' fro xylene. RIH with charges. POH wi on paraffin. POH circulate 140 bbl: mill past tight spo RIH with open er to pass 1080' wit joint and cut lip g 2015' and 1965' 14. I hereby certify that | pleted. Final Al site is ready for f U Basic Ener ver. Pull on tu om surface. F 40' string sho ith 64 joints tu I, tools caked s. with hot oil to tin casing a mded tubing to th minimal rot guide, able to from surface. | bandonment Notices shall be fi inal inspection.) gy. POH with rods. Atten ubing, tubing stuck. RIH with 2138' and stacked out. ubing. RIH with swage, d in paraffin. RIH with mul er. SD for weekend. Pick t 600'. Drop 5' and tag, u o fish. Cannot pass 1080 ation. Tag fish at 2016' fi pass at 1080'. Call BLM POH. Test injection rate For ENDURAN Committed to AFMSS fo SIRGO III | esults in a multiple completion or reco iled only after all requirements, include mpt to establish injection rate. F with wireline to free point. Stac hable to make headway with kr Pull up to 2000' from surface, Irill collars and jars. Tag at 600 le shoe, string mill and jars, rev c up tapered mill, string mill and inable to get past. Call BLM. O of from surface. POH and pick to rom surface. POH with tubing. for orders. Perforate 50' above e down casing @ one bpm at 1 #313111 verified by the BLM We ICE RESOURCES LLC, sent to to for processing by LINDA DENNIS Title ENGIN Date 08/18/2 | ompletion in a new ling reclamation, h Pressure up to sked out hife and set off ', beat down verse d jars, up mule shoe, a RIH with pup A e fish at 300 psi. RIH with be Carlsbad STON on 09/09/2 EER | ave been completed, L M C L/ L J M C L/ L J M C L/ L J M C L/ able ccepted as to pl in face restoration wrface restora | and the operator has AMATION -29-16 | | |
| testing has been com determined that the s 7/10/2015 MI&RI 2000 psi at roll or on paraffin 10' fro xylene. RIH with charges. POH wi on paraffin. POH circulate 140 bbl: mill past tight spo RIH with open er to pass 1080' wit joint and cut lip g 2015' and 1965' 14. I hereby certify that Name (<i>Printed/Typed</i>) | pleted. Final Al inte is ready for f U Basic Enern ver. Pull on tu om surface. F 40' string shu ith 64 joints tu I, tools caked s. with hot oil ot in casing a nded tubing to th minimal rot guide, able to from surface. | bandonment Notices shall be fi inal inspection.) gy. POH with rods. Atten ubing, tubing stuck. RIH with 2138' and stacked out. ubing. RIH with swage, d in paraffin. RIH with mul er. SD for weekend. Pick t 600'. Drop 5' and tag, u o fish. Cannot pass 1080 ation. Tag fish at 2016' fi pass at 1080'. Call BLM POH. Test injection rate For ENDURAN Committed to AFMSS fo SIRGO III | esults in a multiple completion or reco iled only after all requirements, includ npt to establish injection rate. F with wireline to free point. Stac nable to make headway with kr Pull up to 2000' from surface, irill collars and jars. Tag at 600 is shoe, string mill and jars, rec up tapered mill, string mill and inable to get past. Call BLM. O from surface. POH and pick to rom surface. POH with tubing. for orders. Perforate 50' above a down casing @ one bpm at 1 #313111 verified by the BLM We ICE RESOURCES LLC, sent to to processing by LINDA DENNIS Title ENGIN | ompletion in a new ling reclamation, h Pressure up to sked out hife and set off ', beat down verse d jars, up mule shoe, a RIH with pup A e fish at 300 psi. RIH with be Carlsbad STON on 09/09/2 EER | ave been completed, L M C L/ L J M C L/ L J M C L/ L J M C L/ able | and the operator has AMATION 29-16 ugging of the well b ond is retained until on is completed. | | |
| testing has been com determined that the s 7/10/2015 MI&RI 2000 psi at roll or on paraffin 10' fro xylene. RIH with charges. POH wi on paraffin. POH circulate 140 bbl: mill past tight spo RIH with open er to pass 1080' wit joint and cut lip g 2015' and 1965' 14. I hereby certify that Name (<i>Printed/Typed</i>) | pleted. Final Al inte is ready for f U Basic Enern ver. Pull on tu om surface. F 40' string shu ith 64 joints tu I, tools caked s. with hot oil ot in casing a nded tubing to th minimal rot guide, able to from surface. | bandonment Notices shall be fi inal inspection.) gy. POH with rods. Atten ubing, tubing stuck. RIH with 2138' and stacked out. ubing. RIH with swage, d in paraffin. RIH with mul er. SD for weekend. Pick t 600'. Drop 5' and tag, u o fish. Cannot pass 1080 ation. Tag fish at 2016' fi pass at 1080'. Call BLM POH. Test injection rate For ENDURAN Committed to AFMSS fo SIRGO III | esults in a multiple completion or reco iled only after all requirements, include mpt to establish injection rate. F with wireline to free point. Stac hable to make headway with kr Pull up to 2000' from surface, Irill collars and jars. Tag at 600 le shoe, string mill and jars, rev c up tapered mill, string mill and inable to get past. Call BLM. O of from surface. POH and pick to rom surface. POH with tubing. for orders. Perforate 50' above e down casing @ one bpm at 1 #313111 verified by the BLM We ICE RESOURCES LLC, sent to to for processing by LINDA DENNIS Title ENGIN Date 08/18/2 | ompletion in a new ling reclamation, h Pressure up to ked out nife and set off ', beat down verse d jars, orders to up mule shoe, a RIH with pup A e fish at 300 psi. RIH w state Carlsbad STON on 09/09/2 EER | ave been completed, L M C L/ L J M C L/ L J M C L/ L J M C L/ able | and the operator has AMATION -29-16 | | |
| testing has been com determined that the s 7/10/2015 MI&RI 2000 psi at roll or on paraffin 10' fro xylene. RIH with charges. POH wi on paraffin. POH with circulate 140 bbls mill past tight spo RIH with open er to pass 1080' witi joint and cut lip g 2015' and 1965' 14. I hereby certify that Name (<i>Printed/Typed</i> Signature | pleted. Final Al inte is ready for f U Basic Ener- ver. Pull on tu om surface. F 40' string sho ith 64 joints tu I, tools caked s. with hot oil of in casing a inded tubing to the minimal rot guide, able to from surface. the foregoing is (Electronic 1) (Electronic 1) (Electronic 2) (Electronic 2) (E | bandonment Notices shall be fi inal inspection.) gy. POH with rods. Atten ubing, tubing stuck. RIH with RIH with paraffin knife, ur of 2138' and stacked out. ubing. RIH with swage, d in paraffin. RIH with mul er. SD for weekend. Pickt 600'. Drop 5' and tag, u o fish. Cannot pass 1080 ation. Tag fish at 2016' fi pass at 1080'. Call BLM POH. Test injection rate Strue and correct. Electronic Submission i For ENDURAN Committed to AFMSS for SIRGO III Submission) THIS SPACE F | esults in a multiple completion or reco iled only after all requirements, includ mpt to establish injection rate. F with wireline to free point. Stac hable to make headway with kr Pull up to 2000' from surface, Irill collars and jars. Tag at 600 le shoe, string mill and jars, rev c up tapered mill, string mill and nable to get past. Call BLM. O ' from surface. POH and pick to rom surface. POH with tubing. for orders. Perforate 50' above a down casing @ one bpm at 1 #313111 verified by the BLM We ICE RESOURCES LLC, sent to to processing by LINDA DENNIS Title ENGIN Date 08/18/2 'OR FEDERAL OR STATE Title | ompletion in a new ling reclamation, h Pressure up to ked out nife and set off ', beat down verse d jars, orders to up mule shoe, a RIH with pup A e fish at 300 psi. RIH ill Information S the Carlsbad STON on 09/09/2 EER | ave been completed, L M C L/ L J M C L/ L J M C L/ L J M C L/ able | and the operator has AMATION 29-16 ugging of the well b ond is retained until on is completed record 20 | | |

** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED **

•

•

Additional data for EC transaction #313111 that would not fit on the form

32. Additional remarks, continued

.

tubing to 2000' from surface, spot 25 sacks cement. Pull up hole to 1053', close BOP, hold psi. WOC. RIH and tag cement at 1850'. POH. RIH to 700' from surface, spot 90 sacks cement to surface. Cut off wellhead below ground level and install dry hole marker. Well plugged and abandoned 7/28/2015.

1