

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
OMB NO. 1004-0135
Expires: July 31, 2010**SUNDRY NOTICES AND REPORTS ON WELLS**
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.*5. Lease Serial No.
NMNM0560353

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on reverse side.7. If Unit or CA/Agreement, Name and/or No.
NMNM126412X

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other8. Well Name and No.
BENSON DELAWARE UNIT 14

2. Name of Operator

CHI OPERATING INCORPORATED

Contact: PAM CORBETT

E-Mail: pamc@chienergyinc.com

9. API Well No.

30-015-37333-00-S1

3a. Address

MIDLAND, TX 79702

3b. Phone No. (include area code).

Ph: 432-685-5001

Fx: 432-687-2662

10. Field and Pool, or Exploratory
BENSON-DELAWARE

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 12 T19S R30E NWNW 480FNL 370FWL

11. County or Parish, and State

EDDY COUNTY, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input checked="" type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

CHI Operating, Inc. intends to convert the Benson Delaware Unit #14 to an injection well.

Procedure is attached.

Accepted for record
NMOC**NM OIL CONSERVATION**
ARTESIA DISTRICT
OCT 19 2015**SEE ATTACHED FOR
CONDITIONS OF APPROVAL**

14. I hereby certify that the foregoing is true and correct.	
Electronic Submission #281223 verified by the BLM Well Information System For CHI OPERATING INCORPORATED, sent to the Carlsbad Committed to AFMSS for processing by CATHY QUEEN on 06/22/2015 (15CQ0398SE)	
Name (Printed/Typed) CLIF MANN	Title FIELD SUPERVISOR
Signature (Electronic Submission)	Date 11/24/2014

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By <u>CHARLES NIMMER</u>	Title <u>PETROLEUM ENGINEER</u>	Date <u>10/12/2015</u>
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		Office <u>Carlsbad</u>

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ****

Benson Delaware Unit #14

API # 30-015-37333

Eddy Co., NM

Convert To Water Injection

DIRECTIONS: From intersection of Hwy 360 & Co. Rd. 222, take Co. Rd 222 approx. 12 miles. Turn left/west on Co. Rd 250/blacktop. Go approx 2.5 miles, go through cattle guard in backtop. Turn left (south) on lease rd. Go approx. .8 mile, turn right just past injection station. Go approx .2 mile, turn left at fork for approx. .6 mile. Turn right approx .2 mile, left approx .2 mile, right approx .2 mile, left approx .4 mile to Munchkin Fed #4 location, continue straight (south) to location.

History/Pertinent Info

Elevation: GL: 3469'

KB: 3481'

Completed: 5/26/10

Tbg Head:

Casing: 8 5/8"
5 1/2"

32 # J-55
15.5 # J-55

set @ 2045' Circ cement
set @ 5230' Circ cement

TD: 5256'

PBTD: 5118'

DV Tool: 3668'

Perfs: 4510'-4534'

4762'-4767', 4779'-4784', 4790'-4800', 4818'-4822', 4833'-4876', 4891'-4904'
4974'-4978', 5022'-5027', 5044'-5046', 5054'-5058', 5070'-5075'

Remarks:

Benson Delaware Unit #14

API # 30-015-37333

Eddy Co., NM

Convert To Water Injection

Project Engineer: Cord Painter

Cell: (325) 792-7255

Recommended Procedure

Note: Deliver 20 Jts 2 7/8" tbg to location to supplement prod tbg for cleanout.

1. MIRU pulling unit. POOH laying down with rods and pump. ND WH. NU BOP.
2. PU tbg as needed and RIH with tbg to tag fill (PBTD is 5118', EOT is ~4514', Btm Pf is 5,075').
3. Estimate and record fill depth.
4. Determine if cleanout is necessary.

If cleanout IS necessary:

5. POOH standing back with tbg, laying down pumping BHA.
6. PU & RIH with sand bailer on tbg. CO well to PBTD (5118'). POOH laying down sand bailer and tbg.

If cleanout IS NOT necessary:

7. POOH laying down tbg and pumping BHA.
8. RIH w/ 5 1/2" x 2 7/8" Arrowset 1X Big Bore packer on 2-7/8" 6.5# J-55 IPC tubing setting packer +/- 100' above top perf. Load backside w/ packer fluid.
9. Pressure test backside as per BLM requirements.
10. Connect injection system to well. Begin water injection.

Benson Delaware Unit #14
 API # 30-015-37333
 Eddy Co., NM

Convert To Water Injection

MECHANICAL DATA

Type Tubular	OD in	ID in	Drift in	Wt. #/ft	Grd	Conn.	Depth ft	Burst psi	Tensile Mlbs.	TOC ft	Cap. bbl/Ft
Surface Casing											
Intermediate Casing	8 5/8	7.921	7.796	32	J-55	STC	2045	3930	372	Surf	
Production Casing	5 1/2	4.95	4.825	15.5	J-55	LTC	5230	4810	247.0	Surf	.0238
Production Tubing	2 7/8"	2.441	2.347	6.5	J-55	8 RD EUE		7260	99.66		.00579
Inj Tbg	2 7/8" IPC										
2 7/8" x 5 1/2" annulus											

* - Assumed

GL = 3469'

KB = 3481'

PBTD = 5118'

TUBING HEAD: 11" 5k X 7 1/16" 5k

CURRENT WELLBORE SCHEMATIC		LEASE: Benson Delaware Unit			WELL NO. 14			
DATE: 6/22/2010		OPER: Chi Energy			API 30-015-37333			
		LOCATION: 480 FNL 370 FWL SEC 12 19S 30E EDDY CO., NM						
		TD 5,256'	PBD 5,118'	KB 3,481'	DF 3,480'			
		COD	DOD	GL 3,469'				
		CASING/TBG:	DEPTH	CMT	ID	DRIFT	BURST	TENS
		INTER. 8 5/8" 32 #J-55 STC	2,045'	CIRC	7.921	7.796	3,930	372.0
		PROD. 5 1/2" 15.5# J-55 LTC	5,230'	CIRC	4.95	4.825	4,810	217.0
		LINER						
		TBG 2 7/8" J-55			2.441	2.347	7,260	99.66
PERFS:								
4510-34' 2 SPF 6/15/10								
4762-67', 4779-84', 4790-4800', 4818-22', 4833-76', 4891-4904' 2 SPF 6/7/10								
4974-78', 5022-27', 5044-46', 5054-58', 5070-75' 2 SPF 5/26/10								
TUBING BREAKDOWN					ROD BREAKDOWN			
Tbg Hd 7 1/16" 5k Slip-Type					1 1/4" X 26' PR W/14' PRL			
130 JTS 2 7/8"					2,2,4,6,8 X 7/8" SUBS			
TAC					47- 7/8" STL RODS			
8 JTS 2 7/8"					121- 3/4" STL RODS			
SN					10- 7/8" STL RODS			
4' PS					8- 1 5/8" KBARS			
1 JT 2 7/8"					1' LIFT SUB			
MA					2 1/2"X1 1/2"X 16' RXBC PUMP			
					1 1/2" X 12' GA			
					AS OF 6/22/10			
					PUMP SET @-4477'			
ART. LIFT								
UNIT	Sentry 320D				SPM	8.5	RT	100%
MOTOR	Torque Master 25 hp 324T 1100 rpm				SL	120	Cond	Fair
Available SL's: 84, 102, 120								
NOTES								
Chem: ?? Injected into FL								
UNCONFORMITY								
4510-34' 2 SPF 6/15/10								
MIKE, NOVEMBER & OSCAR								
4762-67', 4779-84', 4790-4800', 4818-22', 4833-76', 4891-4904' 2 SPF 6/7/10								
PAPA & MUNCHKIN								
4974-78', 5022-27', 5044-46', 5054-58', 5070-75' 2 SPF 5/26/10								

PROPOSED WELLBORE SCHEMATIC		LEASE: Benson Delaware Unit		WELL NO. 14																																				
DATE: 8/24/2014		OPER: Chi Energy		API 30-015-37333																																				
		LOCATION: 480 FNL 370 FWL SEC 12 19S 30E EDDY CO., NM																																						
		TD 5,256'	PBD 5,118'	KB 3,481'	DF																																			
		COD	DOD	GL 3,469'																																				
		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>CASING/TBG:</th> <th>DEPTH</th> <th>CMT</th> <th>ID</th> <th>DRIFT</th> <th>BURST</th> <th>TENS</th> </tr> </thead> <tbody> <tr> <td>INTER. 8 5/8" 32 #J-55 STC</td> <td>2,045'</td> <td>CIRC</td> <td>7.921</td> <td>7.796</td> <td>3,930</td> <td>372.0</td> </tr> <tr> <td>PROD. 5 1/2" 15.5# J-55 LTC</td> <td>5,230'</td> <td>CIRC</td> <td>4.95</td> <td>4.825</td> <td>4,810</td> <td>217.0</td> </tr> <tr> <td>LINER</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>TBG 2 7/8" J-55</td> <td></td> <td></td> <td>2.441</td> <td>2.347</td> <td>7,260</td> <td>99.66</td> </tr> </tbody> </table>				CASING/TBG:	DEPTH	CMT	ID	DRIFT	BURST	TENS	INTER. 8 5/8" 32 #J-55 STC	2,045'	CIRC	7.921	7.796	3,930	372.0	PROD. 5 1/2" 15.5# J-55 LTC	5,230'	CIRC	4.95	4.825	4,810	217.0	LINER							TBG 2 7/8" J-55			2.441	2.347	7,260	99.66
CASING/TBG:	DEPTH	CMT	ID	DRIFT	BURST	TENS																																		
INTER. 8 5/8" 32 #J-55 STC	2,045'	CIRC	7.921	7.796	3,930	372.0																																		
PROD. 5 1/2" 15.5# J-55 LTC	5,230'	CIRC	4.95	4.825	4,810	217.0																																		
LINER																																								
TBG 2 7/8" J-55			2.441	2.347	7,260	99.66																																		
		PERFS:																																						
		4510-34' 2 SPF 6/15/10 4762-67', 4779-84', 4790-4800', 4818-22', 4833-76', 4891-4904' 2 SPF 6/7/10 4974-78', 5022-27', 5044-46', 5054-58', 5070-75' 2 SPF 5/26/10																																						
		TUBING BREAKDOWN		ROD BREAKDOWN																																				
		Tbg Hd 7 1/16" 5k Slip-Type ~142 jts 2 7/8" J-55 IPC 5 1/2" x 2 7/8" Arrowset 1X Big Bore packer PKR SET @ ~4,460'																																						
		ART. LIFT																																						
		UNIT		SPM	RT																																			
		MOTOR		SL	Cond																																			
		NOTES																																						
		UNCONFORMITY 4510-34' 2 SPF 6/15/10 MIKE, NOVEMBER & OSCAR 4762-67', 4779-84', 4790-4800', 4818-22', 4833-76', 4891-4904' 2 SPF 6/7/10 PAPA & MUNCHKIN 4974-78', 5022-27', 5044-46', 5054-58', 5070-75' 2 SPF 5/26/10																																						

Conditions of Approval

Chi Operating Incorporated
Benson Delaware Unit - 14, API 3001537333
T19S-R30E, Sec 12, 480FNL & 370FWL
October 12, 2015

1. Subject to like approval by the New Mexico Oil Conservation Division.
2. Before casing or a liner is added, replaced, or repaired prior BLM approval of the design is required. Use notice of intent Form 3160-5.
3. Surface disturbance beyond the existing pad shall have prior approval.
4. A closed loop system is required. The operator shall properly dispose of drilling/circulating contents at an authorized disposal site. Tanks are required for all operations, no excavated pits.
5. Functional H₂S monitoring equipment shall be on location.
6. 2000 (2M) Blow Out Prevention Equipment to be used. All BOPE and workover procedures shall establish fail safe well control. Blind ram(s) and pipe ram(s) designed to close on all workstring diameters used is required equipment. A manual BOP closure system (hand wheels) shall be available for use regardless of BOP design. Function test the installed BOPE to 500 psig when well conditions allow. Related equipment, (choke manifolds, kill trucks, gas vent or flare lines, etc.) shall be employed when needed for reasonable well control requirements.
7. All waste (i.e. trash, salts, chemicals, sewage, gray water, etc.) created as a result of work over operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area. Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.
8. **Perform a charted casing integrity test** of 1200 psig. Document the pressure test on a one hour full rotation calibrated (within 6 months) recorder chart registering within 25 to 85 per cent of its full range. Verify all annular casing vents are plumbed to the surface and open during this pressure test. **Call BLM 575-200-7902 and arrange for a BLM witness of that pressure test.** Include a copy of the chart in the subsequent sundry for this workover.
9. **Provide BLM with an electronic copy (Adobe Acrobat Document) cement bond log record from 4410' taken with 0 psig casing pressure. The CBL may be attached to a pswartz@blm.gov email.**
10. Submit a (BLM Form 3160-5 subsequent report (daily reports) via BLM's Well Information System; <https://www.blm.gov/wispermits/wis/SP> (email pswartz@blm.gov for instructions) describing all wellbore activity and Mechanical Integrity Test. Include the date(s) of the well work, and the setting depths of installed equipment: internally corrosive protected tubing, tubing on/off equipment just above the packer, and an in line tubing check valve below the

packer or between the on/off tool and packer. The setting depths and descriptions of each are to be included in the subsequent sundry. File intermediate Form 3160-5 within 30 days of any interrupted workover procedures and a complete workover subsequent sundry.

11. Submit the BLM Form 3160-4 **Recompletion Report** within 30 days of the date all BLM approved procedures are complete.
12. Workover approval is good for 90 days (completion to be within 90 days of approval). A legitimate request is necessary for extension of that date.

Well with a Packer - Operations

- 1) Conduct a Mechanical Integrity Test of the tubing/casing annulus after a tubing, packer or casing seal is established.
- 2) The minimum test pressure should be 500 psig for 30 minutes or 300 psig for 60 minutes, with a minimum 200 psig differential between tubing and casing pressure (at test time) but no more than 70% of casing burst pressure as described by Onshore Order 2.III.B.1.h. (The tubing or reservoir pressure may need to be reduced). Verify all annular casing vents are plumbed to surface and those valves open to the surface during this pressure test. An alternate method for a BLM approved MIT is to have the fluid filled system open to atmospheric pressure and have a loss of less than five barrels in 30 days witnessed by a BLM authorized officer.
- 3) Document the pressure test on a one hour full rotation chart recorder (calibrated within the last 6 months) registering within 25 to 85 percent of its full range. Greater than 10% pressure leakoff will be viewed as a failed MIT. Less than 10% pressure leak-off will be evaluated site specifically and may restrict injection approval.
- 4) Make arrangements 24 hours before the test for BLM to witness. In Eddy County email Paul R. Swartz pswartz@blm.gov or phone 575-200-7902, if there is no response, 575-361-2822. If no answer, leave a voice mail or email with the API#, workover purpose, and a call back phone number
- 5) Use of tubing internal protection, tubing on/off equipment just above the packer, a profile nipple, and an in line tubing check valve below the packer or between the on/off tool and packer is a "Best Management Practice". The setting depths and descriptions of each are to be included in the subsequent sundry.
- 6) **Submit the original subsequent sundry with three copies to BLM Carlsbad.**
- 7) Compliance with a NMOCD Administrative Order is required, submit documentation of that authorization.
 - a) Approved injection pressure compliance is required.
 - b) If injection pressure exceeds the approved pressure you are required to reduce that pressure and notify the BLM within 24 hours.
 - c) When injection pressure is within 50 psig of the maximum pressure, install automation equipment that will prevent exceeding that maximum. Submit a subsequent report (Sundry Form 3160-5) describing the installed automation equipment within 30 days.

- 8) Unexplained significant variations of rate or pressure to be reported within 5 days of notice.
- 9) The casing/tubing annulus is required to be monitored for communication with injection fluid or loss of casing integrity. A BLM inspector may request verification of a full annular fluid level at any time.
- 10) Maintain the annulus full of packer fluid at atmospheric pressure. **Installation of equipment that will display continuous open to the air packer fluid level above the casing vent is required.**
- 11) Notify the BLM's authorized officer ("Paul R. Swartz" <pswartz@blm.gov>, cell phone 575-200-7902) **before injection begins** to arrange for approval of the annular monitoring system.
- 12) Loss of packer fluid above five barrels per month indicates a developing problem. Notify BLM Carlsbad Field Office, Petroleum Engineering within 5 days.
- 13) A suggested format for monthly records documenting that the casing annulus is fluid filled is available from the BLM Carlsbad Field Office.
- 14) Gain of annular fluid pressure requires notification within 24 hours. Cease injection and maintain a production casing pressure of Opsia. Notify the BLM's authorized officer ("Paul R. Swartz" <pswartz@blm.gov>, cell phone 575-200-7902). If there is no response phone 575-361-2822.
- 15) Submit a (BLM Form 3160-5 subsequent report (daily reports) via BLM's Well Information System; <https://www.blm.gov/wispermits/wis/SP> (email pswartz@blm.gov for operator setup instructions) describing all wellbore activity and Mechanical Integrity Test as per item 1) above. Include the date(s) of the well work, and the setting depths of installed equipment: internally corrosive protected tubing, tubing on/off equipment just above the packer. The setting depths and descriptions of each are to be included in the subsequent sundry.
- 16) A request for increased wellhead pressures is to be accompanied by a step rate test. PRIOR to a Step Rate Test BLM – CFO is requiring a Notice of Intent.

Access information for use of Form 3160-5 "Sundry Notices and Reports on Wells"

NM Fed Regs & Forms - http://www.blm.gov/nm/st/en/prog/energy/oil_and_gas.html

§ 43 CFR 3162.3-2 Subsequent Well Operations.

§ 43 CFR 3160.0-9 (c)(1) Information collection.

§ 3162.4-1 (c) Well records and reports.