Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED OMB No. 1004-0137 Expires: July 31, 2010

BUREAU OF LAND MANAGEMENT				5. Lease Serial No.
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.				LC 028772 B
				6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE – Other instructions on page 2				7, If Unit or CA/Agreement, Name and/or No.
1. Type of Well				
Oil Well Gas Well Other				8. Well Name and No.
2. Name of Operator				Dunn B Federal 8
Breitburn Operating LP				9. API Well No.
3a. Address 3b. Phone No. (include area code)				30-015-01834
1401 McKinney St., Suite 2400, Houston, TX 77010 713 - 634 - 4696				10. Field and Pool, or Exploratory Area
TX 77010 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				⊣
66 0 FSL, 1980 FEL				Artesia 11. County or Parish, State
Sec. 12, T. 18S,E 28E, NMP	H Unit Letter 1			Eddy, New Mexico
	· .	ES) TO INDICATE NA	TURE OF NOTICE RI	EPORT, OR OTHER DATA
TYPE OF SUBMISSION	THO I III I BOX	EB) TO INDICATE WA	TYPE OF ACTION	El OKI, OK OTTEK DATA
THE OF SOBIMISSION	<u> </u>			
Notice of Intent	∐ Acidize	Deepen	Production (Start/Resu	·
	Alter Casing	Fracture Treat	Reclamantion	Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomplete	Other
Final Abandonment Notice	Change Plans	Plug and Abandon	Temporarily Abandon	
	Convert to Injection	Plug Back	Water Disposal	
Pressured up to 800 psi. PO Tagged plug @ 2048'. POH. to 500 psi for 10 minutes. Po and spotted 25 sx cement @ Saenz w/ BLM). WOC. Tag 11/12/15 Tagged plug @ 25 WOC. Tagged plug @ 30'. S	H w/ packer. RIH Pressured tested OH. Perf'd csg @ 770-621. POH. W ged plug @ 610'. 2. POH. ND BOP Spotted 15 sx @ 3' t off wellhead. W	I open ended. Spotte casing. Holes in cas. 720'. Set packer @ 5 VOC. No Tag. Re-sp POH. Perf'd csg @ 5 Spotted 40 sx cemen 0 ft to surface. Rigge elded on "Above Gr	d 25 sx @ 2200-2051 ing from 440 to surf- 520. Pressured up to otted 30 sx cement w 550'. Spotted 55 sx co at @ 252 to suuface. ed down moved off. 1	5 RIH w/7" packer and set @ 2080. 1, (per Jim Amos w/BLM) WOC. 2 ace. Set Packer @ 520'. Pressured up 500 psi. 11/11/15 RIH open ended 2 2% CACL @ 770-591 (per Jose 2 ement @ 550-222. POH. WOC. 3 Set packer @ 10 ft. Sqzpd 25 sx. 3 11/13/15 Moved in welder and 3 cker". Backfilled cellar. Removed
	- 117	AL REPORT.	riON.	Accepted for record
	NM (OIL CONSERVAT		NMOCD
RECLANIAT	ION G	DEC 1 4 2015	Accepted as to pl Liability under be Surface restoration	ugging of the well bore. and is retained until an is completed.
		RECEIVED		,
14. I hereby certify that the foregoing is t	rue and correct.)		*	
Name (Printed/Typed)			7	_^_
Jeanie McMillan	*	Title		
Signature Aldrie Mc	Millar	Date	11-16-2	1975 LEPTED FUR RECU
	THIS SPACE	E FOR FEDERAL (OR STATE OFFICE	USE
Approved by	· · · · · · · · · · · · · · · · · · ·		Title	Date) F.C. 9 2015
Conditions of approval, if any, are attached the applicant holds legal or equitable title applicant to conduct operations thereon.				1 Para

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department on agree of the United NAGEMENT States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

CARLSBAD FIELD OFFICE