

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-015-29460

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

001796

7. Lease Name or Unit Agreement Name

Poker Lake Unit

8. Well Number 127

9. OGRID Number

260737

10. Pool name or Wildcat

SWD: Delaware

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other SWD

2. Name of Operator

BOPCO, LP

3. Address of Operator

PO Box 2760 Midland, TX 79702

4. Well Location

Unit Letter L : 4980 feet from the South line and 660 feet from the West lineSection 02 Township 25S Range 30E NMPM County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐CLOSED-LOOP SYSTEM ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☒CASING/CEMENT JOB ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

BOPCO, LP submits this sundry notice to report P&A of referenced well. Procedure is as follows:

12/02/2015 - 12/05/15

MIRU PU. ND WH & NU BOP and function test. Release 5-1/2" Loc-Set Pkr @ 4473'; POH and LD pkr and tbg. Clean out fill to 6010' PBTD. RIH w/CIBP to 5836' and set. RIH w/cmt ret to 5543' and set. Sting into retainer, tested csg to 500 psi (good). Bull head 45 bbls Poly Gel plug into formation.

12/06/15

Sting into ret @ 5543'. Mix and pump 45 bbls Poly Plug Clear Gel.

12/07/15

Sting into ret @ 5543' pressure test to 500#, bled to 400# in 30 sec, held. Sting out of ret. Pump 40 bbls salt wtr gel mud & 25 sxs 'C' on cmt ret.

12/08/15

RIH w/tbg, tag TOC @ 5208'. Displace w/ 20sxs salt gel mud, PUH to 4050, spot 50 sxs 'C'. PUH WOC. Tag TOC @ 3665'.

12/09/15

Pump 120 sxs 'C' @ 1639'. WOC. Tag @ 739'. Pump 20 sxs 'C' 100' to surf. RDMO. Dig out WH, make cut off on WH & anchors. Weld plate on well. Set dry hole marker and clean location. Well P&A.

Spud Date:

Rig Release Date:

Approved for plugging of well bore only.
Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.oecd.state.nm.us/oecd.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Sr. Regulatory AnalystDATE 12/11/2015Type or print name Tracie J CherryE-mail address: tjcherry@basspet.comPHONE: 432/528-8977

For State Use Only

APPROVED BY:

TITLE

DATE

Conditions of Approval (if any):

Submit Subsequent C-103