

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-43419
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Journey 12 B2MP Fee
8. Well Number 1H
9. OGRID Number 14744
10. Pool name or Wildcat Malaga; Bone Spring North 42800
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 2975 GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Mewbourne Oil Company

3. Address of Operator
PO Box 5270, Hobbs NM 88241

4. Well Location

Unit Letter M : 470 feet from the North line and 285 feet from the West line
Section 12 Township 24S Range 28E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
2975 GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/15/15.. TD 12 1/4" hole @ 2599'. Ran 2599' of 9 3/4" 40# & 36# J55 & N80 LT&C csg. Cemented with 650 sks Lite Class C (35:65:4) with additives. Mixed @ 12.5 /g w/ 2.19 yd. Tail w/200 sks Class C Neat. Mixed @ 14.8/g w/1.32 yd. Plug down @ 11:00 PM
12/15/15. Circ 155 sks cement to pit. WOC. Set wellhead slips w/110k#. Tested csg spool pack-off to 1500#. At 11:30 AM 12/16/15, tested csg to 2500# for 30 minutes, held OK. Drilled out with 8 3/4" bit.

NM OIL CONSERVATION
ARTESIA DISTRICT

Spud Date: 12/12/15

Rig Release Date:

JAN 07 2016

RECEIVED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Regulatory DATE 12/30/15

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905
For State Use Only

APPROVED BY: [Signature] TITLE Dr. J. Spewison DATE 1/15/16
Conditions of Approval (if any):