

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Oil Cons.  
N.M. DIV-Dist. 2  
1301 W. Grand Avenue  
Artesia, NM 88210

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Nearburg Producing Company

3. Address and Telephone No.

3300 North "A" St., Bldg. 2, Ste. 120, Midland, TX 79705

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit H, 1980' FNL & 660' FEL, Sec. 31, T-19-S, R25-E

5. Lease Designation and Serial No.

NMNM 0659176

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Dagger Draw 31 Fed. Co

9. API Well No.

30-015-28434

10. Field and Pool, or Exploratory Area

N Dagger Dr u/Penn

11. County, Parish, State

Eddy County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☐ Subsequent Report  
☒ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other \_\_\_\_\_
- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

6-05-03 Rig up unit.

6-06-03 POOH w/ RBP (9-5/8") & spot 150 sx @ 5760' (plug okayed by Jim Amos w/ B.L.M.).

6-09-03 Tag cmt. plug @ 5496', mud up w/ 150 bbls. Spot 100 sx cmt. @ 5496'.

6-10-03 POOH w/ tbg. @ 3500', mud up w/ 120 bbls. Spot 45 sx cmt. @ 3500', POOH w/ tbg. @ 2250', spot 40 sx cmt., POOH w/ tbg. @ 1165' spot 50 sx cmt. w/ 2% CaCl & WOC for 4 hrs. Tag plug @ 1086', mud up w/ 80 bbls., add 25 sx cmt. to plug. Spot 25 sx cmt. to surface.

Cut off wellhead, install dry hole marker, clean location, & RDMO.

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

**APPROVED**

JUN 26 2003

LES BABYAK  
PETROLEUM ENGINEER

14. I hereby certify that the foregoing is true and correct

Signed

Title Agent

Date 6-10-03

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: