

	UNITED STATE PARTMENT OF THE I		0	FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010	
	UREAU OF LAND MANA	AGEMENT V	arlsbad.	LAN APP	
CFB 1 Do not use thi	s form for proposals to	ORTS ON WELLS o drill or to re-enter an PD) for such proposals.		that AlOGRODITibe Name	
abandoned wel	1. Use form 3160-3 (AP	D) for such proposals.	0. II k		
RESUBMIT IN TRI	PLICATE - Other instru	ctions on reverse side.	7. If U	nit or CA/Agreement, Name and/or No	
 Type of Well Gas Well Oth 	ler			8. Well Name and No. PINTAIL 23 FEDERAL COM 2	
2. Name of Operator Contact: CIMAREX ENERGY COMPANY OF CO-Mail: DEYLER		DAVID A EYLER @MILAGRO-RES.COM		Well No. 015-35757-00-S1	
3a. Address 202 S CHEYENNE AVE SUITE 1000 TULSA, OK 74103.4346				ld and Pool, or Exploratory TTONWOOD DRAW	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description		n)	11. Co	11. County or Parish, and State EDDY COUNTY, NM	
Sec 23 T25S R26E SWSW 1250FSL 660FWL			ED		
17 CHECV ADDI		O INDICATE NATURE OF 1	NOTICE REPORT		
	VOLVIA LE DOY(E3) 10	U INDICATE INATUKE OF	NOTICE, KEPUKI		
TYPE OF SUBMISSION	TYPE OF ACTION				
🛛 Notice of Intent	🗂 Acidize	Deepen	Production (Star	rt/Resume) 🔲 Water Shut-Of	
-	Alter Casing	Fracture Treat	Reclamation	🗖 Well Integrity	
Subsequent Report	🗖 Casing Repair	New Construction	🗖 Recomplete	🗖 Other	
Final Abandonment Notice	Change Plans	🛛 Plug and Abandon	□ Temporarily Ab	andon	
	Convert to Injection		U Water Disposal		
If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab	ally or recomplete horizontally k will be performed or provide operations. If the operation re bandonment Notices shall be fi	, give subsurface locations and measure the Bond No. on file with BLM/BL/ esults in a multiple completion or rec.	rred and true vertical dep A. Required subsequent ompletion in a new inter	oths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once	
If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 1) SET 5-1/2" CIBP @ 2,800'; 2) CIRC. WELL W/ PXA FLUID 3) PUMP 45 SXS.CMT. @ 1,8 4) MIX X CIRC. TO SURF. 50 5) DIG OUT X CUT OFF WELL DURING THIS PROCEDURE	Illy or recomplete horizontally rk will be performed or provide operations. If the operation re andonment Notices shall be fi inal inspection.) PUMP 25 SXS.CMT. @ D. 82'-1,584(T/DLWR.,B/S/ SXS.CMT. @ 362'-3'(T/ LHEAD 3' B.G.L.; WELD WE PLAN TO USE THE	, give subsurface locations and measure e the Bond No. on file with BLM/BL/ esults in a multiple completion or rec led only after all requirements, include 2,800'-2,692'(9-5/8"CSG.SHO ALT); WOC X TAG CMT. PLU SALT.13-3/8"CSG.SHOE)	red and true vertical dep A. Required subsequent completion in a new inter ling reclamation, have be DE). G. (400 S. X INSTALL DRY.	val, a Form 3160-4 shall be filed once een completed, and the operator has HOLE MARKER.	
If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 1) SET 5-1/2" CIBP @ 2,800'; 2) CIRC. WELL W/ PXA FLUID 3) PUMP 45 SXS.CMT. @ 1,8 4) MIX X CIRC. TO SURF. 50	Illy or recomplete horizontally rk will be performed or provide operations. If the operation re andonment Notices shall be fi inal inspection.) PUMP 25 SXS.CMT. @ D. 82'-1,584(T/DLWR.,B/S/ SXS.CMT. @ 362'-3'(T/ LHEAD 3' B.G.L.; WELD WE PLAN TO USE THE	, give subsurface locations and measure e the Bond No. on file with BLM/BL/ esults in a multiple completion or rec led only after all requirements, include 2,800'-2,692'(9-5/8"CSG.SHO ALT); WOC X TAG CMT. PLU SALT.13-3/8"CSG.SHOE)	red and true vertical dep A. Required subsequent completion in a new inter ling reclamation, have be DE). G. (400 S. X INSTALL DRY.	ths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once sen completed, and the operator has HOLE MARKER.	
If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 1) SET 5-1/2" CIBP @ 2,800'; 2) CIRC. WELL W/ PXA FLUID 3) PUMP 45 SXS.CMT. @ 1,8 4) MIX X CIRC. TO SURF. 50 5) DIG OUT X CUT OFF WELL DURING THIS PROCEDURE	Illy or recomplete horizontally rk will be performed or provide operations. If the operation re andonment Notices shall be fi inal inspection.) PUMP 25 SXS.CMT. @ D. 82'-1,584(T/DLWR.,B/S/ SXS.CMT. @ 362'-3'(T/ LHEAD 3' B.G.L.; WELD WE PLAN TO USE THE	, give subsurface locations and measure e the Bond No. on file with BLM/BL/ esults in a multiple completion or rec led only after all requirements, include 2,800'-2,692'(9-5/8"CSG.SHO ALT); WOC X TAG CMT. PLU SALT.13-3/8"CSG.SHOE)	A. RECEAMATION C. A. RECEAMATION Mathematical and the second Mathematical and the second Mathematic	ths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once sen completed, and the operator has HOLE MARKER.	
If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 1) SET 5-1/2" CIBP @ 2,800'; 2) CIRC. WELL W/ PXA FLUID 3) PUMP 45 SXS.CMT. @ 1,8 4) MIX X CIRC. TO SURF. 50 5) DIG OUT X CUT OFF WELL DURING THIS PROCEDURE	Illy or recomplete horizontally rk will be performed or provide operations. If the operation re andonment Notices shall be fi inal inspection.) PUMP 25 SXS.CMT. @ D. 82'-1,584(T/DLWR.,B/S/ SXS.CMT. @ 362'-3'(T/ LHEAD 3' B.G.L.; WELD WE PLAN TO USE THE	, give subsurface locations and measure the Bond No. on file with BLM/BL/ esults in a multiple completion or reco led only after all requirements, include 2,800'-2,692'(9-5/8"CSG.SHC ALT); WOC X TAG CMT. PLU SALT_13-3/8"CSG.SHOE)	A. RECEAMATION C. A. RECEAMATION Mathematical and the second Mathematical and the second Mathematic	ths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once sen completed, and the operator has HOLE MARKER.	
If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 1) SET 5-1/2" CIBP @ 2,800'; 2) CIRC. WELL W/ PXA FLUID 3) PUMP 45 SXS.CMT. @ 1,8 4) MIX X CIRC. TO SURF. 50 5) DIG OUT X CUT OFF WELL DURING THIS PROCEDURE	Illy or recomplete horizontally rk will be performed or provide operations. If the operation re andonment Notices shall be fi inal inspection.) PUMP 25 SXS.CMT. @ D. 82'-1,584(T/DLWR.,B/S/ SXS.CMT. @ 362'-3'(T/ LHEAD 3' B.G.L.; WELD WE PLAN TO USE THE	, give subsurface locations and measure the Bond No. on file with BLM/BL/ esults in a multiple completion or reco led only after all requirements, include 2,800'-2,692'(9-5/8"CSG.SHC ALT); WOC X TAG CMT. PLU SALT_13-3/8"CSG.SHOE)	A. RECEAMATION C. A. RECEAMATION Mathematical and the second Mathematical and the second Mathematic	ths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once sen completed, and the operator has HOLE MARKER.	
If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 1) SET 5-1/2" CIBP @ 2,800'; 2) CIRC. WELL W/ PXA FLUII 3) PUMP 45 SXS.CMT. @ 1,8 4) MIX X CIRC. TO SURF. 50 5) DIG OUT X CUT OFF WELL DURING THIS PROCEDURE THE REQUIRED DISPOSAL,	Illy or recomplete horizontally rk will be performed or provide operations. If the operation rr andonment Notices shall be fi inal inspection.) PUMP 25 SXS.CMT. @ D. 182'-1,584(T/DLWR.,B/S/ SXS.CMT. @ 362' -3'(T/ LHEAD 3' B.G.L.; WELD WE PLAN TO USE THE PER OCD RULE 19.15.	, give subsurface locations and measure the Bond No. on file with BLM/BL/ esults in a multiple completion or reco led only after all requirements, include 2,800'-2,692'(9-5/8"CSG.SHC ALT); WOC X TAG CMT. PLU SALT_13-3/8"CSG.SHOE)	A. RECEAMATION C. A. RECEAMATION Mathematical and the second Mathematical and the second Mathematic	ths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once sen completed, and the operator has HOLE MARKER.	
If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 1) SET 5-1/2" CIBP @ 2,800'; 2) CIRC. WELL W/ PXA FLUII 3) PUMP 45 SXS.CMT. @ 1,8 4) MIX X CIRC. TO SURF. 50 5) DIG OUT X CUT OFF WELL DURING THIS PROCEDURE THE REQUIRED DISPOSAL,	Illy or recomplete horizontally rk will be performed or provide operations. If the operation re- andonment Notices shall be fi- inal inspection.) PUMP 25 SXS.CMT. @ D. 82'-1,584(T/DLWRB/S/ SXS.CMT. @ <u>362'-3'(T/</u> LHEAD 3' B.G.L.; WELD WE PLAN TO USE THE PER OCD RULE 19.15.	, give subsurface locations and meass e the Bond No. on file with BLM/BL/ esults in a multiple completion or rec led only after all requirements, includ 2,800'-2,692'(9-5/8"CSG.SHC ALT); WOC X TAG CMT. PLU SALT 13-3/8"CSG.SHOE). ON STEEL PLATE TO CSG E CLOSED-LOOP SYSTEM W 17.	red and true vertical dep A. Required subsequent completion in a new inter- ling reclamation, have be DE). G S. X INSTALL DRY. V A RECEAMATION ATTAC CTCI	oths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once sen completed, and the operator has HOLE MARKER. PROCEDURENTENTS TO HED	
If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 1) SET 5-1/2" CIBP @ 2,800'; 2) CIRC. WELL W/ PXA FLUID 3) PUMP 45 SXS.CMT. @ 1,8 4) MIX X CIRC. TO SURF. 50 5) DIG OUT X CUT OFF WELL DURING THIS PROCEDURE THE REQUIRED DISPOSAL, 14. I hereby certify that the foregoing is	Illy or recomplete horizontally the will be performed or provide operations. If the operation re- andonment Notices shall be fi- inal inspection.) PUMP 25 SXS.CMT. @ D. 82'-1,584(T/DLWR.,B/S/ SXS.CMT. @ 362'-3'(T/ LHEAD 3' B.G.L.; WELD WE PLAN TO USE THE PER OCD RULE 19.15. The and correct. Electronic Submission # For CIMAREX EN	, give subsurface locations and measure the Bond No. on file with BLM/BL/ esults in a multiple completion or reco led only after all requirements, include 2,800'-2,692'(9-5/8"CSG.SHC ALT); WOC X TAG CMT. PLU SALT_13-3/8"CSG.SHOE)	The dand true vertical dep A. Required subsequent completion in a new inter- ting reclamation, have be DE). G. (100 S. X INSTALL DRY. V A RECEAMATION ATTAC CTCI C	The provided and the operator has been completed, and the operator has been completed, and the operator has been completed, and the operator has been completed. The operator has been completed and the operator has been completed and the operator has been completed. The operator has been completed and the operator has been completed and the operator has been completed. The operator has been completed and the operator has been completed and the operator has been completed. The operator has been completed and the operator has been completed and the operator has been completed. The operator has been completed and the operator has been completed and the operator has been completed. Been completed and the operator has been completed and the operator has been completed and the operator has been completed. Been completed and the operator has been completed and the operator has been completed. Been completed and the operator has been completed and the operator has been completed and the operator has been completed. Been completed and the operator has been completed and the operator has been completed. Been completed and the operator has been completed and the operator has been completed. Been completed and the operator has been completed and the operator has been completed and the operator has been completed. Been completed and the operator has been	
If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 1) SET 5-1/2" CIBP @ 2,800'; 2) CIRC. WELL W/ PXA FLUIU 3) PUMP 45 SXS.CMT. @ 1,8 4) MIX X CIRC. TO SURF. 50 5) DIG OUT X CUT OFF WELL DURING THIS PROCEDURE THE REQUIRED DISPOSAL, 14. I hereby certify that the foregoing is	Illy or recomplete horizontally rk will be performed or provide operations. If the operation re- andonment Notices shall be fi- inal inspection.) PUMP 25 SXS.CMT. @ D. 82'-1,584(T/DLWRB/S) SXS.CMT. @ <u>362'-3'(T/</u> LHEAD 3' B.G.L.; WELD WE PLAN TO USE THE PER OCD RULE 19.15. Thue and correct. Electronic Submission from For CIMAREX ENI- mitted to AFMSS for processor	, give subsurface locations and meast e the Bond No. on file with BLM/BL/ esults in a multiple completion or rec led only after all requirements, includ 2,800'-2,692'(9-5/8"CSG.SHC ALT); WOC X TAG CMT. PLU SALT 13-3/8"CSG.SHOE)	red and true vertical dep A. Required subsequent completion in a new inter- ling reclamation, have be DE). G. 4 S. X INSTALL DRY. V A RECEAMATION ATTAC CTCI EE-ATTACHE DE-ATTACHE DE-ATTACHE DE-ATTACHE DE-DE-DE-DE-DE-DE-DE-DE-DE-DE-DE-DE-DE-D	oths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once sen completed, and the operator has HOLE MARKER. PROCEDURENTENTS TO HED DEFOR DEFOR	
If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 1) SET 5-1/2" CIBP @ 2,800'; 2) CIRC. WELL W/ PXA FLUID 3) PUMP 45 SXS.CMT. @ 1,8 4) MIX X CIRC. TO SURF. 50 5) DIG OUT X CUT OFF WELL DURING THIS PROCEDURE THE REQUIRED DISPOSAL, 14. I hereby certify that the foregoing is Com	Illy or recomplete horizontally rk will be performed or provide operations. If the operation re- andonment Notices shall be fi- inal inspection.) PUMP 25 SXS.CMT. @ D. 82'-1,584(T/DLWRB/S) SXS.CMT. @ <u>362'-3'(T/</u> LHEAD 3' B.G.L.; WELD WE PLAN TO USE THE PER OCD RULE 19.15. Thue and correct. Electronic Submission from For CIMAREX ENI- mitted to AFMSS for processor	, give subsurface locations and meass e the Bond No. on file with BLM/BL/ esults in a multiple completion or rec led only after all requirements, includ 2,800'-2,692'(9-5/8"CSG.SHC ALT); WOC X TAG CMT. PLU SALT 13-3/8"CSG.SHOE) ON STEEL PLATE TO CSG E CLOSED-LOOP SYSTEM W 17.	red and true vertical dep A. Required subsequent completion in a new inter- ling reclamation, have be DE). G. 4 S. X INSTALL DRY. V A RECEAMATION ATTAC CTCI EE-ATTACHE DE-ATTACHE DE-ATTACHE DE-ATTACHE DE-DE-DE-DE-DE-DE-DE-DE-DE-DE-DE-DE-DE-D	oths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once sen completed, and the operator has HOLE MARKER. PROCEDURENTENTS TO HED DEFOR DEFOR	
If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 1) SET 5-1/2" CIBP @ 2,800'; 2) CIRC. WELL W/ PXA FLUID 3) PUMP 45 SXS.CMT. @ 1,8 4) MIX X CIRC. TO SURF. 50 5) DIG OUT X CUT OFF WELL DURING THIS PROCEDURE THE REQUIRED DISPOSAL, 14. I hereby certify that the foregoing is Com	Illy or recomplete horizontally k will be performed or provide operations. If the operation re- andonment Notices shall be fi- inal inspection.) PUMP 25 SXS.CMT. @ D. 82'-1,584(T/DLWR.,B/S/ SXS.CMT. @ <u>362'-3'(T/</u> LHEAD 3' B.G.L.; WELD WE PLAN TO USE THE PER OCD RULE 19.15. True and correct. Electronic Submission fi For CIMAREX ENI- mitted to AFMSS for proc EYLER	, give subsurface locations and meass e the Bond No. on file with BLM/BL/ esults in a multiple completion or rec led only after all requirements, includ 2,800'-2,692'(9-5/8"CSG.SHC ALT); WOC X TAG CMT. PLU SALT 13-3/8"CSG.SHOE) ON STEEL PLATE TO CSG E CLOSED-LOOP SYSTEM W 17.	red and true vertical dep A. Required subsequent completion in a new inter- ling reclamation, have be DE). G. 4 S. X INSTALL DRY. V A RECEAMATION ATTAC C.T.CI EE-ATTACHEE Deformation system C.T.CI C.T.	oths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once sen completed, and the operator has HOLE MARKER. PROCEDURENTENTS TO HED DEFOR DEFOR	
If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 1) SET 5-1/2" CIBP @ 2,800'; 2) CIRC. WELL W/ PXA FLUID 3) PUMP 45 SXS.CMT. @ 1,8 4) MIX X CIRC. TO SURF. 50 5) DIG OUT X CUT OFF WELL DURING THIS PROCEDURE THE REQUIRED DISPOSAL, 14. I hereby certify that the foregoing is Name (Printed/Typed) DAVID A E	Illy or recomplete horizontally rk will be performed or provide. operations. If the operation re- andonment Notices shall be fi- inal inspection.) PUMP 25 SXS.CMT. @ D. 182'-1,584(T/DLWR.,B/S) SXS.CMT. @ <u>362'-3'(T/</u> : LHEAD 3' B.G.L.; WELD WE PLAN TO USE THE PER OCD RULE 19.15. The period correct. Electronic Submission # For CIMAREX ENI mitted to AFMSS for prov EYLER Submission)	, give subsurface locations and measu e the Bond No. on file with BLM/BL/ esults in a multiple completion or rec led only after all requirements, includ 2,800'-2,692'(9-5/8"CSG.SHC ALT); WOC X TAG CMT. PLU SALT 13-3/8"CSG.SHOE) ON STEEL PLATE TO CSG E CLOSED-LOOP SYSTEM W 17.	red and true vertical dep A. Required subsequent completion in a new inter- fing reclamation, have be DE). G CDE). G CDE). G CDE). C CDE). C	oths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once sen completed, and the operator has HOLE MARKER. PROCEDURENTENTS TO HED DEFOR DEFOR	
If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 1) SET 5-1/2" CIBP @ 2,800'; 2) CIRC. WELL W/ PXA FLUII 3) PUMP 45 SXS.CMT. @ 1,8 4) MIX X CIRC. TO SURF. 50 5) DIG OUT X CUT OFF WELL DURING THIS PROCEDURE THE REQUIRED DISPOSAL, 14. I hereby certify that the foregoing is Com Name (Printed/Typed) DAVID A E Signature (Electronic S	Illy or recomplete horizontally rk will be performed or provide. operations. If the operation re- andonment Notices shall be fi- inal inspection.) PUMP 25 SXS.CMT. @ D. 182'-1,584(T/DLWR.,B/S) SXS.CMT. @ <u>362'-3'(T/</u> : LHEAD 3' B.G.L.; WELD WE PLAN TO USE THE PER OCD RULE 19.15. The period correct. Electronic Submission # For CIMAREX ENI mitted to AFMSS for prov EYLER Submission)	, give subsurface locations and meass e the Bond No. on file with BLM/BIJ esults in a multiple completion or rec led only after all requirements, includ 2,800'-2,692'(9-5/8"CSG.SHC ALT); WOC X TAG CMT. PLU SALT.13-3/8"CSG.SHOE) ON STEEL PLATE TO CSG CLOSED-LOOP SYSTEM W 17. ACCEPTIC SCIENCE SIGNAL SCORPTON STEEL PLATE TO CSG CLOSED-LOOP SYSTEM W 17. ACCEPTIC SCIENCE SIGNAL SCORPTON STEEL SCORPANE SCORPANE SCORPTON ST	red and true vertical dep A. Required subsequent completion in a new inter- fing reclamation, have be DE). G CDE). G CDE). G CDE). C CDE). C	ths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once sen completed, and the operator has HOLE MARKER. PROCEDURENTENTS TO HED DESCENTIONED DE	
If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 1) SET 5-1/2" CIBP @ 2,800'; 2) CIRC. WELL W/ PXA FLUID 3) PUMP 45 SXS.CMT. @ 1,8 4) MIX X CIRC. TO SURF. 50 5) DIG OUT X CUT OFF WELL DURING THIS PROCEDURE THE REQUIRED DISPOSAL, 14. I hereby certify that the foregoing is Name (Printed/Typed) DAVID A E Signature (Electronic S	Illy or recomplete horizontally the will be performed or provide operations. If the operation re- andonment Notices shall be fi- inal inspection.) PUMP 25 SXS.CMT. @ D. B2'-1,584(T/DLWRB/S/ SXS.CMT. @ <u>362'-3'(T/</u> LHEAD 3' B.G.L.; WELD WE PLAN TO USE THE PER OCD RULE 19.15. THIS SPACE FOR Submission) THIS SPACE FOR THIS SPACE FOR	, give subsurface locations and meass e the Bond No. on file with BLM/BL/ esults in a multiple completion or rec led only after all requirements, includ 2,800'-2,692'(9-5/8"CSG.SHC ALT); WOC X TAG CMT. PLU SALT 13-3/8"CSG.SHOE) ON STEEL PLATE TO CSG E CLOSED-LOOP SYSTEM W 17. ACOMPANS OF SYSTEM W 17. ACOMPANS OF CO, set ERGY COMPANY OF CO, set cessing by PRISCILLA PEREZ of Title AGENT Date 01/07/2 OR FEDERAL OR STATE	red and true vertical dep A. Required subsequent completion in a new inter- fing reclamation, have be DE). G CDE). G CDE). G CDE). C CDE). C	oths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once sen completed, and the operator has HOLE MARKER. PROCEDURENTENTS TO HED DEFOR DEFOR	
If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 1) SET 5-1/2" CIBP @ 2,800'; 2) CIRC. WELL W/ PXA FLUII 3) PUMP 45 SXS.CMT. @ 1,8 4) MIX X CIRC. TO SURF. 50 5) DIG OUT X CUT OFF WELL DURING THIS PROCEDURE THE REQUIRED DISPOSAL, 14. I hereby certify that the foregoing is Com Name (<i>Printed/Typed</i>) DAVID A E Signature (Electronic S	Illy or recomplete horizontally the will be performed or provide operations. If the operation re- andonment Notices shall be fi- inal inspection.) PUMP 25 SXS.CMT. @ D. 182'-1,584(T/DLWRB/S/ SXS.CMT. @ <u>362'-3'(T/</u> LHEAD 3' B.G.L.; WELD WE PLAN TO USE THE PER OCD RULE 19.15. THE PER OCD RULE 19.15. Intervention of the second second Electronic Submission for For CIMAREX ENI mitted to AFMSS for proce EYLER Submission) THIS SPACE For a Approval of this notice doe itable title to those rights in th	, give subsurface locations and meass e the Bond No. on file with BLM/BL/ esults in a multiple completion or rec led only after all requirements, includ 2,800'-2,692'(9-5/8"CSG.SHC ALT); WOC X TAG CMT. PLU SALT 13-3/8"CSG.SHOE) ON STEEL PLATE TO CSG E CLOSED-LOOP SYSTEM W 17. ACCEPTIC LOOP SYSTEM SYSTEM SYSTEM SYSTEM SYSTEM SYSTEM SYSTEM SY	red and true vertical dep A. Required subsequent completion in a new inter- fing reclamation, have be DE). G CDE). G CDE). G CDE). C CDE). C	ths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once sen completed, and the operator has HOLE MARKER. PROCEDURENTENTS TO HED DESCENTIONED DE	

•

** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **





Printed 1/4/2016

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of _ **brine** water. Minimum nine (9) pounds per gallon.

5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. <u>Show date well was plugged.</u>

8. <u>Trash</u>: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.

- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909, 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Linda Denniston Environmental Protection Specialist 575-234-5974

Henryetta Price Environmental Protection Specialist 575-234-5951

Dara Glass Environmental Protection Specialist 575-234-5924

Shelly Tucker Environmental Protection Specialist 575-234-5979