

NM OIL CONSERVATION
ARTESIA DISTRICT
OCT 31 2016

RECEIVED

CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

| |
|---|
| WELL API NO. 30-005-61986 |
| 5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> |
| 6. State Oil & Gas Lease No. |
| 7. Lease Name or Unit Agreement Name Spool SU |
| 8. Well Number 2 |
| 9. OGRID Number 025575 |
| 10. Pool name or Wildcat Pecos Slope; Abo |
| 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3704'GR |

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other P&A

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South Fourth Street, Artesia, NM 88210

4. Well Location
Unit Letter D : 660 feet from the North line and 660 feet from the West line
Section 23 Township 7S Range 25E NMPM Chaves County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/6/16 – Loaded 4-1/2" annulus with 10 bbls and test.

10/7-9/16 – ND wellhead and NU BOP. Tried to release packer, would not move. RIH with 1-11/16" jet cutter and cut tubing at 3625'. RIH with GR/JB. Set 4-1/2" CIBP at 3599'. Tagged CIBP and load. Spotted 25 sx Class "C" cement. WOC.

10/10/16 – Tagged plug at 2630'. Perforated 4 holes at 1555'. Pressured perfs, no pump in. Spotted 25 sx Class "C" cement at 1605'. Calc TOC 1242'. WOC.

10/11/16 – Tagged plug at 1235'. Perforated 4 holes at 890'. Pressured 500 psi, dropped down to 947'. Spotted 25 sx Class "C" cement. WOC. Tagged plug at 690'. Perforated 4 holes at 562'. Pressured perfs to 500 psi, no pump in. Perforated 4 holes at 60'. Pressured to 500 psi, no pump in. RIH to 612'. Loaded hole with 60 sx Class "C" cement to surface. Topped out casing. ND BOP. Dug out cellar and cut off wellhead. Installed dry hole marker and filled cellar. **WELL IS PLUGGED AND ABANDONED.**

Spud Date:

Rig Release Date:

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Form C-103. www.enr.state.nm.us/oecd.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Reporting Supervisor DATE October 27, 2016

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: Shelby L. Bal TITLE COMPLIANCE OFFICER DATE 10/31/2016

Conditions of Approval (if any):