

District I
1625 N. French Dr., Hobbs, NM 88240

District II
1301 W. Grand Ave., Artesia, NM 88210

District III
1000 Rio Brazos Rd., Aztec, NM 87410

District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

NOV 02 2016

WELL API NO. 30-005-63265
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 26233
7. Lease Name or Unit Agreement Name Willow Springs "29" State
8. Well Number 1
9. OGRID Number 149441
10. Pool name or Wildcat Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
Reliance Energy, INC

3. Address of Operator
300 N Marienfield Suite 1100 Midland TX 79701

4. Well Location
Unit Letter N : 660 feet from the South line and 1980 feet from the West line
Section 29 Township 4S Range 25E NMPM County - Chavez

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3,880' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

9-1-16 Notified OCD of move in and rig up.

9-2-16 Set 5-1/2" CIBP @ 3585' on wireline.

9-6-16 RIH tbg, tag, & circulate w/10 # salt gel mud. Spot 25 sx class C @ 3585'-3338'. WOC plug. Tag TOC @ 3348'. Spot 25 sx class C @ 3136'-2834'. Perforate 5-1/2" csg @ 1954'. Squeeze 50 sx @ 1954'-1750'. WOC.

9-7-16 Tag top of cement at 1710'. Perf & sqz 40 sx @ 1600'-1438'. WOC & Tag TOC @ 1420'. Perf & sqz 40 sx @ 913'-751'. WOC & tag TOC @ 760'. Perforate and circulate 30 sx from 60' to surface.

9-8-16 RDMOWSU.

Spud Date:

Rig Release Date:

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plug) which
may be found at OCD Web Page under
Forms: www.enr.state.nm.us/oed.

NOV 16 2016

RECEIVED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Traci Coursey TITLE Engineering Tech DATE 11/1/2016

Type or print name Traci Coursey E-mail address: tcoursey@reimid.com PHONE: 432-683-4816

For State Use Only

APPROVED BY: Robert J. Byrd TITLE COMPLIANCE OFFICER DATE 11/16/16

Conditions of Approval (if any):