

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD Artesia
NM OIL CONSERVATION

ARTESIA DISTRICT

FORM APPROVED
OMB No. 1004-0137
Expires July 31, 2010

DEC 02 2016

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.
NM 1531

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE – Other instructions on page 2.

7. If Unit of CA/Agreement. Name and/or No.

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

8. Well Name and No
FEDERAL "4" COM #4

2. Name of Operator
CHEVRON U.S.A. INC.

9. API Well No
30-015-31579

3a. Address
6301 DEAUVILLE BLVD
MIDLAND, TX 79705

3b. Phone No. (include area code)
(432)687-7279

10. Field and Pool or Exploratory Area
AVALON; BONE SPRING, EAST

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1298' FNL & 660' FEL
SEC 4-21S-R27E

11. Country or Parish, State
EDDY, NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input checked="" type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

1. NOTIFY BLM 24 HRS. BEFORE OPERATIONS.
2. SET CIBP@6,300' AND SPOT 25SX OF CLASS "C" CEMENT FROM 6,300'-6,100'.
3. CIRCULATE WELLBORE WITH MLF.
4. SPOT 25SX OF CLASS "C" CEMENT FROM 5,100'-4,900' (BONE SPRING/SPACER).
5. SPOT 30SX OF CLASS "C" CEMENT FROM 2,780'-2,500' (DEL/SOE).WOC & TAG.
6. PERF AT 691' AND SQUEEZE 175SX OF CLASS "C" CEMENT FROM 691'-SURFACE (SHOE/FR WTR./SURFACE).
7. CLEAN LOCATION, CUT-OFF WELLHEAD, INSTALL DRY HOLE MARKER AND TURN OVER FOR REMEDIATION.

ALL FLUIDS WILL BE IN CLOSED LOOP SYSTEM.

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

Provide C102 to OCD

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)
M. LEE ROARK

Title PROJECT MANAGER

Signature

Date 11/11/2016

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

CURRENT WBD

FEDERAL 4 COM. #4

Well #: 4 St. Lse: NM 1531
Lease: Federal 4 Com.
Field: Avalon; Bone Spring, East
Surf. Loc.: 1298' FNL & 660' FEL
Bot. Loc.:
County: Eddy St.: NM
Status: Shut in

API 30-015-31579
Unit Ltr.: Section: 4
TSHP/Rng: 21S-27E
Unit Ltr.: Section:
TSHP/Rng:
Directions:
Chevno:

Surface Casing

Size: 13 3/8"
Wt., Grd.: 48# J-55
Depth: 655'
Sxs Cmt: 641
Circulate: Yes
TOC: Surface
Hole Size: 17 1/2"

Intermediate Casing

Size: 8 5/8"
Wt., Grd.: 24# J-55
Depth: 2,700'
Sxs Cmt: 400
Circulate: Yes
TOC: Surface
Hole Size: 11"

Size: 5 1/2"
Wt., Grd.: 15.5# J-55
Depth: 6,651'
Sxs Cmt: 822
TOC: 1,100' CBL
Hole Size: 7 7/8"

KB: 3,207.9'

DF:

GR: 3,193'

Ini. Spud: 2/18/2001

Ini. Comp.: 3/17/2001

TUBING:

199 JTS. 2-7/8" 6.50# J-55 6,275'

1 TAC

1 SN

RODS:

1 - 1 1/2"

1 - 7/8"

90 - 7/8" N-54 (D)

151 - 3/4" N-78 (D)

7 - 1 1/2"

1 Pump pump 25-150-R x BC-0-0

Perfs: 6,348'-6,536'(OA)

PBTD: 6,607'

TD: 6,653'

Del 2730
BS 5093

DV too 5523

**BUREAU OF LAND MANAGEMENT
Carlsbad Field Office
620 East Greene Street
Carlsbad, New Mexico 88220
575-234-5972**

**Permanent Abandonment of Federal Wells
Conditions of Approval**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within ninety (90) days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. Notification: **Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.**

3. Blowout Preventers: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. Mud Requirement: Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.

5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. **Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.**

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well.

Show date well was plugged.

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.